MIL-D-80038D
27 January 1986
SUPERSEDING
MIL-D-80038C
4 August 1982

MILITARY SPECIFICATION

DRILLING MACHINE, UPRIGHT, ROUND COLUMN, ELECTRIC MOTOR DRIVEN

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers electric motor driven, round column, hand feed and optional power feed, single and multiple spindle, upright, bench type, and floor type drilling machines with equipment and accessories specified herein.

1.2 Classification. The drilling machines covered by this specification shall be of the following types, styles, and sizes. The type, style and size of the machine to be furnished shall be as specified (see 6.2.1).

Type I - Bench Mounting

Type II - Floor Mounting

Style A - One spindle
Style B - Two spindle
Style C - Three spindle
Style D - Four spindle
Style E - Five spindle
Style F - Six spindle

Size 1 - 1/2" (12.7 mm) drill capacity - 15" (381 mm) swing
Size 2 - 11/16" (17.5 mm) drill capacity - 17" (431.8 mm) swing
Size 3 - 1" (25.4 mm) drill capacity - 20" (508 mm) swing

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSM, Memphis, Tennessee 38114-5297, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this Document or by letter.

AMSC N/A FSC 3413
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents and publications. The following other Government documents and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

U. S. DEPARTMENT OF LABOR

OSHA 2206 - General Industry, OSHA Safety and Health Standards (29 CFR 1910).

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

(Copies of specifications, standards and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issue of the documents which are DoD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issue of documents not listed in the DoDISS shall be the issue of the nongovernment documents which are current on the date of the solicitation.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI B5.1	- T-Slots, Their Bolts, Nuts, Tongues.
ANSI B5.10	- Machine Tapers.
ANSI B11.8	- Drilling, Milling and Boring Machines, Safety Requirements for the Construction, Care and Use.
ANSI/NFPA 79	- Metalworking Machines Tools and Plastics Machinery, Electrical Standard for.

(Application for copies should be addressed to the American National Standards Institute, ATTN: Sales Dept., 1430 Broadway, New York, NY, 10018.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 3951	- Commercial Packaging, Standard Practice for.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or military standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:33Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order (see 6.2.1), a sample shall be subjected to first article inspection (see 4.4 and 6.3).

3.2 Design. The drilling machine shall be new and one of the manufacturer's current models capable of operations in accordance with the requirements herein. The drilling machine shall include all components, parts, and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair.

3.2.1 Measurement systems. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used in the design and construction of the drilling machine. When only one system of measurement is acceptable, the particular system required shall be as specified (see 6.2.1). In this specification, all measurements, dimensions, sizes, and capacities are given in US units. These measurements may be converted to SI units through the use of the conversion factors and methods specified in FED-STD-376.

3.2.1.1 Measuring and indicating device calibrations. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used to graduate measuring and indicating devices such as scales, depth stops, carriage stops, dial indicators, pressure gauges, temperature indicators, and other similar devices. When only one system of graduation is acceptable, the particular graduation required shall be as specified (see 6.2.1). Regardless of the measurement system used, all measuring and indicating devices on the drilling machine shall be graduated in the same system. All feed dials shall have independent zero adjustments and shall be calibrated in such a manner that the last dial graduation progresses into and is continuous with the first dial graduation as the dial is rotated through the zero position.

3.2.2 Reclaimed materials. The drilling machine may contain reclaimed materials provided such materials will not jeopardize the drilling machine's intended use and performance. The reclaimed materials shall have been reprocessed, remanufactured or cycled in a manner which will restore them to the same chemical composition and physical properties as the materials originally selected for use on the drilling machine.

3.2.3 Energy efficiency. The drilling machine and all its applicable components that directly consume energy in normal operation shall be designed and constructed for the highest degree of energy efficiency as governed by the latest developments available within the industry.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

have means for determining fluid level. All oil holes, grease fittings, and filler caps shall be accessible.

3.2.6 Environmental protection. The drilling machine shall be so designed and constructed that, under the operating, service, transportation, and storage conditions described herein, the drilling machine shall not emit materials hazardous to the ecological system as prescribed by Federal, state, or local statutes in effect at the point of installation (see 6.4).

3.2.7 Interchangeability. To provide for replacement of worn parts, all parts shall be manufactured to definite dimensions and tolerances.

3.3 Construction. The drilling machine shall be constructed of parts which are new, without defects, and free of repairs. The structure shall be capable of withstanding all forces encountered during operation of the drilling machine to its maximum rating and capacity without permanent distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free of scale and mismatching. No processes such as welding, peening, plugging, or filling with solder or paste shall be used for reclaiming any defective part.

3.3.2 Welding, brazing, or soldering. Welding, brazing or soldering shall be employed only where specified in the original design. None of these operations shall be employed as a repair measure for any defective part.

3.3.3 Fastening devices. All screws, pins, bolts, and other fasteners shall be installed in a manner to prevent change of tightness. Fastening devices subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently installed.

Source: https://assist.dla.mil -- Downloaded: 202610-23T04:33Z
Check the source to verify that this is the current version before use.

3.3.4 Surfaces. All surfaces shall be clean and free of sand, dirt, fins, sprues, flash, scale, flux, and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer's commercial practice.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), the drilling machine shall be painted in accordance with the manufacturer's commercial practice.

3.3.6 Threads. All threaded parts used on the drilling machine and its related attachments and accessories shall conform to FED-STD-H28 and the applicable "Detailed Standard" section referenced therein.

3.3.7 Dials. All rotating dials or handwheels which are used to position machine axes or for tool movement shall be graduated in increments not larger than 0.001 inch. Dial and handwheel diameters shall be permanently and legibly engraved or etched on a nonglare background with graduation that can be read from the operator's normal position.

3.3.8 Gears. All gears shall be constructed from a material suitable for the intended purpose. All metal gears shall be machined and heat treated by a process that will impart the hardness, surface finish, and toughness that will enable the gear train to transmit full-rated torque to the drive motor without gear damage, failure or premature deterioration and wear.

3.3.9 Electromagnetic interference control. When specified (see 6.2.1), equipment furnished under this specification shall comply with MIL-STD-461. The equipment and subsystems class and the emission and susceptibility requirements shall be as specified.

3.4 Components.

3.4.1 Coolant system. When specified (see 6.2.1), a coolant system shall be provided. The coolant system shall include a sump or reservoir, a power driven pump and all necessary piping. The sump or reservoir shall have sufficient capacity to permit full flow of coolant. The system shall have means for draining and cleaning and shall include a baffle or a strainer which is easily removable for cleaning. Means shall be provided to permit the operator to direct and control the amount of coolant.

3.4.2 Electrical system. Unless otherwise specified (see 6.2.1), the electrical system shall conform to ANSI/NFPA 79. Each drilling machine shall draw all of its electrical power from a single 115/230 volt, single phase, 60 Hz circuit having a safety disconnect switch. Each drilling machine shall have a fused safety disconnect switch or circuit breaker. The machine shall be initially wired for operation on 230 volts. An identified terminal for grounding the machine when it is installed shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

mounted in or near the disconnect switch. The terminal shall be suitable for connecting the size grounding conductor specified in ANSI/NFPA 79 for the disconnect fuse rating.

3.4.2.1 Motors. Motors shall be rated for continuous duty and shall have ball or roller bearings of the sealed and permanently lubricated type. Unless otherwise specified (see 6.2.1), each motor enclosure shall meet the requirements for a dripproof enclosure.

3.4.2.2 Solid state components. Solid state design shall be used throughout for electronic components.

3.4.3 Base. The drilling machine shall have a base. The base shall be an iron or steel casting, ribbed and braced to form a foundation for the entire drilling machine. The top of the base shall have a surface with not less than two through slots or T-slots. The T-slots shall be in accordance with ANSI B5.1. The top of the base surface shall be machine finished flat within a tolerance of ± 0.010 inch. The drilling machine base shall have not less than three mounting pads.

3.4.4 Column. The machine shall have a steel or steel alloy column, securely mounted on the base for the support of the worktable and drillhead assembly. The column shall be round with the exterior surface machine ground for slide adjustment of the worktable and drillhead. The worktable and drillhead shall be clamped to the column by a means that will permit quick repositioning and rigid clamping without distorting the column.

3.4.5 Standard worktable. Unless otherwise specified (see 6.2.1), the machine shall be furnished with a worktable. The worktable shall be an iron or steel casting with a top work surface finished flat to within ± 0.010 inch. The worktable shall have not less than two through slots or T-slots. T-slots shall be in accordance with ANSI B5.1 The worktable shall revolve around the center of the column. The worktable shall be vertically adjustable along the column to any position between the base and drillhead assembly. The worktable shall be manually raised, lowered or rotated on the column by releasing a hand lever locking device.

3.4.5.1 Production table-base. When specified (see 6.2.1), a production type table-base shall be provided in lieu of the base and worktable for the type I machines only. The table-base shall be an iron or steel casting with a top work surface finished flat within a tolerance of ± 0.010 inch. The size of the work surface shall be in accordance with table I. The table-base shall have a coolant trough extending around its periphery with provisions for draining. Appropriate means shall be provided for leveling and securing the table-base to a flat mounting surface.

3.4.6 Drillhead assembly. The machine shall have a drillhead assembly which shall include a drillhead, bracket, quill and spindle assembly, power transmission assembly and motor. The drillhead assembly shall be vertically

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

adjustable on the column and shall also be radially adjustable, 360 degrees about the center or the column.

3.4.6.1 Drillhead. The drillhead shall be a metal casting ribbed and braced to house and support the quill and spindle assembly to maintain tool alignment and drilling performance required herein. The drillhead shall be supported by the column and be provided with a locking device for clamping the head securely in position.

3.4.6.2 Quill and spindle assembly. The quill shall be machine ground to fit the cylindrical portion of the bracket in which it travels. Manual drill feeds shall be accomplished by means of a spoke type feed lever through a rack and pinion gear arrangement. A spring arrangement with tension adjustment shall be provided to retract the quill and spindle assembly when the handwheel is released. Guides shall support and maintain quill alignment through the full range of travel. Not less than two sealed-for-life type ball bearings shall be provided to suspend the spindle free of the quill. The spindle shall have two or more splines at the drive end with the work end designed to accept a tapered socket. Tapers shall be in accordance with ANSI B5.10 and shall be of the size designated in table I.

3.4.6.3 Power transmission assembly. The drilling machine shall be powered by an electric motor mounted on a bracket at the rear of the drillhead. Unless otherwise specified (see 6.2.1), the drive shall be either through a belt and step pulley, belt and gear, all gear or direct motor spindle type drive arrangement. Unless otherwise specified, (see 6.2.1), the number of spindle speeds and the spindle speed range shall be as required by table I. When specified (see 6.2.1), the assembly shall provide infinitely variable spindle speeds throughout the required range. All drive pulleys shall have outside circumferences that are concentric with the drive shafts and shall be balanced to avoid excessive vibration. When a belt driven machine is furnished, provisions for adjusting the belt tension shall be provided.

3.4.6.4 Power feed. When required, the spindle shall be power fed to accomplish feed rates and ranges as specified (see 6.2.1).

3.4.6.5 Depth stop. The machine shall have a depth stop equipped with a positive locking device. The depth stop shall be provided with an indicating scale marked in increments of not more than 1/16 inch.

3.4.7 Illuminating lamp. When specified (see 6.2.1), an illuminating lamp shall be provided. The lamp shall be shielded or recessed and shall be permanently attached to the machine in such a manner as to provide illumination of the workpiece. The bulb of the lamp shall be provided with a heat-resistant guard. The lamp shall have an "ON-OFF" switch, and shall be wired to operate on 115-volt AC.

3.4.8 Multiple spindle machines. The styles B through F machines shall comprise a multiple number of single spindle machines as specified herein,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

mounted on a production type table complete with legs. Legs shall be of sufficient number and distribution to maintain rigidity. Table sizes shall be in accordance with table I for the style required. Each spindle shall operate as an independent unit and each unit shall be interchangeable with each of the other units. When required, the spindle center-to-center distances shall be as specified (see table I) and the base dimensions shall be adjusted accordingly.

3.5 Sizes and capacities. Unless otherwise specified (see 6.2.1), the sizes and capacities of the machine shall meet the requirements of table I for the machine style and size specified.

3.6 Performance. The machine shall be capable of drilling 15 holes of the maximum capacity drill size through 1-inch thick soft cast iron within 20 minutes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

TABLE I - Sizes and capacities.

MACHINE CHARACTERISTICS	REQUIREMENTS					
	Type I			Type II		
	Size 1	Size 2	Size 3	Size 1	Size 2	Size 3
Swing, inches	15	17	20	15	17	20
Drill capacity minimum, inches	1/2	11/16	1	1/2	11/16	1
Centerline of spindle to column face, inches	7-1/2	8-1/2	10	7-1/2	8-1/2	10
Spindle nose to base, minimum, inches	16	16	16	44	38	36
Spindle, tapered hole, Morse number	2	2	3	2	2	3
Spindle speed, minimum number	4	5	5	4	5	5
Spindle speed range, RPM	500-1900	460-2800	280-1500	500-1900	460-2800	290-1500
Spindle diameter, minimum, inches	5/8	13/16	3/4	5/8	13/16	3/4
Quill diameter, minimum, inches	1-3/4	2-1/4	2-3/8	1-3/4	2-1/4	2-3/8
Column wall thickness, minimum, inches	1/8	5/32	1/2	1/8	5/32	1/2
Worktable work surface, length x width, minimum, inches	10 x 9	12 x 14	15x 13	10 x 9	12 x 14	15 x 13
Production table						
Base work surface, length x width, minimum size, inches						
Style A	10 x 10	12 x 10	15 x 13	—	—	—
B	20 x 14	31 x 14	35 x 19	—	—	—
C	38 x 14	46 x 14	70 x 19	—	—	—
D	50 x 14	60 x 14	77 x 19	—	—	—
E	65 x 14	91 x 14	105 x 19	—	—	—
F	74 x 14	91 x 14	105 x 19	—	—	—
Motor, horsepower	1/2	3/4	1	1/2	3/4	1
Multi spindles, center to center, minimum, inches	12	15	17	—	—	—

NOTE: Machine size and capacities shall be not less than the stated requirements of the size ordered nor greater than the requirements of the next larger size shown in above table. When the largest size and capacity machine shown in above table is ordered, the size and capacity of the machine offered shall not exceed the stated requirements by more than 10 percent. When a range is shown, the required performance is from the stated minimum or less to the stated maximum or greater.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

3.7 Alignment tolerances. The machine shall meet the alignment tolerances specified in table II.

TABLE II - Alignment accuracies.

Description	Allowable deviation not more than
Table Flatness	.010 inch
Spindle Taper Runout	
TIR at 1 1/4 inches from face	.002 inch
TIR at 5 inches from face	.005 inch
Spindle (Quill) Travel	
Square with table in 12 inches	.005 inch
Spindle incline toward column	.005 inch
Table Travel Square	
To column in 12 inches	.005 inch

3.8 Standard equipment. Unless otherwise specified (see 6.2.1), the following equipment shall be furnished with each drilling machine:

a. One set of hand tools normally furnished by the manufacturer.

b. One drill chuck for each spindle, 1/2-inch capacity, having arbor taper corresponding to spindle taper for the size machine specified.

3.9 Lubrication chart or plate. Unless otherwise specified (see 6.2.1), a lubrication chart or plate shall be securely attached to the drilling machine. If a chart is furnished, it shall be placed in a transparent plastic folder, or permanently sealed between clear plastic sheets, with suitable means for mounting. The following information shall be furnished on the chart or plate:

Points of lubricant application
Servicing interval
Type of lubricant
Viscosity

3.10 Nameplate. Unless otherwise specified (see 6.2.1), a nameplate shall be securely attached to each drilling machine and contain the infor-

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

mation listed below. If the drilling machine is a special model, the model designation shall include the model of the basic standard machine and a suffix identified in the manufacturer's permanent records. The captions listed may be shortened or abbreviated, provided the entry for each caption is clear as to its identity.

Nomenclature
Manufacturer's name
Manufacturer's serial number
Manufacturer's model designation
Drill capacity _____ inches
Swing _____ inches
Power input (volts, total amps, phase, frequency)
Contract number
National Stock Number or Plant Equipment Code
Date of manufacture
U.S.

3.11 Technical data. When technical data (operating manuals, maintenance manuals, parts catalogs, prints, wiring diagrams, lubrication charts, machine alignment and accuracy test results) is required, it shall be furnished in accordance with the requirements of DD Form 1423. All technical data furnished shall be written in the English language.

3.12 Fungus control. When required (see 6.2.1), fungus proofing shall be specified.

3.13 Workmanship. Workmanship of the drilling machine and accessories shall be equal to that of the manufacturer's current commercial machines of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conform-

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

period.

4.7.2 Alignment tolerance test. Each machine shall be tested to determine that it complies with the alignment tolerance requirements of table II (see 3.7).

4.7.3 Performance tests. The machine shall be tested for conformance with 3.6. Any evidence of overloading, overheating, excessive vibration or deformation of the machine during or after drilling operations shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

4.7.4 Electromagnetic interference control tests. Equipment requiring electromagnetic interference control shall be tested for compliance with 3.3.9.

5. PACKAGING

5.1 Preservation, packing, and marking. Unless otherwise specified, preservation, packing, marking shall be in accordance with ASTM D 3951. When specified (see 6.2.1), level A preservation, level A or level B packing, and marking shall be accomplished in accordance with MIL-M-18058.

6. NOTES

6.1 Intended use. The drilling machines covered by this specification are intended for use in production shops where wide varieties of drilling operations are performed.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Type, style, and size required. (see 1.2).

c. When a first article is required for inspection and approval (see 3.1).

d. If machine is required to be configured in a specific measurement system (US or SI), state required system (see 3.2.1).

e. If measuring and indicating devices are required to be graduated in a specific measuring system (US or SI), state required system (see 3.2.1.1).

f. Additional safety and health requirements, if required (see 3.2.4).

g. Painting, if different (see 3.3.5).

h. If electromagnetic interference control is required, specify the equipment and subsystem class and the emission and susceptibility required (see 3.3.9).

i. Coolant system, if required (see 3.4.1).

j. Electrical system, if different (see 3.4.2).

k. Motor enclosure, if different (see 3.4.2.1).

l. Worktable, if not required (see 3.4.5).

m. If production table base is required for the type I machine (see 3.4.5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

q. [illegible]

r. Illuminating lamp, if required (see 3.4.7).

s. Sizes and capacities, if different (see 3.5).

t. Standard equipment, if different (see 3.8).

u. Lubrication chart, if different (see 3.9).

v. Nameplate, if different (see 3.10).

w. Fungus proofing, if required (see 3.12).

x. First article inspection, if different (see 4.4).

y. Quality conformance inspection, if different (see 4.5).

z. Preservation, packing, and marking, if different (see 5.1).

6.2.2 Contract data requirements. Required technical data (operating manuals, parts lists, wiring diagrams, foundation and anchor bolt plans and acceptance test reports) should be specified on a DD Form 1423, Contract Data Requirements List, incorporated into the contract.

6.3 First article. When a first article is required, the item to be tested should be the first item offered for acceptance under the contract. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.4 Safety and health requirements. Paragraph 3.2.4 requires compliance only with those OSHA requirements that concern the drilling machine itself. It does not require compliance with those OSHA requirements that concern "the drilling machine in its operating environment" such as noise levels, radiation levels, electromagnetic emissions, noxious vapors, air contaminants, and heat. Since OSHA limits the total hazard level of these hazards in the environment (and does not limit the hazard level of individual drilling machines in the environment) the procuring activity is advised to analyze the existing hazard levels in the proposed operating environment, and specify additional requirement that will integrate the new machine into its future operating environment. The machine shall be equipped with all point-of-operation guarding normally furnished as standard on the manufacturer's commercial machine supplied to the commercial market. If specific point-of-operation guarding is required, since the guard configuration is dependent on the size and configuration of the workpieces. The above, and any other additional safety and health requirements should be specified in detail under 6..2.1(f).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes changes.

Custodians:
Army - AL
Navy - SH
Air Force 99

Review activities:
Army - AR
DLA - GS
Navy - YD
Air Force - 84

User activities:
Army - SM
Navy - YD

Preparing activity:
DLA - IP

Project (3413-0134)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-D-80038D	Drilling Machine, Upright, Round Column, Electric Motor Driven

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*:

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T04:33Z
Check the source to verify that this is the current version before use.