INCH-POUND

MIL-G-63445 (AR)
AMENDMENT 6
21 June 1994
SUPERSEDING
AMENDMENT 5
08 February 1991

MILITARY SPECIFICATION

GRENADE, GENERAL PURPOSE, PRACTICE, M75

This amendment forms a part of MIL-G-63445 (AR), dated 2 August 1982, and is approved for use by the US Army Armament, Munitions, and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

2.1.1, under "SPECIFICATIONS": Add:

"MIL-D-70430 Decelerator, Ram Air Parts and Container Assembly"

PAGE 2

2.1.2: Add:

"INSPECTION EQUIPMENT DRAWINGS

9362755 Detonator, Electric, PA526 (XM70)
9345168 Fuze, General Purpose Grenade, M231 (Practice)"

3.2: Delete in its entirety and substitute the following:

"3.2 Components and assemblies. The components and assemblies shall comply with all the requirements specified on drawings 9334151, 9386964 and associated drawings and with all requirements specified in applicable specifications and standards."

3.3: Add "and MIL-D-70430."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:53Z
Check the source to verify that this is the current version before use.

PAGE 3

Add 3.9 as follows:

"3.9 Plastic integrity test. The lid, container P/N 9334146 and smoke, container P/N 9334145 shall be subjected to and pass the plastic integrity test as specified in 4.5.5."

PAGE 4

4.3.1: Add the following:

"Cone, Plastic	9386963	10
Submunition Body, Dummy (Powdered Metal)	9386964	15
Submunition Body Assembly, Dummy (No. 4 S/M)	9386965	10
Tolerance Pad Assembly	9390414	10
Submunition Body, Dummy (Powdered Metal No. 5-9 S/M)	12598684	15".

PAGE 5

TABLE I: Add the following:

"Cone, Plastic (Dwg. 9386963) Examination for defects	10	3.2	4.4.2.4
Submunition Body, Dummy (Powdered Metal) (Dwg. 9386964) Examination for defects	15	3.2	4.4.2.5
Submunition Body Assembly, Dummy (No. 4 S/M) (Dwg. 9386965) Examination for defects	10	3.2	4.4.2.6
Tolerance Pad Assembly (Dwg. 9390414) Examination for defects	10	3.2	4.4.2.8
Submunition Body, Dummy (Powdered Metal No. 5-9 S/M) (Dwg. 12598684) Examination for defects	15	3.2	4.4.2.9"

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

PAGE 7

4.4.2.1: Delete "None Defined" and add Major 101 as follows:

"101	Plastic integrity test	50	---	3.9	4.5.5".

PAGE 9

4.4.2.3, Critical 1: Delete "Arming" and substitute "shear"; Add "(before and after staking)".

Major 102: Delete "0.65%" and substitute "0.40%"

Add Majors 103 and 104 as follows:

"103	Safety collar missing or loose or improperly positioned	0.40%	3.2	Visual
104	Fuze surface adjacent to staking area above top of body assembly	0.40%	3.2	Visual"

Add the following paragraphs:

4.4.2.4 included as (9a).
4.4.2.5 included as (9b).
4.4.2.6 included as (9c).
4.4.2.7 included as (9d).
4.4.2.8 included as (9e).
4.4.2.9 included as (9f).
4.4.2.10 included as (9g).

Source: https://assist.dla.mil -- Downloaded: 20260-23T02:53Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-G-63445 (AR)
AMENDMENT 6

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Cone, Plastic	1 OF 1	9386963
			NEXT HIGHER ASSEMBLY: 9386965

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major	None defined.			
Minor				
201	Outside diameter	0.65%	3.2	Gage
202	Height	0.65%	3.2	Gage
203	Evidence of poor workmanship	0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-G-63445 (AR)
AMENDMENT 6

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Submunition Body, Dummy (Powdered Metal)	1 OF 1	9386964
			NEXT HIGHER ASSEMBLY: 9386965

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Largest outside diameter	0.40%	3.2	Gage
102	Staking height	0.40%	3.2	Gage
Minor				
201	Largest inside diameter	0.65%	3.2	Gage
202	Second largest inside diameter	0.65%	3.2	Gage
203	Smallest outside diameter	0.65%	3.2	Gage
204	Hardness	0.65%	3.2	4.5.4
205	Density	0.65%	3.2	Visual
206	Evidence of poor workmanship	0.65%	3.8	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89

Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-G-63445 (AR)
AMENDMENT 6

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Submunition Body Assembly, Dummy (No. 4 S/M)	1 OF 1	9386965
			NEXT HIGHER ASSEMBLY: N/A

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Plastic cone missing or improperly installed	0.40%	3.2	Visual
Minor				
201	Black band missing	100%	N/A	Visual
202	Evidence of poor workmanship	0.65%	3.8	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-G-63445 (AR)
AMENDMENT 6

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Cover, Plastic	1 OF 1	9386966
			NEXT HIGHER ASSEMBLY: 9386967

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major	None defined.			
Minor				
201	Thickness	0.65%	3.2	Gage
202	Evidence of poor workmanship	0.65%	3.8	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89

Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-G-63445 (AR)
AMENDMENT 6

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Tolerance Pad Assembly	1 OF 1	9390414
			NEXT HIGHER ASSEMBLY: N/A

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Plastic cover missing or improperly installed	0.40%	3.2	Visual
Minor				
201	Evidence of poor workmanship	0.65%	3.8	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89 Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

MIL-G-63445 (AR)
AMENDMENT 6

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Submunition Body, Dummy (Powdered Metal No. 5-9 S/M)	1 OF 1	12598684
			NEXT HIGHER ASSEMBLY: N/A

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Largest outside diameter	0.40%	3.2	Gage
102	Stacking height	0.40%	3.2	Gage
Minor				
201	Largest inside diameter	0.65%	3.2	Gage
202	Smallest outside diameter	0.65%	3.2	Gage
203	Hardness	0.65%	3.2	4.5.4
204	Density	0.65%	3.2	Visual
205	Evidence of poor workmanship	0.65%	3.8	Visual

NOTES:

AMSMC Form 1570b-E, 1 Jul 89

Replaces AMSMC Form 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Lid, Container	1 OF 1	9334416
			NEXT HIGHER ASSEMBLY: 9334144

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined.			
Major				
101	Plastic integrity test	50	3.9	4.5.5
Minor				
201	Evidence of poor workmanship	0.65%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

PAGE 10

Add 4.5.4 as follows:

"4.5.4 Density. The density shall be determined using the comparative weight method (weight in air - weight in distilled water). Compensating factors for air and water temperature shall be used in computing the density."

* 4.5.5: Delete in its entirety and substitute the following:

"4.5.5 Plastic integrity. In preparation for testing the container lid, the container lid shall be bonded to the smoke container (vice versa applies when the smoke container is to be tested, namely the smoke container shall be bonded to the container lid) after the smoke container is filled with 14 ± 1 gram of smoke composition per drawing 9334147. The smoke container assembly shall be completely assembled into an M75 Grenade, except a modified M231 Fuze shall be used. A modified M231 is the same as an M231, except a hole is drilled/milled into the fuze body to allow for external initiation of the M55 detonator in its fully safe position. Instead of staking, the modified M231 shall be secured to the M75 Grenade in such a way that will provide the equivalent retaining force but allows for easy removal of the modified M231 without damaging the grenade.

The complete M75 Grenade shall be conditioned to -50° ± 5°F for 4 hours prior to the test. Within 3 minutes after removal from the conditioning chamber, the modified M231 shall be initiated by dropping an external firing pin (P/N 9345321 for configuration of firing pin tip). Minimum energy required to fire the M55 Detonator is 0.75 inch-ounce. After initiation of the detonator, the smoke container assembly shall be inspected for any evidence of cracks. The lot shall be rejected if any crack occurs as a result of the initiation of the detonator."

PAGE 11

* 6.3: Delete "US Army Armament Research and Development Command, ATTN: DRDAR-QAF-I" and substitute "Armament Research, Development and Engineering Center, US Army Armament, Munitions and Chemical Command, ATTN: SMCAR-QAF-I".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1330-0383)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:53Z
Check the source to verify that this is the current version before use.