MILITARY SPECIFICATION

PLUG TEST, ATOMIC WEAPON

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for the following: (1) one type of dummy warhead plug entitled as Dummy Connector Plug; (2) one type of special purpose fuze test plug entitled as Plug, Special Purpose, Electrical Connector; (3) one type of safing plug entitled as Plug, Safing, Atomic Weapon which is used with the Honest John warhead section.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-E-5272	- Environmental Testing, Aeronautical and Associated Equipment, General Specification For.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-810	- Environmental Test Methods.
MIL-STD-1460	- Soldering of Electrical Connections and Printed Wiring Assemblies, Procedure For.

DRAWINGS

ORDNANCE CORPS

8800706	- Dummy Connector Plug, Warhead Simulator.
8806600	- Bag, Packing for Repair Parts.
8808362	- Container, Packing, Ammunition, for Domestic (CONUS) Shipments of Special Weapons Items, Packing and Marking.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

8813490 - Plug, Special Purpose Electrical Connector.
8813503 - Plug, Safing, Atomic Weapon.
8822032 - Bag, Packing, Ammunition, for Plug, Test, Atomic Weapon.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The plug assemblies shall comply with all requirements specified on the drawing (dwg) 8800706, 8813490 and 8813503, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Circuit resistance. The resistance of each circuit listed in Tables I, II and III, as applicable, shall not exceed the specified value when determined as specified in 4.4.1.

Table I - Circuit Resistance (see dwg 8800706)

From Pin	To Pin	Resistance-Ohms (max)
B	K	0.015
B	N	0.015
B	O	0.015
B	T	0.015
B	c	0.015
C	H	0.015
D	S	0.015
G	Y	0.015
F	L	0.015
k	g	0.015
I	a	0.015

Table II - Circuit Resistance (see dwg 8813490)

From Pin	To Pin	Resistance-Ohms (max)
C	G	0.015
F	T	0.015
Y	Z	0.015

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

Table III - Circuit Resistance (see dwg 8813503)

From Pin	To Pin	Resistance-Ohms (max)
1	13	0.015
2	4	0.015
6	18	0.015
7	19	0.015
14	31	0.015
17	34	0.015

3.5 Insulation resistance. The insulation resistance of each pin to all other pins and ground as listed in Tables IV, V and VI, as applicable, shall be greater than 20 megohms when tested at 500 ± 50 volts direct current (vdc). Testing shall be as specified in 4.4.2.

Table IV - Insulation Resistance (see dwg 8800706)

Pin	Resistance-Megohms (min)
B	20
C	20
D	20
G	20
F	20
kk	20
I	20
Unused Pins (Note 1)	
Ground (Note 2)	

Note 1 - Pins A, E, J, M, P, R, U, V, W, X, Z, b, d, e, f, h and j may be connected together and tested as one pin.
Note 2 - Test fixture ground. Connector shell shall be at ground potential.

Table V - Insulation Resistance (see dwg 8813490)

Pin	Resistance-Megohms (min)
C	20
F	20
Y	20
Unused Pins (Note 1)	20
Ground (Note 2)	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

Note 1 - Pins A,B,D,E,H,I,J,K,L,M,N,O,P,Q,R,S,U,V,W, and X may be connected together and tested as one pin.
Note 2 - Test Fixture ground. Connector shell shall be at ground potential.

Table VI - Insulation Resistance (see dwg 8813503)

Pin	Resistance-Megohms (min)
1	20
2	20
6	20
7	20
14	20
17	20
Unused Pins (Note 1)	20
Ground (Note 2)	

Note 1 - Pins 3, 5, 8, 9, 11, 12, 15, 16, 20-29, 30, 32, 33, 35-53 and 54-62 may be connected together and tested as one pin.
Note 2 - Test fixture ground. Connector shell shall be at ground potential.

3.6 Environmental testing. The plug assemblies shall comply with MIL-STD-810, visual inspection and failure criteria, section 3. The plug assemblies shall also comply with 4.3.3.1 before and after each environmental test. Testing shall be as specified in 4.4.3. Tests shall be conducted in the order specified.

3.6.1 Transportation vibration. The plug assemblies shall withstand transportation vibration at the frequencies, amplitudes, accelerations, and for the time specified in Table VII without evidence of damage such as cracks, chips, separations or loosening of parts, and shall comply with the requirements of 3.4 and 3.5 after being tested as specified in 4.4.3.1.

Table VII

Frequency Range (Hertz)	Double Displacement or Peak g Level ± 5 Percent	Cycle Time to Cover Frequency Range (minutes ± 0.5)	Total Test Time Per Axis (minutes)
10-20-10	± 2 g	3	10
20-50-20	0.036 inch	3	20
50-500-50	± 5 g	3	15

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

3.6.2 Flight vibration. Assembly 8813490 shall withstand vibration over a frequency range 75 to 1000 to 75 Hertz (Hz) at a peak level of 5 g's ± 10 percent and at a temperature of 80 ± 20°F. The vibration shall be applied from a low to a high frequency and returned to a low frequency over a period of 0.9 ± 0.1 minute in each of three mutually perpendicular axes, one of which is in the direction of forward motion (see Figure 1). All circuits in Table II shall be monitored to evidence continuity with not more than 20 microseconds interruption. The plug assembly shall comply with the requirements of 3.4 and 3.5 after being tested as specified in 4.4.3.2.

3.6.3 Transportation shock. The plug assemblies shall withstand shocks of 75 ± 8 g's peak amplitude with a half amplitude duration of 9 ± 3 milliseconds applied three times in each of three mutually perpendicular major axes. The plug assemblies shall comply with the requirements of 3.4 and 3.5 after being tested as specified in 4.4.3.3.

3.6.4 Acceleration. Assembly 8813490 shall withstand without malfunction, acceleration of 50 ± 5 g's for 5 seconds in the direction of forward motion (see Figure 1), and of 21 ± 1 g's for 15 seconds perpendicular to the direction of forward motion. The plug assembly shall comply with the requirements of 3.4 and 3.5 after testing in accordance with 4.4.3.4.

3.6.5 High temperature. The plug assemblies shall withstand exposure to a temperature of 160 ± 5°F without evidence of cracking, peeling or other damage and shall comply with 3.4 and 3.5 when tested as specified in 4.4.3.5.

3.6.6 Low temperature. The plugs shall be protected against frost by mating to a receptacle and shall then withstand exposure to -80 ± 5°F without evidence of cracking, peeling or other damage and shall meet the requirements of 3.4 and 3.5 while at -65 ± 5°F when tested as specified in 4.4.3.6.

3.6.7 Humidity. The plug assemblies shall withstand exposure to a relative humidity of 95 ± 5 percent at temperature cycling from 80 ± 20°F to 160 ± 5°F to 80 ± 20°F without evidence of damage or functional deterioration when tested as specified in 4.4.3.7. Upon completion of this test the plug assemblies shall comply with 3.4 and 3.5.

3.7 Soldering. All soldering shall comply with the requirements specified in MIL-STD-1460.

3.8 Workmanship.

3.8.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.8.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

3.8.3 Burrs. Parts shall be free from burrs.

3.8.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.8.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

3.8.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 3 complete assemblies (see dwgs 8800706, 8813490 and 8813503) for first article testing to the testing facility designated in the invitation for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table VIII. Tests shall be conducted in order specified in Table VIII.

Table VIII

First article inspection and tests

Inspection or Test	Assembly 8800706	Assembly 8813490	Assembly 8813503	Dest	Non-Dest
1. Classification of characteristics (see 4.3.2.1)	X	X	X		X
2. Circuit resistance (see 3.4)	X	X	X		X
3. Insulation resistance (see 3.5)	X	X	X		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

Inspection or Test	Assembly 8800706	Assembly 8813490	Assembly 8813503	Dest	Non-Dest
4. Low temperature (see 3.6.6)	X	X	X		X
5. High temperature (see 3.6.5)	X	X	X		X
6. Humidity (see 3.6.7)	X	X	X		X
7. Acceleration (see 3.6.4)		X			X
8. Transportation shock (see 3.6.3)	X	X	X		X
9. Transportation vibration (see 3.6.1)	X	X	X		X
10. Flight vibration (see 3.6.2)		X			X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Inspection lot formation. All items in each inspection lot shall be from one production line, one shift, one batch of products, one manufacturer of raw material, one manufacturer of components, one production method, and one manufacturing operation. The entire lot shall be submitted as a unit from inspection.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristics table (see Table IX and Table X), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

Table IX
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

Table X
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Plug, safing, atomic weapon: Plug, Special purpose electrical connector; and dummy connector plug, warhead simulator; excluding cover and potting (see dwg 8813503, 8813490 or 8800706 as applicable).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Improper soldering (see 3.7)	Visual
	102. Evidence of poor workmanship (see 3.8)	Visual
	103. Any part missing, loose or damaged	Visual/Manual
	104. Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

4.3.2.1.2 Plug, safing, atomic weapon: Plug, special purpose, electrical connector and dummy connector plug, warhead simulator excluding cover (see dwg 8813503, 8813490, or 8800706 as applicable).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Inadequate potting	Visual
	102. Evidence of poor workmanship (see 3.8)	Visual
Minor:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

4.3.2.1.3 Plug, safing atomic weapon: and dummy connector plug, warhead simulator: (see dwg 8813503, 8800706 as applicable).

Categories		Characteristics	Method of Inspection
Critical:		None defined.	
Major:			
	101.	Wrong connector	Visual
	102.	Deformation of connector sufficient to impair mating	Visual
	103.	Any pin missing (as evidenced by empty hole in insert)	Visual
	104.	Improper location of male contacts	Visual
	*105.	Height of pins (pins of the same diameter must all appear to be within 1/16 inch in height relative to the adjacent pins)	Visual
	106.	Any parts missing, damaged or loose	Visual/Manual
	107.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:			
	201.	Improper ribbon color (8813503 only)	Visual
	202.	Absence of snaps on ribbon (8813503 only)	Visual
	203.	Stamping inadequate or improper	Visual

4.3.2.1.4 Plug, special purpose, electrical connector (see dwg 8813490).

Categories		Characteristics	Method of Inspection
Critical:		None defined.	
Major:			
	**101.	Depth of sockets (female sockets of same diameter must all appear to be within 1/16 inch in depth relative to the adjacent sockets)	Visual
	102.	Any part missing, damaged or loose	Visual/Manual
	103.	Objective evidence relating to material missing or improper (see 3.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

Minor:

201. Chain assembly missing or incomplete.....Visual
202. Inadequate or improper marking on cover.....Visual
203. Set screw missing or loose.....Visual/Manual

4.3.2.1.5 Bag, packing, ammunition for repair parts and adaption kit parts (see dwg 8806600 or 8822032 as applicable).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Wrong size bag	Gage
	102. Bag not sealed	Visual
	103. Air in bag not minimized before sealing	Visual
	104. Marking improper, illegible, smeared, missing or in wrong location	Visual
	105. Packing material visibly wet	Visual
	106. Incorrect or insufficient cushioning material	Visual
	107. Evidence of poor workmanship in packing (see 3.8)	Visual
	108. Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:	None defined.	

4.3.2.1.6 Container, packing, ammunition, for domestic (CONUS) shipments of special weapons items. Packing and marking. (see dwg 8808362).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Marking incorrect, missing, or mislocated	Visual
	102. Packing material visibly wet	Visual
	103. Incorrect or insufficient cushioning material	Visual
	104. Evidence of poor workmanship (see 3.8)	Visual
Minor:	None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

*In the event pins do not appear to be within 1/16 inch in height relative to the adjacent pins, a gage (see 4.3.4.1) shall be used to determine that variation from the normal height. Reject any pin that varies by more than 0.063 inch maximum from the normal pin height of the individual connector. The normal height of the individual connector pins shall be determined by calculating the average height from measurements taken of pins adjacent to the pin that appears to be defective. The forward edge of the connector shall be utilized as the reference for all measurements of pin heights.

**In the event socket inserts do not appear to be within 1/16 inch in depth relative to adjacent sockets, a gage (see 4.3.4.1) shall be used to determine that variation from the normal depth. Reject any insert that varies by more than 0.063 inch maximum from the normal socket depth of the individual connector. The normal depth of the individual connector sockets shall be determined by calculating the average depth from measurements taken of sockets adjacent to thy socket that appears to be defective. The forward edge of the connector shall be utilized as reference surface for all measurements of the socket depths.

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Circuit resistance	Major
b. Insulation resistance	Major
c. Transportation vibration	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Circuit resistance and insulation resistance. Each plug assembly shall be tested in accordance with 4.4.1 and 4.4.2. If any item fails to comply with 3.4 and 3.5, the item shall be rejected and removed form the lot.

4.3.3.2 Transportation vibration. A sample shall be selected at random in accordance with Table XI. The sample shall be tested in accordance with 4.4.3.1. If any item fails to comply with 3.6.1, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

Table XI

Sample sizes for non-destructive testing

Lot Size	Sample Size
2-15	2
16-50	3
51-150	5
151-500	8

over 500 - MIL-STD-105D-Special Inspection Level 3.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions designed or specified by the contractor. The contractor shall obtain approval of such designs, operating instructions and calibration instructions prior to use on the contract from Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-N-I as specified on DI-R-1714 (see 6.1.2).

4.3.4.2 Minor characteristics and tests. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Circuit resistance. The resistance shall be measured with a suitable electrical resistance measuring instrument which has been connected to the specified plug pins.

4.4.2 Insulation resistance. An insulation resistance tester, capable of supplying the required voltage and with which a resistance in megohms can be obtained, shall be used to measure the resistance. The current should be limited to a maximum of 5 milliamperes to protect human life.

4.4.3 Environmental testing (see 3.6).

4.4.3.1 Transportation vibration. The fixture with plug shall be placed in a suitable test chamber. The test item shall be vibrated at the frequencies, amplitudes, temperatures, and for the times specified in Table VII. Following this test the assembly shall be tested as specified in 4.4.1 and 4.4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

4.4.3.2 Flight vibration. Mount the test item in the manner described in 4.4.3.1. Vibrate the item in each of three mutually perpendicular axes with one of these axes along the direction of forward motion. The circuits described in Table II shall be monitored during this test to ensure that no circuit interruptions over 20 microseconds duration are experienced. Following this test, the assembly shall be tested as specified in 4.4.1 and 4.4.2.

4.4.3.3 Transportation shock. Mount the test item in the manner described in 4.4.3. This fixture must be capable of supporting the test item readily in each of three mutually perpendicular axes. The test item shall be subjected to shocks of 75 ± 8 g's with a half amplitude duration of 9 ± 3 milliseconds, three times in each of the three mutually perpendicular axes. Following this test, the assembly shall be tested as specified in 4.4.1 and 4.4.2.

4.4.3.4 Acceleration. Mount the assembly on the centrifuge so that the forward direction of the assembly is oriented in the radial direction of the centrifuge. Rotate centrifuge to produce an acceleration of 50 ± 5 g's in the direction of forward motion (see Figure 1) for 5 seconds minimum. Mount the assembly on the centrifuge so that the direction of forward motion of the assembly is perpendicular to the radial direction of the centrifuge. Rotate centrifuge to produce an acceleration of 21 ± g's in the direction perpendicular to the direction of forward motion of the assembly for a period of 15 seconds minimum. Following this test, the assembly shall be tested as specified in 4.4.1 and 4.4.2.

4.4.3.5 High temperature. The plug assembly shall be placed in a test chamber and the temperature of the chamber shall be raised to 160 ± 5°F. The plug assembly will soak at this temperature for a minimum of 4 hours or until stabilization (see 6.4) is reached, whichever is longer. The plug assembly shall then be tested as specified in 4.4.1 and 4.4.2.

4.4.3.6 Low temperature. The plug assembly shall be placed in the test chamber and the temperature of the chamber shall be lowered to -80 ± 5°F. The plug assembly shall soak at this temperature for a minimum of 4 hours. The chamber temperature shall then be raised to -65 ± 5°F and maintained for an additional 1 hour period or until stabilization (see 6.4) is reached, whichever is longer. While at this stabilized temperature, the plug assembly shall be tested as specified in 4.4.1 and 4.4.2.

4.4.3.7 Humidity. The assembly shall be mated to a connector and placed in a humidity chamber at a temperature of 80 ± 20°F and relative humidity of 95 ± 5 percent. During the first 2 hour period, the temperature shall be gradually raised to 160 ± 5°F. The temperature of 160 ± 5°F shall be maintained during the next 6 hour period. During the following 16 hour period, the temperature in the chamber shall be gradually reduced to 80 ± 20°F. This completes one cycle. The relative

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.

humidity throughout the cycle shall be 95 + 5 percent. The test shall consist of 3 such cycles (72 hours). Upon completion of the 3 cycles, the assembly shall be removed immediately from the test chamber and excessive moisture removed by blowing dry filtered compressed air over the unit for a period of 5 minutes per MIL-E-5272. The assembly shall then be tested as specified in 4.4.1 and 4.4.2.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Level A. The plug assemblies shall be packaged in accordance with dwg 8806600, 8808362 and 8822032 using the specified moisture barrier.

5.1.2 Level C. The plug assemblies shall be packaged in accordance with dwg 8806600, 8808362 and 8822032 except that the moisture barrier may be omitted.

5.2 Packing.

5.2.1 Level A and C. The plug assemblies shall be packed in accordance with dwg 8806600, 8808362 and 8822032.

5.3 Marking. Marking shall be as specified in accordance with dwg 8808362.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when required on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-N-I.

6.4 Temperature stabilization. The temperature is considered stabilized when the greatest peaks (both highest and lowest) continually observed over 5 minutes min. do not exceed the nominal temperature plus tolerance specified.

6.5 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1676 (Rev 2) dated 11 December 1964.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1190-A062

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:22Z
Check the source to verify that this is the current version before use.