MIL-S-48084A (AR)
19 August 1981
SUPERSEDING
MIL-C-48084
1 September 1972

MILITARY SPECIFICATION

STRIKER NUT ASSEMBLY FOR 4.2 INCH AMMUNITION

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification contains requirements not covered by the drawings and provides quality assurance provisions for the fabrication of parts and assembly for the striker nut assembly for use on the 4.2 Inch, HE, M329A2 Cartridge.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

DRAWINGS (See 6.4)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

9257181 - Striker Nut Assembly

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

ASTM Method E-340 - Macroetching Metals and Alloys

(Applications for copies should be addressed to the American Society for Test and Materials, 1916 Race Street, Philadelphia, PA 19103).

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal Agencies).

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on drawing (dwg.) 9257181 and with all requirements specified in applicable specifications and standards.

3.3 Macroetch Test (for metal defects). Parts shall be free from cracks, splits, cold shuts, inclusions, porosity, laminations or similar defects when tested as specified in 4.4.1.

3.4 Workmanship. All parts and assemblies shall be free of burrs, chips, grease, rust, dirt, corrosion products and other foreign matter. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material.

Source: https://assist.dla.mil -- Downloaded: 20260-22T19:12Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. Quality conformance inspection shall be conducted on this item.

4.3 First article inspection. Not required

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, the extrusion lot shall consist of not more than 1000 pounds of extruded stock of the same alloy that has been thermally treated by the same method in the same furnace equipment at the same temperature and time in one unchanged process regardless of the solution heat treatment method utilized. Each extrusion lot representing material that has been solution heat treated after extrusion, must be solution heat treated at the same time in the same furnace using the same temperature and time in that furnace.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48084A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Bar, rod or tubing				NEXT HIGHER ASSEMBLY 9257180
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Macroetch test		100%	3.3	4.5.1
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48084A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8835181
4.4.2.2	Point, Striker				NEXT HIGHER ASSEMBLY 92757181
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length from shoulder to point		0.40%	3.2	Gage
Minor					
201	Total length		0.65%	3.2	Gage
202	Large outside diameter		0.65%	3.2	Gage
203	Small outside diameter		0.65%	3.2	Gage
204	Length of large outside diameter		0.65%	3.2	Gage
205	Radius missing		0.65%	3.2	Visual
206	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48084A (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Plate, Striker		8835180
			NEXT HIGHER ASSEMBLY 9257181

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Thickness		0.65%	3.2	Gage
202	Width of tab at base		0.65%	3.2	Gage
203	Diameter of hole in tab		0.65%	3.2	Gage
204	Outside diameter		0.65%	3.2	Gage
205	Radius of tab		0.65%	3.2	Gage
206	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48084A (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9257180
4.4.2.4	Nut, Striker				NEXT HIGHER ASSEMBLY 9257181
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Minor diameter of thread, max.		0.40%	3.2	Gage
103	Length of thread engagement, min.		0.40%	3.2	Gage
Minor					
201	Perpendicularity of forward face with pitch diameter of thread		0.65%	3.2	Gage
202	Diameter of forward thread relief		0.65%	3.2	Gage
203	Diameter of rear thread relief		0.65%	3.2	Gage
204	Depth of forward thread relief		0.65%	3.2	Gage
205	Diameter of striker plate c'bore		0.65%	3.2	Gage
206	Depth of striker plate c'bore		0.65%	3.2	Gage
207	Depth from forward face to rear thread relief shoulder		0.65%	3.2	Gage
208	Diameter through hole, min.		0.65%	3.2	Gage
209	Depth from rear face to shoulder		0.65%	3.2	Gage
210	Diameter of hole, min.		0.65%	3.2	Gage
211	Rear thread relief missing		0.65%	3.2	Visual
212	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-S-48084A (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Striker Nut Assembly	1 OF 1	9257181
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Striker point extends through striker plate		100%	3.2	Visual/Strightedge
102	Striker point missing		100%	3.2	Visual
103	Striker point insecurely riveted		100%	3.2	Manual
Minor					
201	Striker plate		0.65%	3.2	Visual
202	Lacquer missing from crimps		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T19:12Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Methods of inspection

4.5.1 Macroetch test. Full section macroetch specimens shall be cut from the front and back end of the bar representing the first and last extruded material, respectively, from each individual extrusion billet. Failure to comply with the requirements of 3.3 will require an additional length of discard from the defective extrusion end(s) and testing of additional macroetch specimen(s) taken from the end(s) of the remaining length of extruded material. This procedure must be continued until a sufficient length of the defective extrusion has been discarded and the requirements of 3.3 are met. Suitable identification of each length of extrusion and corresponding macroetch must be maintained until the extruded material is accepted. The specimens shall be macroetched as specified in ASTM Method E-340 except that sodium hydroxide shall be used as the macroetch reagent.

5. PACKAGING

5.1 Packaging and marking. Packing and marking shall be in accordance with Standard MIL-STD-1169.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on the 4.2 Inch, HE, M329A2 Cartridge.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approval. See MIL-A-48078. Submit designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAT-I, Dover, NJ 07801.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1315-A402

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-S-48084A Striker Nut Assembly for 4.2 Inch Ammunition

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT
COMMAND
ATTN: DRDAR-QAT
DOVER, NJ 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:12Z
Check the source to verify that this is the current version before use.