INCH-POUND
MIL-DTL-16377K(SH)
SUPPLEMENT 1
26 May 2023

DETAIL SPECIFICATION

FIXTURES, LIGHTING; AND ASSOCIATED PARTS;
SHIPBOARD USE, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-16377K(SH), dated 26 May 2023.

TABLE I. Specification sheets, numerical listing.

MIL-F-16377/1*	-	Fixtures, Lighting; Incandescent, Detail Lighting for Motors and Generators 50 Watts, 120 Volts, Symbol 126.3
MIL-F-16377/2*	-	Fixtures, Lighting; Fluorescent, Detail Lighting for Water Gages 6 Watts, 120 Volts, 60 Hertz, Symbols 152 and 154
MIL-F-16377/3*	-	Fixtures, Lighting; Fluorescent, Detail Lighting for Water Gages 8 Watts, 120 Volts, 60 Hertz, Symbols 151 and 153
MIL-DTL-16377/4	-	Fixtures, Lighting; Fluorescent and Solid-State Equivalent, Detail Lighting for Secretary Bureau, 8 Watts, 120 Volts, 60 Hertz, Symbols 142.2 and 142.2SSL
MIL-F-16377/5*	-	Fixtures, Lighting; Fluorescent, General Lighting, 15 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 338.1, 338.2, 339.1 and 339.2
MIL-F-16377/6*	-	Fixtures, Lighting; Fluorescent, General Lighting, Directional 16 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 149.4 and 149.5
MIL-DTL-16377/7	-	Fixtures, Lighting; T5 Fluorescent and SSL Equivalent, General Lighting, 16 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 70.3, 70.4, 78.2, 336, 336.1, 70.3SSL, 70.4SSL, 78.2SSL, 336SSL, and 336.1SSL
MIL-DTL-16377/8	-	Fixtures, Lighting; Fluorescent and SSL Equivalent, General Lighting, 20 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 331.1, 331.2, 347.2, 347.3, 331.1SSL, 331.2SSL, 347.2SSL, and 347.3SSL
MIL-DTL-16377/9	-	Fixtures, Lighting; Fluorescent and SSL Equivalent, General Lighting, 24 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 73.3, 73.4, 346.2, 346.3, 73.3SSL, 73.4SSL, 346.2SSL, and 346.3SSL
MIL-DTL-16377/10	-	Fixtures, Lighting; Fluorescent and Solid-State Equivalent, General Lighting, Directional, 32 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 145.4, 145.5, 145.4SSL and 145.5SSL
MIL-DTL-16377/11	-	Fixtures, Lighting; Fluorescent and SSL Equivalent, General Lighting, 40 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 77.4, 77.5, 344.2, 344.3, 77.4SSL, 77.5SSL, 344.2SSL, and 344.3SSL

* Inactive for new design.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:38Z
Check the source to verify that this is the current version before use.

TABLE I. Specification sheets, numerical listing - Continued.

MIL-DTL-16377/12	-	Fixtures, Lighting; Fluorescent and SSL Equivalent, General Lighting, 60 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 333.1, 333.2, 341.1, 341.2, 342.2, 342.3, 333.1SSL, 333.2SSL, 341.1SSL, 341.2SSL, 342.2SSL, and 342.3SSL
MIL-DTL-16377/13*	-	Fixtures, Lighting; Fluorescent, General Lighting, 180 Watts, 120 Volts, 60 Hertz, Dripproof, Symbols 74 and 74.1
MIL-DTL-16377/14	-	Fixtures, Lighting; T5 Fluorescent and SSL Equivalent, General Lighting, 8 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 79.1, 79.2, 80.1, 80.2, 79.1SSL, 79.2SSL, 80.1SSL, and 80.2SSL
MIL-F-16377/15*	-	Fixtures, Lighting; Fluorescent, Detail Lighting for Desks 8 Watts, 120 Volts, 60 Hertz, Symbol 148.2
MIL-DTL-16377/16	-	Fixtures, Lighting; Fluorescent and Solid-State Equivalent, Detail Lighting for Desks, 8 Watts, 120 Volts, 60 Hertz, Symbols 141.2, 150.2, 141.2SSL, and 150.2SSL
MIL-DTL-16377/17	-	Fixtures, Lighting; Fluorescent and Solid-State Equivalent, Detail Lighting for Berths, 8 Watts, 120 Volts, 60 Hertz, Symbols 229.1, 231.1, 232.1, 229.1SSL, 231.1SSL, 232.1SSL, 229.1SSL-USB, 231.1SSL-USB, and 232.1SSL-USB
MIL-F-16377/18*	-	Fixtures, Lighting; Fluorescent, Detail Lighting for Mirrors 15 Watts, 120 Volts, 60 Hertz, Symbols 337 and 340
MIL-DTL-16377/20	-	Fixtures, Lighting, Incandescent and Solid-State Equivalent, General Lighting, 50 Watts, 120 Volts, Dripproof 15 Degrees, Symbols 64.1, 65, 64.1SSL, and 65SSL
MIL-DTL-16377/21	-	Fixtures, Lighting; Incandescent and Solid-State Equivalent, General Lighting, 100 Watts, 120 Volts, Dripproof 15 Degrees, Symbols 89, 90.2, 89SSL, and 90.2SSL
MIL-DTL-16377/23	-	Fixtures, Lighting; Incandescent and Solid-State Equivalent, General Lighting, 200 Watts, 115 Volts, Watertight, Symbols 57, 57.1, 69, 69.1 103, 57SSL, 57.1SSL, 69SSL, 69.1SSL, and 103SSL
MIL-DTL-16377/25	-	Fixtures, Lighting; Incandescent and Solid-State Equivalent, General Lighting, 110 Watts, 120 Volts, Explosionproof, Symbols 48.2, 68.2, 48.2SSL, and 68.2SSL
MIL-DTL-16377/26	-	Fixtures, Lighting; Incandescent and SSL Equivalent, General Lighting, 110 Watts, 120 Volts, Watertight, Symbols 112, 113, 113.1, 112SSL, 113SSL, and 113.1SSL
MIL-DTL-16377/27	-	Fixtures, Lighting; Incandescent and Solid-State Equivalent, General Lighting, 50 Watts, 120 Volts, Watertight, Symbols 92.2, 93.2, 93.4, 93.5, 92.2SSL, 93.2SSL, 93.4SSL, and 93.5SSL
MIL-F-16377/28*	-	Fixtures, Lighting; Incandescent, Detail Lighting for Ammunition Hoist, 50 Watts, 120 Volts, Watertight, Symbol 23.1
MIL-DTL-16377/30	-	Fixtures, Lighting; Incandescent and Solid-State Equivalent, General Lighting for Psychiatric Wards, 100 Watts, 120 Volts, Dripproof 15 Degrees, Symbols 137 and 137SSL

* Inactive for new design.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:38Z
Check the source to verify that this is the current version before use.

TABLE I. Specification sheets, numerical listing - Continued.

MIL-DTL-16377/31	-	Fixtures, Lighting; Incandescent and Solid-State Equivalent, Detail Lighting for Spot Illumination, 6-25 Watts, 120 Volts, Totally Enclosed, Symbols 147.2 and 147.2SSL
MIL-F-16377/32*	-	Fixtures, Lighting; Incandescent, Detail Lighting for Water Gauges, 15 or 25 Watts, 120 Volts, Symbol 134.1
MIL-DTL-16377/33	-	Fixtures, Lighting; Incandescent and Solid-State Equivalent, Detail Lighting for Sightglasses, 6 Watts, 120 Volts, Watertight, Symbols 136.1, 156, 136.1SSL, and 156SSL
MIL-F-16377/34*	-	Fixtures, Lighting, Incandescent, Detail Lighting for Gyro Compass for Submarines, Pressureproof, 15 Watts, 120 Volts, Symbol 335
MIL-F-16377/35*	-	Fixtures, Light, Incandescent, Detail Lighting for Small Boats, 3 Candlepower, 12 to 16 or 24 to 28 Volts, Splashproof, Symbol 310
MIL-DTL-16377/36	-	Fixtures, Lighting; Incandescent and Solid-State Equivalent, General Lighting, 21 Candlepower or 25 Watts, 115 Volts, Watertight, Symbols 95.1, 96.1, 97.1, 98.1, 95.1SSL, 96.1SSL, 97.1SSL, and 98.1SSL
MIL-DTL-16377/38	-	Fixtures, Lighting; Detail Lighting for Hull Numerals, 120 Volts, Watertight, Symbol 304
MIL-DTL-16377/39	-	Fixtures, Lighting; Streamer Type, Detail Lighting for Topside Ship Dress Lighting, Watertight, 120 Volts, Symbol 307
MIL-DTL-16377/40	-	Fixtures, Lighting; Locks, Fluorescent Lamp
MIL-F-16377/41	-	Fixtures, Lighting; Shockmounts, for Lighting Fixtures
MIL-DTL-16377/42	-	Fixtures, Lighting; Filters, Plastic, Tubular Shaped for Fluorescent Lamps
MIL-F-16377/43*	-	Fixtures, Lighting; Filters, Plastic, Roundel Shaped for Lantern
MIL-F-16377/44*	-	Fixtures, Lighting; Ballast, for One 20-Watt T-12 Fluorescent Lamp
MIL-F-16377/45	-	Fixtures, Lighting; Ballast, for One 8-Watt T-5 Fluorescent Lamp
MIL-F-16377/46	-	Fixtures, Lighting; Ballast Box, for One 8-Watt T-5 Fluorescent Lamp, Symbols 514 and 514.1
MIL-F-16377/48	-	Fixtures, Lighting; Filter Assemblies for Desk Lights, Adjustable Red and White Symbol 121.1 and Blue and White Symbol 121.2
MIL-DTL-16377/49	-	Fixtures, Lighting; Extension, Solid-State, 115 Volts, 60 Hertz, Explosionproof and Watertight, Detail Lighting, Shipboard Use, Symbol 306.2SSL
MIL-DTL-16377/52	-	Fixtures, Lighting; Solid-State, Light, Extension, 120 Volts, Explosionproof and Watertight, Symbol 286SSL
MIL-DTL-16377/53	-	Fixtures, Lighting; Light Emitting Diode (LED), Detail Lighting, Lantern, Hand, Portable and Bulkhead-Mounted, Watertight, Symbols 100.2L, 101.2L, and 101.3L
MIL-F-16377/54	-	Fixture, Bracket, Lug Supporting for Hand Lanterns, Symbol 2438
MIL-F-16377/55	-	Fixture, Bracket Assembly, Adjustable for Supporting Hand Lanterns Symbol 2432.1

* Inactive for new design.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:38Z
Check the source to verify that this is the current version before use.

TABLE I. Specification sheets, numerical listing - Continued.

MIL-DTL-16377/56	-	Fixtures, Lighting; 120 Volts, Machine Tool, Portable, Floating Adjustment, Symbol 266.2
MIL-DTL-16377/57	-	Fixtures, Lighting; Fluorescent and SSL Equivalent, General Lighting, 60, 80, and 120 Watts, 120 Volts, 60 Hertz, Dripproof, Symbols 348, 349, 350, 348SSL, 349SSL, and 350SSL
MIL-DTL-16377/58	-	Fixtures, Lighting; Fluorescent, Detail Lighting for Mirrors, 120 Volts, 60 Hertz, Dripproof, Symbols 351, 351.1, 352, 352.1, 351SSL, 351.1SSL, 352SSL, and 352.1SSL
MIL-DTL-16377/59	-	Fixtures, Lighting; Fluorescent and Solid-State Equivalent, Detail Lighting for Step Illumination, 8 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 353, 353.1, 353.2, 353SSL, 353.1SSL, and 353.2SSL
MIL-DTL-16377/60	-	Fixtures, Lighting; Incandescent, Floodlights, 150 Watts, 120 Volts, Dripproof 15 Degrees, Symbols 316 and 317
MIL-DTL-16377/61	-	Fixtures, Lighting; Incandescent and Solid-State Equivalent, Floodlights, 300 Watts, 120 Volts, Drip-proof 15 Degrees, Symbols 303.2, 303.3, 303.4, 303.2SSL, 303.3SSL, and 303.4SSL
MIL-F-16377/62*	-	Fixtures, Lighting; Incandescent, Floodlights 500 Watts, 120 Volts, Watertight, Symbols 300 and 300.1
MIL-F-16377/65*	-	Fixtures, Lighting; Fluorescent, General Lighting, 30 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 81, 81.1, 345.2 and 345.3
MIL-F-16377/66*	-	Fixtures, Lighting; Fluorescent, General Lighting, 45 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 82, 82.1, 343.1 and 343.2
MIL-F-16377/67	-	Fixtures, Lighting; Window Assemblies, Clear White Shielded, to be Used for Replacement Parts Only
MIL-DTL-16377/71	-	Fixtures, Lighting; Fluorescent and Solid-State Equivalent, Detail Lighting for Mirrors for Small Boats, 8 Watts, 120 Volts, 60 Hertz, Totally Enclosed, Symbols 354, and 354SSL
MIL-DTL-16377/72	-	Fixtures, Lighting; Ballast, for One 20-Watt T-12 Fluorescent Lamp
MIL-DTL-16377/73	-	Fixtures, Lighting; Fluorescent and SSL Equivalent, Emergency Lighting, 20 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 331.1EM, 331.2EM, 347.2EM, 347.3EM, 331.1EMSSL, 331.2EMSSL, 347.2EMSSL, and 347.3EMSSL
MIL-DTL-16377/74	-	Fixtures, Lighting; Fluorescent and SSL Equivalent, Emergency Lighting, 40 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 77.4EM, 77.5EM, 344.2EM, 344.3EM, 77.4EMSSL, 77.5EMSSL, 344.2EMSSL, and 344.3EMSSL
MIL-DTL-16377/75	-	Fixtures, Lighting; Fluorescent and SSL Equivalent, Emergency Lighting, 60 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 333.1EM, 333.2EM, 341.1EM, 341.2EM, 342.2EM, 342.3EM, 333.1EMSSL, 333.2EMSSL, 341.1EMSSL, 341.2EMSSL, 342.2EMSSL, and 342.3EMSSL
MIL-DTL-16377/76	-	Fixtures, Lighting; Fluorescent and Solid-State Equivalent, Emergency Lighting, 60 and 80 Watts, 120 Volts, 60 Hertz, Dripproof, Symbols 348EM, 349EM, 348EMSSL, and 349EMSSL

* Inactive for new design.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:38Z
Check the source to verify that this is the current version before use.

TABLE I. Specification sheets, numerical listing - Continued.

MIL-DTL-16377/77	-	Fixtures, Lighting; Emergency Ballast, for One 17- or 20-Watt T12 or 17-Watt T8 Fluorescent Lamp
MIL-DTL-16377/78	-	Fixtures, Lighting; T8 Fluorescent, General Lighting, 17 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 331.1T8, 331.2T8, 347.2T8, and 347.3T8
MIL-DTL-16377/79	-	Fixtures, Lighting; T8 Fluorescent, General Lighting, 34 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 77.4T8, 77.5T8, 344.2T8, and 344.3T8
MIL-DTL-16377/80	-	Fixtures, Lighting; T8 Fluorescent, General Lighting, 51 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 333.1T8, 333.2T8, 341.1T8, 341.2T8, 333.1T8RC, 341.4T8, 342.2T8, and 342.3T8
MIL-DTL-16377/81	-	Fixtures, Lighting; Ballast, for One 17-Watt T8 Fluorescent Lamp
MIL-DTL-16377/82	-	Fixtures, Lighting; T8 Fluorescent, Emergency Lighting, 17 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 331.1T8EM, 331.2T8EM, 347.2T8EM, and 347.3T8EM
MIL-DTL-16377/83	-	Fixtures, Lighting; T8 Fluorescent, Emergency Lighting, 34 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 77.4T8EM, 77.5T8EM, 344.2T8EM, and 344.3T8EM
MIL-DTL-16377/84	-	Fixtures, Lighting; T8 Fluorescent, Emergency Lighting, 54 Watts, 120 Volts, 60 Hertz, Watertight, Symbols 333.1T8EM, 333.2T8EM, 342.2T8EM, and 342.3T8EM
MIL-DTL-16377/85	-	Fixtures, Lighting; Fluorescent, General Lighting, 162 Watts, 120 VAC, 60 Hertz, Dripproof, Symbols 76.1, 76.3, 76.4, and 76.5
MIL-DTL-16377/86	-	Fixtures, Lighting; Lamp, Solid-State, for Use as Replacement for Commercial Fluorescent Lamp

* Inactive for new design.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:38Z
Check the source to verify that this is the current version before use.

The following tables detail the procedure for the extension of first article approval to other similar type I and type II lighting fixtures covered by this specification. The approval extension is based upon the similarity of design, the type, and class of lighting fixtures and tooling and fabrication methods and techniques used in the production of the fixtures. When multiple types are presented in the same table, extensions should only be approved for fixtures of the same type. Qualification by extension does not apply to SSL fixtures. For SSL fixtures, qualification will be determined on a case-by-case basis since there is no use of standard parts.

TABLE II. Group I – fluorescent fixtures, type I, class 1, detail illumination.

Slant Sheet	Fixture Use/Description	Approval Extension 1/
/2	Water gauges (6 watts)	/3
/3	Water gauges (8 watts)	/2
/4	Secretary bureau (8 watts)	---
/15	Desks (8 watts)	/4, /16
/16	Desks (8 watts)	/4, /15
/17	Berths (8 watts)	/4, /15, /16
/18	Mirrors (15 watts)	/71
/49	Extension (8 watts)	---
/58	Mirrors (30 watts)	/71
/59	Step (8 watts)	---
/71	Small boat mirrors (8 watts)	---

NOTE:

1/ Optical uniformity and light output testing should be required if lens material is different.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:38Z
Check the source to verify that this is the current version before use.

TABLE III. Group II -fluorescent fixtures, type I class 2, general illumination.

Slant Sheet	**Fixture Use/Description**	**Approval Extension** [1/]
/5	General lighting (15 watts)	---
/6	General lighting, directional (16 watts)	/7, /14
/7	General lighting (16 watts)	/6, /14
/8	General lighting (20 watts)	/5
/9	General lighting (24 watts)	/6, /7, /14
/10	General lighting, directional (32 watts)	/6, /7, /9, /14
/11	General lighting (40 watts)	/5, /8, /65
/12 (symbols 333.1, 333.2, 342.2, and 342.3)	General lighting; symbols 333.1, 333.2, 342.1, and 342.2 (60 watts)	/5, /8, /11, /65, /66
/12 (symbols 341.1 and 341.2)	General lighting; CIC; symbols 341.1, 341.2 (60 watts)	/5, /8, /11, /12, /65, /66
/13	General lighting (180 watts)	---
/14	General lighting (8 watts)	---
/57 (60 watts)	General lighting (60 watts)	---
/57 (80 watts)	General lighting (80 watts)	/57 (60 watts)
/57 (120 watts)	General lighting (120 watts)	/57 (60 and 80 watts)
/65	General lighting (15 watts)	/5
/66	General lighting, directional (16 watts)	/5, /65
/73	General lighting, emergency (20 watts)	---
/74	General lighting, emergency (40 watts)	/73
/75 (symbols 333.1EM, 333.2EM, 342.2EM, and 342.3EM)	General lighting, emergency, (60 watts)	/73, /74
75 (341.1EM and 341.2EM)	General lighting, emergency (60 watts)	/73, /74, /75
/76 (60 watts)	General lighting, emergency (60 watts)	---
/76 (80 watts)	General lighting, emergency (80 watts)	/76 (60 watts)
/78	General lighting, T8 (17 watts)	---
/79	General lighting, T8 (34 watts)	/78
/80 (symbols 333.1T8, 333.2T8, 342.2T8, and 342.3T8)	General lighting, T8 (51 watts)	/78, /79
/80 (symbols341.1T8 and 341.2T8)	General lighting, T8 (51 watts)	/78, /79, /80
/82	General lighting, T8 emergency (17 watts)	---
/83	General lighting, T8 emergency (34 watts)	/82
/84 (symbols 333.1T8EM, 333.2T8EM, 342.2T8EM, and 342.3T8EM)	General lighting, T8 emergency (51 watts)	/82, /83
/84 (symbols 341.1T8EM and 341.2T8EM)	General lighting, T8 emergency (51 watts)	/82, /83, /84

NOTE:

[1/] Optical uniformity and light output testing should be required if lens material is different.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:38Z
Check the source to verify that this is the current version before use.

Slant Sheet	Fixture Use/Description
/1	Motors and generators
/28	Ammunition hoist
/31	Spot illumination
/32	Water gauges
/33	Sightglasses
/34	Submarine gyrocompasses
/35	Small boats
/38	Hull numerals
/39	Streamers
/52	Extension, explosionproof and watertight (100 watts)
/53	Hand lantern
/56	Machine tool

TABLE V. Group IV – incandescent (type II, class 2, general illumination).

Slant Sheet	Fixture Use/Description	Approval Extension
/20	General lighting (50 watts)	/21, /22
/21	General lighting (100 watts)	/20, /22
/23	General lighting (200 watts)	/20, /21
/25	General lighting (explosionproof)	/26
/26	General lighting (110 watts)	---
/27	General lighting (50 watts)	---
/30	General lighting (psychiatric wards)	---
/36	General lighting (25 watts)	---
/60	Floodlight (150 watts)	---
/61	Floodlight (300 watts)	/60
/62	Floodlight (500 watts)	---

CONCLUDING MATERIAL

Preparing Activity:
Navy – SH

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T08:38Z
Check the source to verify that this is the current version before use.