
DETAIL SPECIFICATION SHEET

ANCHORS, GROUND, ARROWHEAD, MALLEABLE IRON, 6 INCH

This specification is approved for use by all Departments and
Agencies of the Department of Defense.


The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-3962.



NOTE: Body and pin dimensions see figure 3.

FIGURE 1. 6 inch ground anchor assembly grade B, style 3.


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:58Z
Check the source to verify that this is the current version before use.



NOTE: Body and pin dimensions see figure 3.

FIGURE 2. 6 inch ground anchor assembly, grade B, style 4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:58Z
Check the source to verify that this is the current version before use.




Inch	mm	Inch	mm
.006	0.15	.45	11.4
.016	0.41	.500	12.70
.031	0.79	1.188	30.18
.032	0.81	1.25	28.58
.063	1.60	1.5	38
.094	2.39	2	51
.188	4.78	3.5	89
.25	6.4	6	152
.313	7.95		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ± .063 inch (1.60 mm) and angles ±3°, wire and metal gages excluded.
4. Casting to be free of fins and flash.
5. Break all sharp edges.

FIGURE 3. Body and pin.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:58Z
Check the source to verify that this is the current version before use.




Inch	mm
.1250	31.75
.25	6.4
1.5	38
42	1067
57	1448

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ± .063 inch (1.60 mm).
4. Wire rope shall be steel, type I, composition A, in accordance with MIL-DTL- 83420/1.
5. Proof load equal to breaking strength as specified in MIL-DTL-3962.

FIGURE 4. Anchoring cable assembly 5500 lb load for type I, grade B, style 3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:58Z
Check the source to verify that this is the current version before use.



Inch	mm
.125	3.18
.25	6.35
1.125	28.58
48	1219.2
101.5	2578.1

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified tolerances are ± .063 inch (1.60 mm).
4. Wire rope shall be steel, type I, composition A, in accordance with MIL-DTL- 83420/1.
5. Proof load equal to breaking strength as specified in MIL-DTL-3962.

FIGURE 5. Anchoring cable assembly with thimble 5500 LB load grade B, style 4.

REQUIREMENTS

Material:

Body Grade B cast malleable iron grade 32510 in accordance with ASTM A47/A47M.

Pin steel in accordance with ASTM A108, cold finished.

Style see table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:58Z
Check the source to verify that this is the current version before use.

TABLE I. Style and style designator.

Style designator	Description
A	Anchor (see figure 3) without cable
3	Anchor (see figure 1) - cable without thimble, 5500-pound load, style 3, see figure 4
3C	Anchor (see figure 1) - cable without thimble, 5500-pound load, style 3,see figure 4, with driving head, holding handle, and driving rod
4	Anchor (see figure 2) - 48 inch cable with thimble, 5500-pound load, style 4, see figure 5
4C	Anchor (see figure 2) - 48 inch cable with thimble, 5500-pound load, style 4,see figure 5, with driving head, holding handle, and driving rod
4-60 1/	Anchor (see figure 2) - 60 inch cable with thimble, 5500-pound load, style 4, see figure 5
4-60C 1/	Anchor (see figure 2) - 60 inch cable with thimble, 5500-pound load, style 4, see figure 5, with driving head, holding handle, and driving rod
4-120 1/	Anchor (see figure 2) - 120 inch cable with thimble, 5500-pound load, style 4, see figure 5
4-120C 1/	Anchor (see figure 2) - 120 inch cable with thimble, 5500-pound load, style 4, see figures 2 and 5, with driving head, holding handle, and driving rod

1/ Same as figures 5 except 48 ±.25 inch dimension is replaced with 60 or 120 ±.25 inch cable.

See MIL-DTL-3962/7 for driving head, holding handle, driving and driving rod. Six inch anchors require the use of a 4 foot driving rod 1.00 inch diameter.

Drive 3.5 feet minimum depth.

Finish (not applicable to zinc coated parts):

Body and pin shall be coated with aluminum pigmented enamel or enamel, alkyd, conforming to MIL-DTL-53039, color designator, see table II.

Holes in driving rods and driving heads shall be free of excess paint to ensure proper fit.


Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:58Z
Check the source to verify that this is the current version before use.

TABLE II. Color codes from FED-STD-595. 1/

Color designator	Color
Blank	Zinc in accordance with ASTM A153/A153M
34079	Forest Green in accordance with FED-STD-595
33303	Sand in accordance with FED-STD-595
33531	Tan in accordance with FED-STD-595
38905	Weapons safety red

1/ See MIL-DTL-53039 for other coating colors.

PIN: The PIN consists of the prefix letter “M” the specification sheet number, a dash number for style, a dash, and color designator.



PIN examples:
M3962/4-3-34079 indicates a 6 inch anchor, cable without thimble, forest green.
M3962/4-4-60C-34079 indicates a 6 inch anchor, 60 inch cable with thimble, with driving head, holding handle, and driving rod, forest green.

Marking shall be as specified on figure 3.

Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Referenced documents shall be of the issue in effect on date of invitations for bid.

Legacy. This slash sheet is a replacement for drawing 4-1-198, referenced in MIL-A-3962, dated 19 May 1986. Color designator 34079 is the original color of the accessories, see table III for supersession listing and associated National Stock Number (NSN).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:58Z
Check the source to verify that this is the current version before use.

TABLE III. Supersession data.

Description	New PIN	Superseded PIN	NSN
Anchor - cable without thimble, 5500-pound load, style 3	MS3962/4-3-34079	MIL-A-3962 SZ6 GRB ST3	4030-01-415-0620
Anchor - 48 inch cable with thimble, 5500-pound load, style 4,	MS3962/4-4-34079	4-1-198	5410-00-545-0424

Referenced documents. In addition to MIL-DTL-3962, this document references the following:

FF-T-276	MIL-DTL-3962/7
FED-STD-595	MIL-DTL-53039
FED-STD-595/33303	MIL-DTL- 83420/1
FED-STD-595/33531	ASTM A108
FED-STD-595/34079	ASTM A47/A47M
FED-STD-595/38905	ASTM A153/A153M

CONCLUDING MATERIAL

Custodians:
Army - GL
Navy - YD
Air Force - 99
DLA - CC

Preparing Activity:
DLA - CC

(Project 4030-2015-014)

Review Activities:
Army - EA, MD
Navy - SA
Air Force- 71

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:58Z
Check the source to verify that this is the current version before use.