MILITARY SPECIFICATION SHEET

Capacitors, Fixed, Electrolytic (Nonsolid Electrolytic), Tantalum, (Polarized, Sintered Slug) - 85°C (Voltage Derated to 125°C), Styles CL14 and CL16

This amendment forms a part of Military Specification Sheet MIL-C-3965/1H, dated 26 August 1970, and is mandatory for use by all Departments and Agencies of Department of Defense.

Page 2

Table I Capacitor Characteristics.

Delete: Values for Dissipation Factor Column 9 for the following Type Designations:

| | |
|---|---|
| CL1-BF101UPG | 21.0% |
| CL1-BF201UPG | 36.0% |
| CL1-BH151UPG | 29.0% |
| CL1-BK800UPG | 16.0% |

Substitute the values in Dissipation Factor Column 9 for the following Type Designation

| | |
|---|---|
| CL1-BF101UPG | 21.5% |
| CL1-BF201UPG | 38.5% |
| CL1-BH151UPG | 30.3% |
| CL1-BK800UPG | 16.2% |

Custodians:
Army-EL
Navy-EC
Air Force 80

Review Activities:
Army-MI
Navy-SH
Air Force 11, 17
DSA-ES

User Activities:
Army -
Navy-AS, MC, OS
Air Force 19

Preparing Activity:
Air Force 80

(Project 5910-1041-1)

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:59Z
Check the source to verify that this is the current version before use.