MIL-S-3960a
21 DECEMBER 1961
SUPERSEDING
MIL-S-3960
8 NOVEMBER 1955

MILITARY SPECIFICATION

STRAPS, RETAINING

This specification has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 Scope. This specification covers metal retaining straps.

1.2 Classification. The straps shall be of the following types, as specified:

Type I — One-hole strap.
Type II — Two-hole strap.

1.3 Sizes. Unless otherwise specified, the straps shall be furnished in the sizes specified on standards MS21314, MS21315, and MS35140.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

NN-K-231 — Kegs, Wood, Slack.
PPP-B-576 — Box, Wood, Cleated, Veneer, Paper Overlaid.
PPP-B-566 — Boxes, Folding, Paperboard.
PPP-B-585 — Boxes, Wood, Wirebound.
PPP-B-591 — Boxes, Fiberboard, Wood-Cleated.
PPP-B-601 — Boxes, Wood, Cleated-Plywood.
PPP-B-621 — Boxes, Wood, Nailed or Lock-Corner.
PPP-B-636 — Box, Fiberboard.
PPP-B-640 — Boxes, Corrugated, Triple Wall, 350 Pound Maximum Weight.
PPP-B-665 — Boxes, Paperboard, Metal Stayed, Including Stay Materials.
PPP-B-676 — Boxes, Set-Up, Paperboard.

MILITARY

MIL-L-10547 — Liners, Case, Waterproof.

FSC 5340

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:57Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL–STD–105 — Sampling Procedures and Tables for Inspection by Attributes.

MIL–STD–129 — Marking for Shipment and Storage.

MS2131 — Strap, Retaining, Two-Hole for Pipe, Conduit and Cable.

MS21315 — Strap, Retaining, Two-Hole for Tubing.

MS35140 — Strap, Retaining, Single-Hole, Open End Type.

3. REQUIREMENTS

3.1 Materials. Materials shall be as specified on standards MS21314, MS21315, and MS35140, and other drawings as required in the contract or order.

3.2 Design.

3.2.1 *Type I.* The design of type I retaining straps shall be as specified on standards MS35140 and other drawings as required in the contract or order.

3.2.2 *Type II.* The design of type II retaining straps shall be as specifie don standards MS21314 and MS21315 and other drawings as required in the contract or order.

3.3 Dimensions and tolerances. The dimensions and tolerances shall be as specified on standards MS21314, MS21315, and MS35140 and other drawings as required in the contract or order.

3.4 Protective coating. The straps shall be plated in accordance with instructions on standards MS21314, MS21315, and MS35140 and other drawings as required in the contract or order.

3.5 Workmanship. The straps shall be manufactured in accordance with this specification, pertinent standards, and best commercial practice. The straps shall have no pits, rust, loose scale, chips, scraps, splits, cracks, burrs, and other defects that would affect serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor inspection. The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examination and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 *For nondestructive tests.* Sampling for nondestructive tests shall be conducted in accordance with standard MIL–STD–105, inspection level II.

4.2.2 *For destructive tests.* Sampling for destructive tests shall be in accordance with Standard MIL–STD–105, inspection level L8.

4.3 Inspection.

4.3.1 *Inspection of straps.* Inspection of straps shall be conducted as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:57Z
Check the source to verify that this is the current version before use.

Categories	*Defects*	*Method of inspection*
Critical	None defined.	
Major:	*AQL 2.5 percent*	
101	Dimensions not as specified	Measure
102	Attaching hole(s) not alined	Measure
103	Deformation	Measure
104	Workmanship defective (3.5)	Visual
Minor:	*AQL 6.5 percent*	
201	Coating not as specified	Pertinent specifications
202	Burs	Visual

4.4 Tests. Straps selected as in 4.2.2 shall be analyzed to determine compliance with pertinent specifications. Plating shall be checked for compliance with pertinent specifications.

4.5 Inspection of preparation for delivery. The preservation, packaging, packing, and marking shall be examined to determine conformance with the requirements of section 5 of this specification and as required by specifications referenced therein. Except as required by referenced specifications, inspection lots and sampling shall be in accordance with Standard MIL–STD–105, with inspection level L–5 and an AQL of 4.0 percent defective.

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A or level C, as specified (see 6.2).

5.1.1 *Level A.* Retaining straps shall be packaged in quantities shown in table I in cartons or boxes conforming to specifications PPP–B–566, PPP–B–636, PPP–B–665, or PPP–B–676.

TABLE I.

Strap size	Quantity in unit package
For cable OD sizes through 1½ in.	100
„ „ „ over 1½ in. through 2⅞ in.	50
„ „ „ „ 2⅞ in. „ 3½ in.	35
„ „ „ „ 3½ in. „ 5 in.	20
„ „ „ „ 5 in.	15

5.1.2 *Level C.* Retaining straps will be packaged to afford adequate protection against corrosion, deterioration, and damage during shipment from supply source to first receiving activity for immediate use or for controlled humidity storage.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 *Level A.* Packaged retaining straps shall be packed in boxes of the overseas class or type of one of the following specifications: PPP–B–576, PPP–B–585, PPP–B–591, PPP–B–601, PPP–B–621, PPP–B–636, or PPP–B–640. Bxoes shall be constructed for type 2 loads unless otherwise specified in the contract or order. When specified, shipping containers shall be provided with waterproof case liners conforming to class 2 of Specification MIL–L–10547, sealed in accordance with the appendix thereto. Unpackaged retaining straps shall be packed in containers conforming to one of the following specifications: NN–K–231; PPP–B–601, overseas type; PPP–B–621, class 2. Boxes for unpackaged retaining straps shall be constructed for type 3 loads. Boxes shall be closed and strapped

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:57Z
Check the source to verify that this is the current version before use.

as specified in the applicable specification or appendix. Gross weight of shipping containers shall not exceed 200 pounds each, except that gross weight of containers conforming to Specification PPP–B–636 shall not exceed the weight limitation of the container selected.

5.2.2 *Level B.* Packaged retaining straps shall be packed in boxes of the domestic class or type of one of the following specifications: PPP–B–576, PPP–B–585, PPP–B–591, PPP–B–601, PPP–B–621, PPP–B–636, or PPP–B–640. Boxes shall be constructed for type 2 loads unless otherwise specified in the contract or order. Unpackaged retaining straps shall be packed in containers conforming to one of the following specifications: NN–K–231; PPP–B–601, domestic type; or PPP–B–621, class 1. Boxes for unpackaged retaining straps shall be constructed for type 3 loads. Boxes shall be closed as specified in the applicable specification. Gross weight of shipping containers shall not exceed 200 pounds each, except that gross weight of containers conforming to Specification PPP–B–636 shall not exceed the weight limitation of the container selected.

5.2.3 *Level C.* Retaining straps will be packed to afford adequate protection against damage during direct shipment from supply source to the first receiving activity. This level, as a minimum, will conform to applicable carrier rules and regulations.

5.2.4 *Bulk shipment.* When specified in the contract or order (see 6.2), retaining straps of like description and size, shall be bulk shipped, regardless of quantity packaging indicated in table I of this specification. When bulk shipment is specified, only exterior containers authorized in 5.2.1, 5.2.2, and 5.2.3 for unpackaged items shall be used.

5.3 **Marking.** Interior and exterior containers shall be marked in accordance with Standard MIL–STD–129, and also with any special markings which may be required by the contract or order

6. NOTES

6.1 Intended use. The straps are used to fasten pipes, conduit, and cables to fixed structures.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Type of strap.
(c) Part number.
(d) Level of packaging and packing (sec. 5).

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may be related thereto.

Custodians:
Army—Ord
Navy—YDSO
Air Force—MOA

Preparing activity:
Army—Ord

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:57Z
Check the source to verify that this is the current version before use.