NOT MEASUREMENT SENSITIVE

MIL-DTL-2/19C
9 June 1995
SUPERSEDING
MIL-V-2/19B
9 September 1970

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS :

ETHYLENE OXIDE-CARBON DIOXIDE MIXTURE, OUTLET 350

Pressures through 3000 PSIG (20,680 KPa) at 120 degrees F (48.9 degrees C)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the valve described herein shall consist of this specification and the latest issue of MIL-DTL-2.

TYPE DESIGNATION	CYLINDER SERVICE PRESSURE PSI	TYPE SAFETY DEVICE
V19-350-3	1800	1
V19-350-4	2015	1
V19-350-5	2265	1

Style	Class	Composition	Inlet Size	Outlet Application	Handwheel	Safety Device
III	30	A	6	350	Required	1

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:38Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS :

1. An educator tube shall be supplied in accordance with Figure 1 of this specification sheet.
2. Mark the valve body: CARBOXIDE S.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).

INTENDED USE:

The valves covered by this specification sheet are intended for use with cylinders for a 10 percent mixture of ethylene oxide and 90 percent carbon dioxide which is a sterilization and fumigation agent known as Carboxide.

NOTES:

1. Type designation will include any style valve from the chart above.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

Custodians:
Army - ME
Navy - SH
Air Force - 68

Review activities:
Army - AV
Navy - AS, MC, YD1
DLA - GS

Preparing activity:
Air Force - 68

(Project 8120-1025-17)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:38Z
Check the source to verify that this is the current version before use.