NOT MEASUREMENT SENSITIVE

MIL-DTL-2/1D
9 June 1995
SUPERSEDING
MIL-V-2/1C
18 February 1981

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS :

ACETYLENE, OUTLET 510, INLET . 75 INCH

Pressures through 500 PSIG (3450 KPa) at 120 degrees F (48.9 degrees C)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the valve described herein shall consist of this specification and the latest issue of MIL-DTL-2.

TYPE DESIGNATION: V1-510-0

| Style | Class | Composition | Inlet Size | Outlet Application | Handwheel | Safety Device |
|---|---|---|---|---|---|---|
| I | 05 | A | 6 | 510 | No | 0 |
| II | 05 | A | 6 | 510 | Required | 0 |
| III | 05 | A | 6 | 510 | Required | 0 |
| IV | 05 | A | 6 | 510 | Required | 0 |



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:35Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS :

1. The valve components shall contain less than 67 percent copper.
2. Mark the valve body: ACETYLENE.

OPTIONAL REQUIREMENTS:

1. Strainer (required) (not required).
2. Outlet cap or plug (required) (not required).
3. Wrench or key for style 1 valve (required) (not required).

INTENDED USE:

The valves covered by this specification sheet are intended for use with acetylene cylinders having .75-inch outlet connections.

NOTES:

1. Type designation will include any style valve from the chart above.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.
4. Size 6 - .75 inch will be standard, size 8 - 1.00 inch will be special.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Review activities:
Army - AV
Navy - AS, MC, YD1
DLA - GS

Preparing activity:
Air Force - 68

(Project 8120-1025-01)



Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:35Z
Check the source to verify that this is the current version before use.