NOT MEASUREMENT SENSITIVE

MIL-DTL-2/20D
25 September 2002
SUPERSEDING
MIL-DTL-2/20C
9 June 1995

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS: CHLORINE, OUTLET 820
(PRESSURES THROUGH 500 psig (3450 kPa) AT 70 ºF (21.1 ºC))

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-2 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

REQUIREMENTS:

TYPE DESIGNATION: V20-820-1

TABLE I. Valve requirements.

Style	Class	Composition	Inlet size	Outlet application	Handwheel	PRD[1]
I	05	C	6	820	No	2

[1] Pressure Relief Device

SPECIAL REQUIREMENTS:

1. A valve outlet cap shall be supplied.
2. Standard inlet threads shall be 0.75-14NGT(C1)-1.
3. Mark the valve body: CHLORINE.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:38Z
Check the source to verify that this is the current version before use.

OPTIONAL REQUIREMENTS:

1. Wrench or key (required) (not required).
2. When specified, larger inlet threads may be either 0.75-14NGT(C1) (-2), (-3), (-4), or (-5).

INTENDED USE: The valves covered by this specification sheet are intended for use with chlorine cylinders.

NOTES:

1. Special requirements will be mandatory for all valve procurements.
2. Optional requirements will be specified for each valve procurement.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Preparing Activity:
DLA - GS3

(Project 8120-1047-20)

Review Activities:
Army - AV
Navy - AS, MC, YD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:38Z
Check the source to verify that this is the current version before use.