NOT MEASUREMENT SENSITIVE

MIL-DTL-2/21C
9 June 1995
SUPERSEDING
MIL-V-2/21B
7 September 1970

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS :

CHLORINE (TON CONTAINER) OUTLET 820

Pressures through 500 PSIG (3450 KPa) at 120 degrees F (48.9 degrees C)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the valve described herein shall consist of this specification and the latest issue of MIL-DTL-2.

TYPE DESIGNATION: V21-820-1

Style	Class	Composition	Inlet Size	Outlet Application	Handwheel	Safety Device
I	05	C	6	820	No	2

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:38Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS :

1. A valve outlet cap shall be supplied.
2. Standard inlet threads shall be .75-14NGT(C1)-1.
   When specified, larger inlet threads shall be either:
   - .75-14NGT(C1)-2
   - .75-14NGT(C1)-3
   - .75-14NGT(C1)-4.
3. Mark the valve body: CHLORINE.

OPTIONAL REQUIREMENTS:

1. Wrench or key (required) (not required).
2. Inlet threads .75-14NGT(C1) (-1), (-2), (-3), or (-4).

INTENDED USE:

The valves covered by this specification sheet are intended for use with 1-ton chlorine containers.

NOTES:

1. Type designation will include any style valve from the chart above.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Review activities:
Army - AV
Navy - AS, MC, YD1
DLA - GS

Preparing activity:
Air Force - 68

(Project 8120-1025-19)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:38Z
Check the source to verify that this is the current version before use.