NOT MEASUREMENT SENSITIVE

MIL-DTL-2/24D
25 September 2002
SUPERSEDING
MIL-DTL-2/24C
9 June 1995

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS: ETHYLENE OXIDE, OUTLET 510 (PRESSURES THROUGH 500 psig (3450 kPa) AT 70 ºF (21.1 ºC))

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-2 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

REQUIREMENTS:

TYPE DESIGNATION: V24-510-1

TABLE I. Valve requirements.

Style	Class	Composition	Inlet size	Outlet application	Handwheel	PRD[1]
I	05	B	6	510	No	2

[1] Pressure Relief Device

SPECIAL REQUIREMENTS:

1. Dip tube shall be in accordance with MIL-DTL-2.
2. Mark the valve body: ETHYLENE OXIDE S.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:39Z
Check the source to verify that this is the current version before use.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. Wrench or key (required) (not required).
3. Dip tube assembled to valve (required) (not required).
4. Diameter of cylinder (inches).

INTENDED USE: The valves covered by this specification sheet are intended for use with ethylene oxide cylinders.

NOTES:

1. Special requirements will be mandatory for all valve procurements.
2. Optional requirements will be specified for each valve procurement.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Preparing Activity:
DLA - GS3

(Project 8120-1047-24)

Review Activities:
Army - AV
Navy - AS, MC, YD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:39Z
Check the source to verify that this is the current version before use.