NOT MEASUREMENT SENSITIVE

MIL-DTL-2/3C
9 June 1995
SUPERSEDING
MIL-V-2/3B
9 September 1970

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS :

ACETYLENE, OUTLET 200

Pressures through 500 PSIG (3,450 KPa) at 120 degrees F (48.9 degrees C)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the valve described herein shall consist of this specification and the latest issue of MIL-DTL-2.

TYPE DESIGNATION: V3-200-1

Style	Class	Composition	Inlet Size	Outlet Application	Handwheel	Safety Device
I	05	A	3	200	No	3

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:35Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS :

1. The valve components shall contain less than 67 percent copper.
2. The centerline of the inlet shall meet the centerline of the stem at an angle of 50 degrees and shall meet the centerline of the outlet at an angle of 40 degrees in a common geometric plane.
3. Marking is not mandatory.
4. A fuse plug from fusible metal poured and anchored in a channel drilled in the valve body shall be acceptable as a Type 3 safety device.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. Wrench or key (required) (not required).

INTENDED USE:

The valves covered by this specification sheet are intended for use with 10- and 40-cubic-foot capacity acetylene cylinders.

NOTES

1. Type designation will include any style valve from the chart above.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Preparing activity:
Air Force - 68

(Project 8120-1025-03)

Review activities:
Army - AV
Navy - AS, MC, YD1
DLA - GS

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:35Z
Check the source to verify that this is the current version before use.