NOT MEASUREMENT SENSITIVE

MIL-DTL-2/6C
9 June 1995
SUPERSEDING
MIL-V-2/6B
9 September 1970

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS :

AIR INDUSTRIAL, OUTLET 590, OIL TOLERANT

Pressures through 3,000 PSIG (20,680 KPa) at 120 degrees F (48.9 degrees C).

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the valve described herein shall consist of this specification and the latest issue of MIL-DTL-2.

TYPE DESIGNATION	CYLINDER SERVICE PRESSURE PSI	TYPE SAFETY DEVICE
V6-590-2	1800 through 2400	5
V6-590-3	1800	1
V6-590-4	2015	1
V6-590-5	2265	1
V6-590-6	2400	1

Style	Class	Composition	Inlet Size	Outlet Application	Handwheel	Safety Device
III	30	A	6	590	Required	1 or 5

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:36Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS :

1. Mark the valve body: AIR INDUSTRIAL.
2. When the cylinder service pressure is specified, the appropriate frangible disk safety device (type 1) shall be supplied.
3. When the cylinder service pressure is not specified, a combination safety device (type 5) shall be supplied with a frangible disk with a burst range between 2700 and 3000 psi. This device shall be utilized only for cylinders of 1800 to 2400 psi rating.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. Cylinder service pressure (psi) (unknown).

INTENDED USE:

The valves covered by this specification sheet are intended for use with cylinders for air used for industrial applications.

NOTES:

1. Type designation will include any style valve from the chart above.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Preparing activity:
Air Force - 68

(Project 8120-1025-06)

Review activities:
Army - AV
Navy - AS, MC, YD1
DLA - GS

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:36Z
Check the source to verify that this is the current version before use.