NOT MEASUREMENT SENSITIVE

MIL-DTL-2/7D
25 September 2002
SUPERSEDING
MIL-DTL-2/7C
9 June 1995

DETAIL SPECIFICATION SHEET

# VALVE, CYLINDER, GAS: ANHYDROUS AMMONIA (DISHED-HEAD CYLINDER), OUTLET 240, INLET 0.75 INCH (PRESSURES THROUGH 500 psig (3450 kPa) AT 70 ºF (21.1 ºC))

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-2 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

REQUIREMENTS:

TYPE DESIGNATION: V7-240-0

TABLE I. Valve requirements.

| Style | Class | Composition | Inlet size | Outlet application | Handwheel | PRD[1] |
|---|---|---|---|---|---|---|
| I | 05 | B | 6 | 240 | No | 0 |

[1] Pressure Relief Device

SPECIAL REQUIREMENTS:

1. Unless otherwise specified, the valve shall be supplied with a dip tube for 15.00-inch diameter cylinders.
2. The dimension from the centerline of the valve to the end of the outlet shall not exceed 1.875 inches.
3. The centerline of the outlet shall meet the centerline of the valve body at an angle of 34 to 40 degrees in a common plane.



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:36Z
Check the source to verify that this is the current version before use.

4. The valve seat shall be tin.
5. Mark the valve body: AMMONIA S.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. Wrench or key (required) (not required).
3. Dip tube assembled to valve (required) (not required).
4. Cylinder diameter if other than 15.00 inches (inches).

INTENDED USE: The valves covered by this specification sheet are intended for use with anhydrous ammonia cylinders having a 0.75-inch outlet connection and a dished head.

NOTES:

1. Special requirements will be mandatory for all valve procurements.
2. Optional requirements will be specified for each valve procurement.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Preparing Activity:
DLA - GS3

(Project 8120-1047-07)

Review Activities:
Army - AV
Navy - AS, MC, YD



Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:36Z
Check the source to verify that this is the current version before use.