MILITARY SPECIFICATION SHEET

ADAPTERS, COAXIAL TO WAVEGUIDE (DOUBLE RIDGE)
(BANDWIDTH RATIO 2 4 1) (SERIES N TO WAVEGUIDE - CLASS 1)

This specification is approved for use by all Departments and Agencies of the Department of Defense

The complete requirements for procuring the adapters described herein shall consist of this document and the latest issue of Specification MIL-A-22641




FIGURE 1 Adapters, coaxial to double ridge waveguide (class 1)

REQUIREMENTS

Design, construction, and physical dimensions See figure 1 and table I

Operating temperature range -54° to +125°C

Frequency range See table I

VSWR See table I

FSC 5985

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:12Z
Check the source to verify that this is the current version before use.

TABLE I Adapters, coaxial to waveguide (series N to waveguide - class 1)

Dash number	Frequency range (GHz)	Typical VSWR over any octave band within frequency range	VSWR over entire frequency range (max) 4/5/	RF insertion loss dB (max) 5/	Waveguide housing	Flange	Waveguide and flange material	Connector	Dimensions 1/2/3/		
									A (max)	B (max)	C (max)
01	84-2 0	1 10 1	1 15 1	.10	M23351/ 4-017	M39000/ 3-001	Aluminum	Male	4 00 (10 2)	2 55 (65 0)	2 90 (74 0)
02	84-2 0	1 10 1	1 15 1	10	M23351/ 1-017	M39000/ 3-001	Aluminum	Female	4 00 (10 2)	2 55 (65 0)	2 90 (74 0)
03	2 0-4 8	1 06 1	1 20 1	10	M23351/ 4-025	M39000/ 3-024	Aluminum	Male	2.25 (57.0)	1.58 (40.0)	1.57 (40.0)
04	2 0-4 8	1 06 1	1 20 1	.10	M23351/ 4-025	M39000/ 3-024	Aluminum	Female	2 25 (57 0)	1 58 (40.0)	1 57 (40 0)
05	2 0-4 8	1 06 1	1 20 1	10	M23351/ 4-025	M39000/ 3-026	Aluminum	Male	2 25 (57.0)	1.58 (40.0)	1 57 (40.0)
06	2 0-4 8	1 06 1	1 20 1	10	M23351/ 4-025	M39000/ 3-026	Aluminum	Female	2 25 (57.0)	1 58 (40 0)	1 57 (40 0)
07	2 0-4 8	1 06 1	1 20 1	10	M23351/ 4-025	M39000/ 3-028	Aluminum	Male	2 25 (57.0)	1 58 (40 0)	1 57 (40 0)
08	2 0-4.8	1 06 1	1 20 1	.10	M23351/ 4-025	M39000/ 3-028	Aluminum	Female	2.25 (57.0)	1.58 (40 0)	1 57 (40.0)
09	3 5-8 2	1 06 1	1 20 1	10	M23351/ 4-029	M39000/ 3-030	Aluminum	Male	1 45 (37 0)	1 28 (33 0)	92 (23.0)
10	3 5-8 2	1 05 1	1 20 1	10	M23351/ 4-029	M39000/ 3 030	Aluminum	Female	1 45 (37 0)	1 28 (33 0)	92 (23.0)
11	3 5-8 2	1 06 1	1 20 1	10	M23351/ 4-029	M39000/ 3-032	Aluminum	Male	1 45 (37.0)	1 28 (33.0)	.92 (23 0)
12	3 5-8 2	1 06 1	1 20 1	10	M23351/ 4-029	M39000/ 3-032	Aluminum	Female	1 45 (37.0)	1 28 (33.0)	92 (23 0)
13	3 5-8 2	1 05 1	1 20 1	10	M23351/ 4-029	M39000/ 3-034	Aluminum	Male	1 45 (37 0)	1 28 (33 0)	92 (23 0)
14	3 5-8 2	1 05 1	1 20 1	10	M23351/ 4-029	M39000/ 3-034	Aluminum	Female	1.45 (37.0)	1.28 (33 0)	92 (23 0)
15	4 75-11.0	1 06 1	1 20 1	.10	M23351/ 4-033	M39000/ 3-036	Aluminum	Male	1 75 (44 0)	1 15 (29 0)	1 20 (30 0)
16	4 75-11.0	1 06 1	1 20 1	10	M23351/ 4-033	M39000/ 3-036	Aluminum	Female	1.75 (44 0)	1.15 (29.0)	1 20 (30 0)
17	4 75-11 0	1 06 1	1 20 1	10	M23351/ 4-033	M39000/ 3-038	Aluminum	Male	1 75 (44 0)	1 15 (29 0)	1 20 (30 0)

See footnotes at end of table

Source: https://assist.dla.mil -- Downloaded: 20260-19T13:12Z
Check the source to verify that this is the current version before use.

TABLE I Adapters, coaxial to waveguide (series N to waveguide - class 1) - Continued

Dash number	Frequency range (GHz)	Typical VSWR over any octave band within frequency range	VSWR over entire frequency range (max) 4/5/	RF insertion loss dB (max) 5/	Waveguide housing	Flange	Waveguide and flange material	Connector	Dimensions 1/2/3/ A (max)	B (max)	C (max)
18	4.75-11.0	1.06:1	1.20:1	10	M23351/4-033	M39000/3-038	Aluminum	Female	1.75 (44.0)	1.15 (29.0)	1.20 (30.0)
19	4.75-11.0	1.06:1	1.20:1	10	M23351/4-033	M39000/3-040	Aluminum	Male	1.75 (44.0)	1.15 (29.0)	1.20 (30.0)
20	4.75-11.0	1.06:1	1.20:1	10	M23351/4-033	M39000/3-040	Aluminum	Female	1.75 (44.0)	1.15 (29.0)	1.20 (30.0)
21	7.5-18.0	1.10:1	1.30:1	10	M23351/4-037	M39000/3-072	Aluminum	Male	1.30 (33.0)	1.06 (27.0)	.77 (20.0)
22	7.5-18.0	1.10:1	1.30:1	10	M23351/4-037	M39000/3-072	Aluminum	Female	1.30 (33.0)	1.06 (27.0)	.77 (20.0)
23	7.5-18.0	1.10:1	1.30:1	10	M23351/4-037	M39000/3-074	Aluminum	Male	1.30 (33.0)	1.06 (27.0)	.77 (20.0)
24	7.5-18.0	1.10:1	1.30:1	10	M23351/4-037	M39000/3-074	Aluminum	Female	1.30 (33.0)	1.06 (27.0)	.77 (20.0)
25	7.5-18.0	1.10:1	1.30:1	10	M23351/4-037	M39000/3-076	Aluminum	Male	1.30 (33.0)	1.06 (27.0)	.77 (20.0)
26	7.5-18.0	1.10:1	1.30:1	10	M23351/4-037	M39000/3-076	Aluminum	Female	1.30 (33.0)	1.06 (27.0)	.77 (20.0)

1/ Dimensions are in inches.
2/ Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm
3/ Metric equivalents are in parentheses
4/ A larger attenuator pad may be used for VSWR test setup (see figure 1 of MIL-A-22641)
5/ VSWR and RF insertion loss may be measured by swept frequency techniques

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:12Z
Check the source to verify that this is the current version before use.

REQUIREMENTS - Continued

RF insertion loss See table I

Connector Connector bodies shall be corrosion-resistant steel

Housing, waveguide See table I

Marking See figure 1

Part number M22641/23- (dash number from table I)

Preparing activity
Navy - EC

Agent
DLA - ES

(Project 5985-0876-4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:12Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No 22-R255

INSTRUCTIONS The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay or will otherwise enhance use of the document DoD contractors government activities or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government Fold on lines on reverse side staple in corner and send to preparing activity Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity

DOCUMENT IDENTIFIER AND TITLE
MIL-A 22641/23

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3 IS THE DOCUMENT RESTRICTIVE?
☐ YES ☐ NO *(If "Yes", in what way?)*

4 REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED S/N 0 0116-1807

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:12Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D.C. 20360

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
NAVY DEPARTMENT
DOD 316

U.S. MAIL

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-19T13:12Z
Check the source to verify that this is the current version before use.