MIL-C-22625(Wep)
31 August 1960
SUPERSEDING
NAVORD OS 8810
20 June 1959

MILITARY SPECIFICATION

CARTRIDGE, DUMPER VALVE, MARK 22 MOD 0

This specification has been approved by the Bureau of Naval Weapons, Department of the Navy.

1. SCOPE

1.1 This specification governs the manufacture, assembly, and preparation for delivery of the Mk 22 Mod 0 dumper valve cartridge and the methods of inspection and tests upon which product acceptance will be based.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings and publications, of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein.

STANDARD

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-414	- Sampling Procedures and Tables for Inspection by Variables for Percent Defective

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

MIL-STD-129 - Marking for Shipment and Storage

DRAWINGS

BUREAU OF NAVAL WEAPONS

LD 491827 - Cartridge, Dumper Valve, Mk 22 Mod 0, List of Drawings and Specifications

LD 419695 - Container, Inner for Cartridge, Dumper Valve, Mk 22 Type, List of Drawings and Specifications

LD 419696 - Container, Outer for Cartridge, Dumper Valve, Mk 22 Type, List of Drawings and Specifications

LD 419699 - Fixture Test, for Cartridge, Dumper Valve, Mk 22 Type, List of Drawings, Assemblies, Parts, Specification, etc.

PUBLICATIONS

BUREAU OF ORDNANCE

OP 400 - General Instructions for the Design and Inspection of Naval Ordnance Equipment

OP 5 - Ammunition Ashore. (This publication is for the exclusive use of the Government Inspector. It is not to be furnished to bidders or contractors)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

NAVORD OS 7859 - Descriptions and Requirements Ignition Element, Electric, Mark 2 and Mods

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

2.2 Other Publications. - The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 71-78 - Transportation, Interstate Commerce Commission, Explosives and Other Dangerous Articles

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D. C. Orders for the above publication should cite the latest edition and supplements thereto).

3. REQUIREMENTS

3.1 General. -

3.1.1 Mk 22 Mod 0 Dumper Valve Cartridge covered by this specification shall be manufactured in accordance with LD 491827 and all documents listed thereon.

3.1.2 The requirements and procedures established in OP 400 shall be adhered to wherever applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

3.2 Material. - All materials used in the manufacture of the cartridges shall conform strictly with the specifications referred to on the respective BUORD drawings unless specific approval in writing covering a departure therefrom has been obtained from the Bureau of Naval Weapons prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.2.1 Pilot production lot. - Unless otherwise specified by the procuring activity, a pilot production lot of 200 Mk 22 Mod 0, Dumper Valve Cartridges shall be furnished the Government prior to starting on full production. See 4.2.2.

3.3 Ignition elements. - The ignition element, Electric Mk 2 Mod 1, shall be furnished from lots manufactured within a year past.

3.3.1 Ignition element lot acceptance tests. - Acceptability of each lot of ignition elements shall be based on the tests prescribed in section 4.4.1.

3.3.2 X-ray. - All ignition elements shall be x-rayed and screened for defects as outlined in 4.4.2.

3.4 Propellant charge. - Each cartridge lot shall contain propellant from a single lot of propellant.

3.4.1 Weighing. - All propellant charges and ignition charges shall be weighed and the weights verified by another operator.

3.4.2 Black powder. - The moisture content of the black powder at the time of loading shall be less than 0.90 percent as determined by the test procedure of 4.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

3.4.3 Composite propellant (Arcite 208X). - Composite propellant shall be handled in the same manner as Smokeless Powder. It shall not be subjected to unnecessary handling or exposure to the atmosphere. Inspect for signs of decomposition as outlined in paragraphs 1308-1318 and 1322 of OP-5. The inspector should familiarize himself with Chapter 18 of OP-5 "Ammunition Ashore" and conduct tests to determine that the smokeless powder to be used in cartridges does not differ appreciably from the condition as received.

3.5 Cartridge inspection. - The complete cartridge shall be free of the visible defects noted in 4.4.4.

3.5.1 Electrical resistance. - The resistance in all completely assembled cartridges manufactured under contract, when measured electrically using the probe and the body as terminals as specified in 4.4.5., shall be not less than 0.08 ohm or more than 0.14 ohm.

3.6 Coordination. - Completely assembled cartridges fabricated in strict agreement with applicable drawings shall assemble with mating components or the firing mechanism without selection or fitting.

3.7 Functioning. - Cartridges from each lot, selected in accordance with 4.4.6.1 shall function properly when subjected to the test prescribed in 4.4.6.1.

3.7.1 Misfire. - There shall be no misfires, see 4.4.6.2.

3.7.2 Hangfire. - There shall be no hangfires, see 4.4.6.3.

3.8 Ballistic requirements. - Cartridges from each production lot, selected in accordance with 4.4.7.1, shall meet the requirements listed below when subjected to the test prescribed in 4.4.7.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

3.8.1 Chamber pressure. - The chamber pressure produced by the cartridge shall be as specified in 4.4.7.2

3.8.2 Time to maximum pressure. - The time to maximum pressure shall be as specified in 4.4.7.3.

3.9 Workmanship. - Cartridges shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention should be directed to dimensions, finishes and coatings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling. - Unless otherwise specified, and when applicable, the sampling plans and procedures used by the government inspector in the determination of the acceptability of products submitted by a supplier for government inspection shall be in accordance with the provisions of MIL-STD-414, or MIL-STD-105, whichever applies. Unless otherwise specified in the contract, order or requisition, all samples for test purposes shall be provided at the expense of the contractor.

4.2 Lots. -

4.2.1 Inspection lots. - As applied to government inspection of units of product, the term "lot" shall mean "inspection lot", i.e., a collection of units of product used as a basis for government inspection. Unless otherwise specified, the number of units of product in "inspection lots" shall be as determined by the government inspector and may differ from the quantity designated in the contract or order as a lot for production, shipment or other purpose.

4.2.2 Pilot production lot. - Before entering into quantity production, a pilot production lot of 200 cartridges shall be delivered by the contractor to the

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

procuring activity, or to the activity designated by the procuring activity, for test. These cartridges shall be manufactured by the same procedures and at the same location proposed by the contractor for the execution of the contract. When a pilot production lot is received which complies with all test and sampling requirements of this document and the applicable drawings, the contractor will be notified and authorized to proceed with production. When production under a new contract immediately follows the manufacture of satisfactory material, a pilot production lot will not be required.

4.2.3 Production lot. - The suggested production lot shall consist of one thousand cartridges plus cartridges required for all test purposes. Samples selected to determine acceptability of the requirements of Section 3.7 will be used by the Government Inspector in lot acceptance tests conducted at the contractor's activity and samples selected to determine conformance with Section 3.9 shall be delivered to any location designated by the procuring activity for test. Unless otherwise provided for in the contract all cartridges for test purposes shall be provided at the expense of the contractor. Cartridges of a lot shall be of consecutive manufacture. The production lot shall be used for delivery and identification of cartridges and is not necessarily related to the inspection lot defined in 4.2.1.

4.3 Inspection. -

4.3.1 Contractor's inspection. - Unless otherwise required by the procuring activity, the contractor is responsible for the performance of all tests and examinations to assure that the Mk 22 Mod 0, Dumper Valve Cartridge delivered to the Government are in full accordance with all applicable requirements. In addition the contractor is required to maintain records of all tests and examinations performed and to make these records available to the Government representative upon request.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

4.3.1.1 Gages. - The contractor shall provide himself with whatever gages are necessary and adequate to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings. If so stipulated in the contract, order or requisition, the Bureau of Naval Weapons or the procuring activity will furnish drawings of pertinent Navy Final Inspection Gages for guidance in the design of the contractor's inspection gages. However, such procedure shall not serve to relieve the contractor of his responsibility in the design and manufacture of such gages as may be required for the satisfactory fulfillment of the contract requirements, but is intended to facilitate acceptance of all components and assemblies by Navy Final Inspection Gages.

4.3.2 Government inspection. - The Government Inspector shall, during the process of manufacture, assembly and loading, make such inspection and tests as necessary to insure that components, assemblies and all cartridges manufactured are in accordance with the terms of the contract, the order or requisition and the applicable drawings and specifications. Unless otherwise designated herein, inspection and disposition of material shall be governed by Bureau of Ordnance OP 400, General Instructions for the Design, Manufacture and Inspection of Naval Ordnance Equipment.

4.3.3 Production and acceptance inspection. - Production and acceptance inspection shall consist of the following:

Item	Nature of Test	Requirement	Test
Ignition Element	Acceptance	3.3.1	4.4.1
Ignition Element	X-ray	3.3.2	4.4.2
Propellant Charge	Weighing	3.4.1	--
Black Powder	Moisture Content	3.4.2	4.4.3
Composite Propellant (Arcite 208X)	Condition	3.4.3	--

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

Item	Nature of Test	Requirement	Test
Cartridge	Visual Inspection	3.5	4.4.4
Cartridge	Electrical Resistance	3.5.1	4.4.5
Cartridge	Functioning	3.7	4.4.6
Cartridge	Ballistic Test	3.8	4.4.7

4.3.4 Packing, packaging and marking. - The inspector shall ascertain that the packing and packaging of the cartridges and their markings conform to section 5 of this specification.

4.4 Tests. -

4.4.1 Ignition element lot acceptance tests. - Each lot of ignition elements shall be accepted in accordance with the provisions set forth in NAVORD-OS-7859.

4.4.2 X-ray. - Ignition elements should be mounted in suitable grooved racks. For the most revealing exposure the elements are laid on their side. Pressure sensitive tape may be used as an aid in positioning the elements.

Reject any that are questionable from any standpoint, especially for:

4.4.2.1 Charge missing or abnormally thin.

4.4.2.2 Charge broken, cracked or porous.

4.4.2.3 Broken bridge wire.

4.4.3 Moisture content of black powder. - Conduct at least one test for each cartridge lot or daily whichever requires the more frequent testing and

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

such additional tests as considered warranted by variations in conditions or process. Samples may be collected at the site of loading or taken from cartridges as the black powder is sealed in the container. The presence of moisture in excess of the limitations of 3.4.2 shall cause suspension of loading until corrective measures have been taken.

4.4.3.1 Determining moisture content. - Enclose a sample in a tared container. Weigh and expose for drying at +95°C ± 5°C for 1-1/2 hours. Close the container, cool and weigh. The loss of weight is calculated as the percentage of moisture in the original sample. As an alternate method, allow the sample to dry to constant weight in an adequate dessicator at room temperature.

4.4.4 Visual inspection. - Examine all cartridges manufactured and reject for: dents, deep scratches, split or cracked lip in the crimped area, damaged or bent probe, cracked insulation, perforated closure discs, sharp edges, burrs, incomplete threads, and other defects which may conceivably prevent entry into the firing mechanism or affect stability or resistance to moisture.

4.4.5 Cartridge electrical resistance. - Conformance with the circuit resistance of 3.5.1 shall be ascertained by means of a test circuit which limits the current to 50 milliamperes, maximum. A safety chamber with an interlock switch shall be used to protect the operator during the application of the current. A suitable bridge which is known to be accurate within 0.01 ohm in the range of resistance specified shall be used to determine whether or not the requirement is being met. Units which conform to the requirements of 3.5.1 shall be acceptable. One hundred percent inspection shall be applied.

4.4.6 Functional tests. -

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

4.4.6.1 Functional test. - The number of Mk 22 Mod 0 Dumper Valve Cartridges selected from each lot for the functional test shall be in accordance with the requirements of Table III, Inspection Level II of MIL-STD-105 at an AQL of 0.04. The cartridges shall be conditioned at +70 ± 5°F for 24 hours and fired in a test fixture equivalent to that described in BUORD LD 419699. The vent plug, made from an aircraft cadmium plated bolt drilled out to 3/8 inch diameter, shall be replaced after each firing when chamber pressure is being measured. The volume of the chamber including the cartridge is equal to 36.5 cu. in. Each sample cartridge shall be assembled in the test fixture assembly and subjected to an open circuit potential of 24 volts a.c., using the probe and the body as terminals. It is important that firm contact on clean bright surfaces is obtained to avoid high contact resistance. The a.c. voltage shall be supplied by an essentially non-inductive source of 0.7 ohms (max.) internal resistance, or by means of a circuit of equivalent characteristics. The shorting clip, which is installed by the manufacturer, shall be removed before the electrical connection to the cartridge is made.

4.4.6.2 Misfire. - One or more misfires shall cause rejection of the lot unless the misfire is clearly attributable to faulty test equipment or procedure.

4.4.6.3 Hangfire. - One or more hangfires shall cause rejection of the lot. A hangfire is obtained if the interval between application of the firing current and case opening is more than 0.010 second.

4.4.7 Ballistic test. -

4.4.7.1 The number of cartridges selected from each lot for the ballistic test shall be in accordance with the requirements of Table A-2, Inspection Level IV of MIL-STD-414 at an AQL of 0.04. Cartridges shall be fired in a "testing chamber" as provided in 4.4.6.1, and adapted to measurement of pressure vs. time. The

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

chamber shall be thoroughly cleaned before each firing and the cartridge temperature shall be 70°±5°F. A record of pressure versus time shall be taken on each firing. Minimum firing voltage shall be 24 volts a.c. or d.c. One or more misfires or hangfires shall result in the rejection of the lot represented. Cartridges for ballistic test may form a part of the sample required under "Functional test". Acceptability is to be based in accordance with conditions specified in 4.4.7.2 and 4.4.7.3.

4.4.7.2 Chamber pressure. - The lot shall be accepted if the total estimated percent defective $p = p_U + p_L$ when computed as shown in example B-4, MIL-STD-414, is less than the maximum allowable percent defective M for an AQL of (0.04); where (U) is equal to upper maximum pressure 25,700 psi and (L) is equal to the lower maximum pressure 17,000 psi.

4.4.7.3 Time to maximum pressure. - The lot shall be accepted if the total estimated percent defective $p = p_U + p_L$, when computed as shown in example B-4, MIL-STD-414, is less than the maximum allowable percent defective M for an AQL of (0.04); where (U) is equal to upper time to maximum pressure 16 milliseconds and (L) is equal to the lower time to maximum pressure 5 milliseconds.

4.4.8 Retest. - There shall be no retests.

4.4.8.1 Test failure. - If test failure is due to improper functioning of test equipment or to causes not related to the requirements for which the cartridges are being tested the original test results should be discarded and the test reconducted in accordance with 4.4.6.1 with a new sample of cartridges.

.4.4.9 Change in propellant lot. - Whenever a change in propellant lot occurs, validity of the charge determination shall be verified by firing over the temperature range from +70°F to 200°F±5°F. In addition cartridges shall be subjected for 90 days at a temperature of 200°F±5°F and tested in accordance with 4.4.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

4.5 Test results. - Results of ballistic test (4.4.7) shall be forwarded to the Bureau of Naval Weapons and the procuring activity.

5. PREPARATION FOR DELIVERY

5.1 Packaging. -

5.1.1 Level A. - In addition to the following, Level A packaging shall be in accordance with the Code of Federal Regulations 49 CFR 71-78.

5.1.1.1 Inner container. - One cartridge shall be packaged in accordance with LD 419695.

5.1.2 Level B. - Not applicable.

5.1.3 Level C. - Not applicable.

5.2 Packing. -

5.2.1 Level A. - In addition to the following, Level A packing shall be in accordance with the Code of Federal Regulations, 49 CFR 71-78.

5.2.1.1 Outer container. - Eight inner containers as described in 5.1.1.1 shall be packed in accordance with LD 419696.

5.2.2 Level B. - Not applicable.

5.2.3 Level C. - Not applicable.

5.3 Marking. - Cartridge marking shall be as specified on Bureau of Naval Weapons Drawing LD 491827. In addition, packaging and packing markings shall be in accordance with the explosive section of the Interstate Commerce Commission regulations and MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

6. Notes. -

6.1 Intended use. - The Mk 22 Mod 0 Dumper Valve Cartridge is an electrically fired cartridge designed to provide the power to shear a steel disc in the runaway steam dumper valve of the aircraft catapult system. Shearing of the disc in an emergency permits the valve to open very rapidly, thereby exhausting steam from the main launching cylinders.

6.2 Ordering data. -

6.2.1 Data cards. - Data cards, five inches by eight inches, printed as shown below, shall be completed for each lot of cartridges. Two of these shall accompany the shipping ticket; three shall be forwarded to the Bureau of Naval Weapons; five shall be furnished the Inspector; one shall be furnished to the procuring activity; and one shall be placed in each packing container.

MK 22 MOD 0 DUMPER VALVE CARTRIDGE

Manufacturer_____ Dwg. No._____

Spec. No._____ Loaded By_____

Contr. No._____ Req. No._____

Lot No._____ No. in Lot _____

No. in Box _____ Date (Mo. & Yr.)_____

Propellant Lot_____ Igniter Lot No._____

Ignition Element Lot No.____

6.3 General safety precautions. -

6.3.1 The loading, assembly, and handling of explosives, ammunition, ammunition components, fuzes, detonators, primers, tracers, boosters, pyrotechnics, etc., and sub-assemblies thereof, involve hazardous

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

operations and therefore require suitable explosives safety precautions. Use of this specification shall not be construed as to relieve the contractor or manufacturer of responsibility for the safety of his operations. Listed below are the minimum provisions which a contractor or manufacturer (loader) of the above items should observe in order to fulfill his responsibility for safety. At Bureau of Naval Weapons, Navy Department, and other government plants, these provisions are mandatory. Such other warnings and precautions, pertinent to the operational effectiveness or safety during use or loading of the specified item, are included in the detail provisions of the specification.

6.3.2 All loading operations should be conducted in a neat and orderly manner.

6.3.3 Safe equipment and methods should be utilized for transporting and handling explosives and loaded parts. Where required, remote control barricaded handling equipment shall be used for explosive operations, such as mixing, pouring, weighing, charging, sifting, drying, pressing, casting, crimping, etc.

6.3.4 Personnel handling detonators, primers, delay elements, lead-ins, boosters, and related parts which effect functioning, should in so far as practicable, avoid using bare fingers or improper equipment in order to prevent damage, corrosion, or deterioration from perspiration or other contaminating deposits.

6.3.5 The exposure of explosive materials and related parts should be so controlled as to minimize the absorption of moisture from the atmosphere or other sources during loading and handling operations.

6.3.6 All explosives and completely or partially loaded items should be stored in suitable storage magazines located in accordance with the American Table of Distances (ATD) or other applicable safety standards; and, while in process, in safety lockers

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

and chests if in loading rooms, or in adequate ready or service magazines located in accordance with Intra-plant distances when outside of loading rooms. For Navy explosives loading plants, the provisions of the Armed Services Explosives Safety Board covering quantity-distance regulations for explosives, shall apply.

6.3.7 Proper care should be exercised at all times to protect personnel from accidents, fires or explosions, and to limit damage to equipment and loading areas. In this connection, the following precautionary measures should be observed:

6.3.7.1 Employ properly proportioned and properly located protective barricades, screens or shields at all required points.

6.3.7.2 Keep only minimum limited quantities of explosives and completed or partially loaded parts present at each stage of operation.

6.3.7.3 Keep explosives and explosive parts in approved covered receptacles with covers in place when material is not being taken out of or put into the receptacles. Where necessary, receptacles should be conductive to ground electrostatic charges.

6.3.7.4 Protect operations from electrostatic charges by effectively grounding all machinery, equipment, and fixtures; and, where necessary, employ suitable grounded conductive coverings for floors, work benches and tables, and workers' conductive shoes. Workers' clothing of a type to minimize the accumulation of static charges should be employed. Fabrics such as silk and nylon, which promote static generation should be avoided. Additional grounding devices such as grounded bracelets for workers should be employed where operations are conducted with items which are unusually sensitive to initiation by static electricity. Such items include initiating explosives, tracer mixtures, and low-energy type electric primers, detonators and

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

squibs. The latter types of items should have the free ends of lead wires bared and twisted together, and be packed in relatively small groups wrapped in bare non-insulated aluminum foil or other uncoated metal foil. During assembly and processing operations such sensitive electric items should be short circuited by clips or other devices until installed with safety shunt in the final device. Additional precautions for these items should include mechanical shielding to contain or deflect fragments and blast, also electrical shielding of these items from induced electric currents generated by sources such as lightning, static, radiations from communications apparatus, radar, or high frequency heating apparatus, etc. Where necessary for safety, humidity (See para. 6.3.5) of work rooms should be increased, as required to lessen electrostatic effects without excessive moisture absorption.

6.3.7.5 Protect all explosive operations from effects of electric current originating from equipment such as soldering irons, heaters, switches, wiring, motors, lights, test instruments, etc. by suitable insulation, grounding, separation or shielding. Such electric sources may initiate explosives by heat, sparks, arcs, or by completing an electric circuit through an electric primer, detonator, or squib. Circuits may be inadvertently completed, for example, from a defective electric soldering iron through a grounded contact. All electric types of primers, detonators or squibs provided with wire leads should have the free ends of the wires bared and twisted together to short circuit each unit, except when in process of assembly into a finished item. Where practicable, removable short circuiting clips, or other devices should be employed during manufacturing operations involving electric primers, detonators or squibs.

6.3.7.6 Enforce, where necessary, the wearing of suitable safety footwear, gloves, goggles, respirators, and impregnated garments to protect personnel against burns, poisoning and associated industrial hazards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.

6.3.7.7 Allow no fires or exposed electrical or other sparking equipment, and little or no flammable material to be present in loading, handling and storage spaces. Enforce proper "Match" and "No Smoking" rules where necessary.

6.3.7.8 Enforce good housekeeping and maintain effective policing, inspection and supervisory methods throughout the loading area and surroundings. Employ effective cleaning methods periodically to minimize the accumulation of explosives or explosive dust and other contamination upon, and assure its removal from, floors, walls, ceilings, ledges, tables, benches, piping, and equipment or the items loaded; also, clean up any spilled material immediately.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:08Z
Check the source to verify that this is the current version before use.