MIL-C-22656B(AS)

22 February 1971
Superseding
MIL-C-22656A(WEP)
7 April 1964

MILITARY SPECIFICATION

CARTRIDGE, IMPULSE, MARK 14 MOD 0

This specification has been approved by the Naval Air Systems Command, Department of the Navy.

1. SCOPE

1.1 This document governs the manufacture, assembly and preparation for delivery of the Cartridge, Impulse, MARK 14 MOD 0 and the methods of inspection and tests upon which product acceptance will be based.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings, and publications, of the issue in effect on date of invitation for bids, form a part of this document to the extent specified herein.

SPECIFICATIONS

Military

MIL-P-116	Preservation, Methods of
MIL-P-223	Powder, Black
MIL-D-21625	Design and Evaluation of Cartridges for Cartridge Actuated Devices
MIL-P-46610	Primers, Percussion, Styphnate and Chlorate, for Small Arms Ammunition

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:14Z
Check the source to verify that this is the current version before use.

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-414	Sampling Procedures and Tables for Inspection by Variables for Percent Defective

DRAWINGS AND ASSOCIATED LISTS

Naval Air Systems Command	(Code Ident 30003)
LD 491824	Cartridge, Impulse, MARK 14 MOD 0, List of Drawings and Specifications
LD 491828	Container, Inner, for Cartridge, Impulse, MARK 14 Type, List of Drawings and Specifications
LD 491829	Container, Outer, for Cartridge, Impulse, MARK 14 Type, List of Drawings and Specifications
1669359	Cartridge, Impulse, MARK 14 MOD 0, Assembly
U. S. Army Munitions Command	(Code Ident 19200)
C 7645339	Primer, Percussion (50M-5061W)

PUBLICATIONS

Bureau of Naval Weapons	(Code Ident 10001)
WR-43	Preparation of Quality Assurance Provisions

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 171-178	Transportation, Explosives and Other Dangerous Articles

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:14Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402. Orders for the above publication should request the latest edition and supplements thereto.)

3. REQUIREMENTS

3.1 General.

3.1.1 The MARK 14 MOD 0 impulse cartridge covered by this specification shall be manufactured in accordance with the drawings listed on LD 491824.

3.2 Materials. All materials used in the manufacture of the cartridges shall conform strictly with the specifications referenced on the respective NAVAIR drawings unless specific approval in writing covering a departure therefrom has been obtained from the Navy cognizant field activity for cartridges prior to manufacture. When alternate materials or methods of cartridge manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.2.1 Preproduction sample. Unless otherwise specified by the procuring activity, a preproduction sample of 94 MARK 14 MOD 0 impulse cartridges shall be manufactured using the same methods and procedures proposed for the production lot. The sample shall be tested as specified in 4.3.2 and is for the purpose of determining that the contractor, prior to starting production, is capable of producing items which comply with the technical requirements of the contract.

3.3 Primary components. For the purposes of this specification the primer and main propellant charge are defined as primary components. See 4.3.3.

3.4 Primer. The primers shall be furnished from lots manufactured within the preceding 12 months. The primers shall be manufactured in accordance with Drawing C7645339, loaded with Remington Arms Company priming mixture 5061W; and shall be from lots which were accepted in accordance with MIL-P-46610, Class 1. See 4.7.1.

3.4.1 X-ray. Primers shall be free of the following defects when examined by x-ray in accordance with 4.7.2: missing or abnormally thin charge; charge broken, cracked or porous; cracked or off-center anvil or other misplaced or deformed inert parts; anvil abnormally close to primer cup dome; and all other observable defects in assembly.

3.5 Propellant charges.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:14Z
Check the source to verify that this is the current version before use.

3.5.1 Quantity. All propellant charges shall be as specified on Drawing 1669359. Charges shall be determined by weight rather than by volume measurements.

3.5.2 Black powder. The moisture content of the black powder shall be determined as specified in MIL-P-223 and at the time of loading shall be within the limits specified therein for the applicable class of black powder being used. See 4.7.3.

3.6 Cartridge inspection.

3.6.1 Visual inspection. Cartridges shall be free of the following visible defects: dents, deep scratches, cracks, burrs, split or cracked lip in the crimped area, damaged "O" ring or closure disc, incomplete or improper sealant application, or any other imperfections which could prevent entry into the firing chamber, or adversely affect performance or resistance to moisture. See 4.7.4.

3.6.2 Leakage. Cartridge leakage rate shall not exceed 10^{-5} cc of air or gas per second when tested in accordance with 4.7.5.

3.6.3 X-ray. Cartridges shall be free of imperfections when examined by x-ray in accordance with 4.7.6.

3.7 Ballistic requirements. Cartridges from each production lot, selected in accordance with 4.7.7.1, shall meet the requirements listed below when subjected to the test prescribed in 4.7.7.1.

3.7.1 Chamber pressure. The lower (L) and upper (U) limits of maximum pressure shall be 3500 psi and 6000 psi, respectively.

3.7.2 Misfire. There shall be no misfires. See 4.7.8.2.

3.7.3 Hangfire. There shall be no hangfires. See 4.7.8.3.

3.8 Packaging, packing and marking. The packaging and packing of cartridges and the container markings shall be in accordance with Section 5. See 4.6.1.

3.9 Workmanship. Cartridges shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention shall be directed to dimensions, finishes and coatings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:14Z
Check the source to verify that this is the current version before use.

of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling. Unless otherwise specified, and when applicable, the sampling plans and procedures used in the determination of the acceptability of products submitted by a supplier shall be in accordance with the provisions of MIL-STD-105 or MIL-STD-414, whichever applies.

4.3 Lots.

4.3.1 Inspection lots. Inspection lot definition, formation and size shall be in accordance with MIL-STD-105 or MIL-STD-414, whichever applies.

4.3.2 Preproduction sample. Before entering into quantity production, an acceptable preproduction sample of 94 MARK 14 MOD 0 impulse cartridges shall be prepared. Of these cartridges, 84 shall be expended in the tests listed below and 10 shall be retained for investigative purposes. A preproduction sample acceptable for environmental and functional testing shall be defined as a sample which has met the requirements of paragraphs 3.3 through 3.6.3 of this specification. Preproduction sample acceptance shall consist of the following tests as prescribed in Table 3 of MIL-D-21625: 40-foot drop (6); 15 g shock (12); vibration (12); temperature and humidity cycling (18). Numbers in parentheses denote the number of cartridges allocated for test. These cartridges (with the exception of the 40-foot drop cartridges), after exposure to environmental treatment, shall be conditioned for a minimum of six hours at +70° ± 5°F together with 12 untreated cartridges and fired in the test fixture of 4.7.7.1. In addition, 24 cartridges shall be temperature conditioned for a minimum of 6 hours, 12 at -65° + 0°F -5°F and 12 at +160° +5°F -0°F, and fired in the test fixture of 4.7.7.1. All cartridges shall fire and produce results within the limits set forth in paragraphs 3.7.1 and 3.7.3, except that the lower (L) limit of maximum pressure for the -65°F firings shall be 2500 psi and the upper (U) limit of maximum pressure for the +160°F firings shall be 7000 psi. The failure of any cartridge to meet the acceptance requirements as stated above shall cause rejection of the preproduction sample.

4.3.3 Production lot. Unless otherwise specified in the contract, the minimum and maximum production lot size shall be 181 and 800 cartridges, respectively. Only primary components from a single lot shall be used in a production lot of cartridges; however, one primary component production lot may be used in more than one cartridge production lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:14Z
Check the source to verify that this is the current version before use.

4.4 Gages. The contractor shall provide gages as necessary to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings.

4.5 Classification of characteristics. The characteristics verified by the tests and examinations herein are classified as Critical, Major or Minor in accordance with WR-43. Tests and examinations that verify critical characteristics are identified by the symbol (C) and major characteristics by the symbol (M). The number following the classification symbol indicates the serial number of test or examination. Tests and examinations which are not annotated with a classification code are classified minor.

4.6 Quality conformance inspection. Quality conformance inspection shall consist of verification of the characteristics classified on the drawings of LD 491824, and verification of the following tests and requirements.

Item	Nature of Requirement Verification	Applicable Paragraphs	Classification (WR-43)
Primary component	Single lot	3.3, 4.3.3	(M101)
Primer	Age, loading and acceptance	3.4, 4.7.1	(C1)
Primer	X-ray	3.4.1, 4.7.2	(C2)
Propellant charge	Type and weight	3.5.1	(C3)
Black powder	Moisture content	3.5.2, 4.7.3	(C4)
Cartridge	Visual inspection	3.6.1, 4.7.4	(M102)
Cartridge	Leakage	3.6.2, 4.7.5	(C5)
Cartridge	X-ray	3.6.3, 4.7.6	(C6)
Cartridge	Ballistic test	3.7, 4.7.7	(C7)
Cartridge	Packaging, packing and container markings	3.8, 4.6.1	(M103)

4.6.1 Packaging, packing and marking. Quality conformance inspection shall be conducted in accordance with the inspection criteria on the applicable drawings referenced in Section 5.

4.7 Tests.

Source: https://assist.dla.mil -- Downloaded: 20261O-19T13:14Z
Check the source to verify that this is the current version before use.

4.7.1 Primer verification. The contractor shall provide verification that the primers to be used were manufactured, loaded and accepted in accordance with the requirements of 3.4 and were furnished from lots manufactured within the preceding 12 months.

4.7.2 Primer x-ray. Examine all primers by x-ray and reject those having any of the defects of 3.4.1. For the most revealing exposure, the primers shall be laid on their sides with the anvil cutouts vertical. Pressure sensitive tape may be used as an aid in positioning the primers.

4.7.3 Moisture content of black powder. Conduct at least one test for each cartridge lot (or daily if this requires more frequent testing) and such additional tests as considered warranted by variations in conditions or process. Samples may be collected at the site of loading from the powder container, or taken from cartridges prior to sealing the black powder charge in the cartridges. The presence of moisture in excess of the limitations of MIL-P-223 shall cause suspension of loading until corrective measures have been taken.

4.7.4 Visual inspection. Examine all completely assembled cartridges and reject those having any of the defects noted in 3.6.1.

4.7.5 Leakage. Each cartridge in the preproduction sample or production lot ballistic sample shall be leak tested in a dry gas or dry air leak tester. Cartridges which exhibit a leak rate in excess of 10^{-5} cc/sec of air or gas at a pressure differential of 1.0 ± 0.1 atmosphere shall be considered defective. Cartridges of the preproduction sample which exhibit a leakage defect shall be rejected. If one or more cartridges of the production lot sample exhibit a leakage defect, then a 100 percent leak test of the lot being tested shall be required at no additional expense to the Government. Cartridges which exhibit a leak rate in excess of that specified above shall be rejected.

4.7.6 X-ray examination. Examine all cartridges by x-ray and reject those having any observable imperfections in assembly. Particular attention shall be given to the presence of the propellant charge.

4.7.7 Ballistic tests.

4.7.7.1 The number of cartridges selected from each production lot for the ballistic tests shall be in accordance with the requirements of Table A2 of MIL-STD-414, Inspection Level IV and an AQL of 0.04. The cartridges shall be conditioned for a minimum of 6 hours at $+70^{\circ} \pm 5^{\circ}$F and fired in a closed chamber having an internal volume, with an expended cartridge in place, of 5.61 ± 0.05 cubic inches and adapted for measurement of pressure. A record of pressure versus time and of the elapsed time between actuation of the firing mechanism and start of pressure rise

Source: https://assist.dla.mil -- Downloaded: 20260-19T13:14Z
Check the source to verify that this is the current version before use.

shall be taken by suitable instrumentation for each firing. In addition to the sample of cartridges for the above test, 10 additional cartridges shall be furnished from each production lot for investigative purposes.

4.7.8 Criteria of acceptability.

4.7.8.1 Chamber pressure. The chamber pressure shall meet the requirements of 3.7.1. Lot acceptability shall be determined in accordance with the applicable provisions of MIL-STD-414 at an AQL of 0.04.

4.7.8.2 Misfire. The failure of any cartridge to fire shall result in rejection of the lot represented, unless such failure is plainly attributable to faulty test equipment or procedure.

4.7.8.3 Hangfire. One or more hangfires shall result in rejection of the lot represented. A hangfire is defined as a firing in which the elapsed time between actuation of the firing mechanism and start of pressure rise exceeds 0.050 second.

4.8 Retest. There shall be no retests.

4.9 Test failure. If test failure is attributable to an assignable cause, excluding the test cartridges, original test results should be discarded and that part of the test reconducted.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. For definitions of packaging levels, see 6.4.

5.1.1 Level A. Level A packaging shall be used for packaging of all production lots for service use. One cartridge shall be packaged in an inner container in accordance with the drawings listed on LD 491828.

5.1.2 Level B. Not applicable.

5.1.3 Level C. When directed by the procuring activity, those cartridges which are intended for expenditure in preproduction sample testing and for production lot acceptance tests shall be packaged in accordance with Method III of MIL-P-116 and with the Code of Federal Regulations 49 CFR 171-178.

5.2 Packing. For definitions of packing levels, see 6.4.

5.2.1 Level A. Level A packing shall be used for packing of all production lots for service use. Eight inner containers as described in 5.1.1 shall be packed in accordance with the drawings listed on LD 491829.

Source: https://assist.dla.mil -- Downloaded: 20261O-19T13:14Z
Check the source to verify that this is the currentversion before use.

5.2.2 Level B. Not applicable.

5.2.3 Level C. When directed by the procuring activity, cartridges intended for expenditure in preproduction sample testing and for production lot acceptance tests and are packaged in accordance with 5.1.3 shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Shipping containers shall be in accordance with the Code of Federal Regulations 49 CFR 171-178.

5.3 Markings.

5.3.1 Special markings. Marking of exterior containers shall be in accordance with the Code of Federal Regulations 49 CFR 171-178.

5.3.2 Normal markings. Unless otherwise specified in the contract or order, the marking information on unit packages and shipping containers shall be in accordance with the drawings listed on LD 491828 and LD 491829, respectively. The specified marking information shall be applied to the containers in accordance with the applicable provisions of MIL-STD-129.

6. NOTES

6.1 Intended use. The MARK 14 MOD 0 impulse cartridge was originally designed for use in jettisoning the canopy of the F-8A aircraft during the emergency escape sequence.

6.2 Ordering information. Procurement documents should specify the following:

a. title, number and date of this specification;

b. whether preproduction inspection is required and, if so, specify the test activity;

c. production lot size and test activity (see 4.3.3);

d. items of data required for each preproduction and production lot (see 6.3).

6.3 Data. For the information of contractors and contracting officers, any of the data specified in (a) subparagraphs below, (b) applicable documents listed in Section 2 of this specification or (c) referenced lower-tier documents need not be prepared for the Government and shall not be furnished to the Government unless specified in the contract or order.

6.3.1 Test report. Results of ballistic tests shall be forwarded to the Naval Air Systems Command (AIR-53222A) and the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:14Z
Check the source to verify that this is the current version before use.

6.3.2 Data cards. The contract or order should state the format, quantity and destination of data cards.

6.4 Definitions. For purposes of this specification, the following definitions apply.

6.4.1 Level A packaging. The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during handling, shipment, indeterminate storage and world-wide redistribution.

6.4.1.1 Level C packaging. The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during shipment from supply source to the first receiving activity for immediate use. This level may conform to supplier's commercial practice when such meets the requirements of this level.

6.4.2 Level A packing. The degree of packing which will afford adequate protection during shipment, handling, indeterminate storage and world-wide redistribution.

6.4.2.1 Level C packing. The degree of packing which will afford protection against damage during direct domestic shipment from the supply source to the first receiving activity for immediate use. This level in general will conform to applicable carrier rules and regulations and may be the supplier's commercial practice when such meets the requirement of this level.

6.5 Explosives safety precautions. Safety precautions for explosive-loaded items are contained in MIL-STD-1314.

6.5.1 Applicability. The loading, assembly and handling of the explosives, explosive-loaded subassemblies and the finished items covered by this specification involve hazardous operations and therefore require suitable explosives safety precautions. At plants of the Naval Air Systems Command, Department of the Navy, and other Government plants where the Government is responsible for safety, the precautions listed in MIL-STD-1314 are mandatory. These same minimum provisions are recommended for observance by a contractor or manufacturer that explosively loads or assembles the item covered in this specification in order to fulfill his own safety responsibility.

Project No. 1377-N464

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:14Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION
MIL-C-22656B(AS) CARTRIDGE, IMPULSE, MARK 14 MOD 0

ORGANIZATION *(Of submitter)*

CITY AND STATE

CONTRACT NO.

QUANTITY OF ITEMS PROCURED

DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*

DATE

DD FORM 1 APR 63 1426

C-8379

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T13:14Z
Check the source to verify that this is the current version before use.