MIL-W-27888B
17 November 1977
SUPERSEDING
MIL-W-27888A
22 October 1965

MILITARY SPECIFICATION

WEIGHT, PARACHUTE PACKING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a two-compartment, cotton duck bag, filled with lead shot, for use as a parachute packing aid.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner

MILITARY

MIL-L-10547 - Liners, Case, and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible
MIL-G-16491 - Grommet, Metallic
MIL-C-43006 - Cloth, Laminated, Vinyl-Nylon, High-Strength Flexible

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1670

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:59Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

DRAWING

U.S. AIR FORCE

66C38599 - Weight, Parachute Packing

(Copies of specifications, standards and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), the contractor shall furnish a sample for first article inspection and approval (see 4.3 and 6.4).

3.2 Materials. Unless otherwise specified herein, all materials shall be as specified on the drawing (see 6.6).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:59Z
Check the source to verify that this is the current version before use.

3 Design and construction. The design and construction shall conform to specifications, standards, and drawing U.S. Air Force 66C38599 listed in section 2 and as specified herein.

3.3.1 Type 301 stitching. Thread breaks or bobbin runouts, or two or more consecutive skipped stitches, shall be overstitched not less than 1 inch (25 mm) each end. Run-offs shall be restitched to conform to the required stitch pattern. Ends of stitching shall be backstitched a minimum of 1/2 inch (13 mm), except where turned under in a hem or held down by other stitching. Thread tension shall be maintained so that there will be no loose stitching and the lock will be imbedded in the materials sewed. All thread ends shall be trimmed.

3.3.2 Setting of grommets. The hole for the grommet shall be smaller than the grommet barrel. The grommet shall be set by forcing the barrel through the hole and clinching securely without cutting the material.

3.4 Workmanship. All components and assemblies of the parachute packing weights shall be free from dirt, grease, oil or other foreign matter. Seams and stitching shall be free of needle or dog chews, omitted and unrelated stitching, open and broken seams and loose threads. Grommets shall be securely clinched without split edges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3).
2. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required, it shall be examined for the defects in table I and dimensions specified. The presence of any defect listed in table I or any dimension not within specified requirements shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:59Z
Check the source to verify that this is the current version before use.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.4.2 In-process inspection. Examination shall be made of the following operation to establish conformance to specified requirements. Whenever non-conformance is noted, correction shall be made to the items affected and to the operation.

4.4.2.1 Grommet hole size. The grommet barrel shall fit tightly in the prepared hole (see 3.3.2).

4.4.3 End item inspection. The inspection lot shall consist of all the same items offered for inspection at one time. The sample unit shall be one completely fabricated parachute packing weight.

4.4.3.1 Visual examination. Examination shall be made of the weight for defects in table I. The inspection level shall be II and the acceptable quality level (AQL) shall be 2.5 for major defects and 6.5 for total defects expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Materials	Color not as specified		X
Construction and assembly	Not assembled or joined as specified; contents not proportionate in interior sacks	X	
Cleanness	Dirt, grease, oil, or other foreign matter		X
	Thread ends not trimmed throughout		X
Stitches and stitching	Not type of stitch specified	X	
	Stitch pattern not as specified	X	
	Stitch margin or gage not as specified		X
	Any row of stitching missing	X	
	Needle chews	X	
	Thread breaks, bobbin runouts, and two or more consecutive skipped stitches not overstitched as specified	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:59Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Minor
Stitches and stitching (cont'd)	Ends of stitching not backstitched as specified		X
	Loose tension resulting in loose top or bobbin thread; or tight tension resulting in tightness or puckering of material at stitch line		X
	One stitch per inch under minimum specified		X
	Two or more stitches per inch under minimum specified	X	
	One or more stitches per inch over maximum specified		X
Cloth, vinyl-nylon, or thread (as applicable)	Not type or size specified	X	
	Cut, hole, thin or weak area	X	
	Raw edges		X
Grommet	Cuts surrounding fabric	X	
	Insecurely clinched, e.g., can be turned by hand	X	
	Split edges		X

4.4.3.2 Dimension and weight examination. Examination shall be made of the end item to determine compliance with dimensions and weights specified. Any nonconformance shall constitute a defect. The inspection level shall be S-3 with and AQL of 2.5 expressed in terms of defects per hundred units.

4.4.4 Inspection of packaging. An examination shall be made to determine that preservation-packaging, packing, and marking are in compliance with section 5. Defects shall be as specified in table II. The sample unit shall be one shipping container fully prepared for delivery, except that it need not be sealed. The lot shall be the number of shipping containers offered for inspection at one time. The inspection level shall be S-2 and the AQL shall be 2.5 expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:59Z
Check the source to verify that this is the current version before use.

TABLE II. Examination of packaging

Examine	Defect
Marking	Omitted; incorrect; illegible; improper size, location, sequence, improper method of application.
Materials	Component missing, damaged, defective, or not as specified.
Workmanship	Improper packaging, contents loose or not snug fit; incomplete or improper closure of case liners or containers; inadequate or improper application of components such as cleats, nails, strapping; bulging or distortion of containers.
Contents	Number per container not as specified.

5. PACKAGING

5.1 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.1.1 Level A packing. Forty weights shall be packed one in length, four in width, and ten in depth in a shipping container conforming to class 2, style 4, type 3 load of PPP-B-621, except that the minimum thickness of the sides, top and bottom shall be 3/4 inch (19 mm) minimum. Thickness of ends shall be 1-1, inches (27 mm). Inside dimensions of the shipping containers shall approximate 20-1/4 inches (514 mm) in length, 10 inches (254 mm) in width, and 8-3/4 inches (222 mm) in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be provided with a type I or II, grade C, sealed case liner conforming to MIL-L-10547. Each shipping container shall be closed and reinforced with steel strapping in accordance with the appendix of the container specification.

5.1.2 Level B packing. Forty weights shall be packed as specified in 5.1.1 except that the case liner shall not be required.

5.1.3 Commercial packing. Weights shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification or National Motor Freight Classification, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:59Z
Check the source to verify that this is the current version before use.

5.2 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The weight covered by this specification is used to hold canopy gores in position during the folding of the canopy and stowing of the suspension lines when packing the parachute.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) When a first article is required (see 3.1, 4.3 and 6.4).
(c) Stock number.
(d) Selection of applicable level of packing (see 5.1).

6.3 For access to standard shade samples, address the procuring activity issuing the invitation for bids.

6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Armed Services Procurement Regulations ASPR 7-104.55. The first article should be a preproduction sample, initial production item, or other specific item described under the definition of a first article in the ASPR. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instruction in all procurement instruments regarding arrangement for inspection and approval of the first article.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

6.6 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.2).

Custodians:

Army - GL
Navy - AS
Air Force - 99

Review activity:

Army - AV

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 1670-0450

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:59Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-W-27888B - Weight, Parachute Packing

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:59Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRXNM-TD G

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314

Commander
US Army Natick Research and Development Command
ATTN: DRXNM-TD G
Natick, MA 01760

NATICK OP 1 JUL 77
FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T12:59Z
Check the source to verify that this is the current version before use.