MIL-C-50214A (MU)
16 December 1970
SUPERSEDING
MIL-C-50214 (MU)
15 January 1969
(See 6.8)

MILITARY SPECIFICATION

CARTRIDGE, 40MM, WHITE STAR, CLUSTER, XM585

LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of cartridge designated as Cartridge, 40MM, White Star, Cluster, XM585.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-223	-	Powder, Black
MIL-A-2550	-	Ammunition and Special Weapons, General Specification for
MIL-I-45607	-	Inspection Equipment, Supply and Maintenance of

FSC: 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables Inspection by Attributes (ABC-STD-105)
MIL-STD-109	-	Quality Assurance Terms and Definitions
MIL-STD-331	-	Fuze and Fuze Components, Envirnmental and Performance Tests for
MIL-STD-650	-	Explosive: Sampling, Inspection and Testing
MIL-STD-1168	-	Lot Numbering of Ammunition
MIL-STD-1234	-	Pyrotechnics, Sampling, Inspection and Testing
MIL-STD-1235	-	Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

9207987	-	Cartridge, 40MM, White Star, Cluster, XM585

PUBLICATIONS

ARMY

ET-9207987	-	Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

CODE OF FEDERAL REGULATIONS

Title 49 - Transportation, Parts 171-179

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders should specify 49 CFR 171-179 [latest revision].)

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Cartridge.-The cartridge shall comply with all requirements specified on drawing (dwg.) 9207987, all associated drawings, and with all requirements specified in applicable specifications.

3.3 Transportation vibration.-The cartridge shall comply with the following requirements when tested as specified in 4.4.7.

3.3.1 The cartridge shall be safe to transport following this test (see 6.6).

3.3.2 There shall be no evidence of external damage to the cartridge that will affect the intended function (see 6.7).

3.4 Functioning.-The cartridge shall comply with the following requirements when tested as specified in 4.4.8.

3.4.1 Altitude.-The cartridge shall function at an average altitude of 600 $\pm$ 100 feet.

3.4.2 Burning time of each White Star pellet.-All white star pellets shall burn a minimum (min.) of six (6) seconds.

3.4.3 Firing.-No projectile shall stick in the gun bore.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

3.4.4 Hot temperature (160 degrees F. plus or minus 5 degrees F).-The cartridge shall comply with the requirements of 3.4.1, 3.4.2, and 3.4.3.

3.4.5 Ambient temperature (70 degrees F. plus or minus 5 degrees F.).-The cartridge shall comply with the requirements of 3.4.1, 3.4.2, and 3.4.3.

3.4.6 Cold temperature (-65 degrees F. plus or minus 5 degrees F.).-The cartridge shall comply with the requirements of 3.4.1, 3.4.2, and 3.4.3.

3.5 Workmanship.-All parts and assemblies shall be fabricated, loaded and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required marking and stamping shall be neat and sharply defined.

3.6 Submission of results of contractor-conducted examinations and tests.-The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract (see 6.5).

3.7 First article testing.-This specification makes provisions for first article testing. Submission of first article quantity by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.1.1 Submission of product.-At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies will all of the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with an identification and date of changes thereto.
c. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.
d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First article inspection.-

4.2.1 Submission.-The contractor shall submit a first article quantity as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.2.2. (see 6.1). The first article sample shall consist of four hundred and seventy-five (475) cartridges to a Government proving ground.

4.2.2 Prior to submission.-Prior to submission of the four hundred and seventy-five (475) cartridges to a Government proving ground for functioning tests, the 475 assemblies shall be inspected by the Government at the contractor's plant for the following tests:

4.2.2.1 Transportation vibration.-The four hundred and seventy-five (475) cartridges, packed in their regular shipping containers, shall be subjected to this test. If any assembly fails to comply with any of the applicable requirements, the first article quantity shall be rejected. In the event of rejection,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity. Until the first article quantity is accepted, the contractor is not authorized by the Government to proceed with regular production unless otherwise directed by the Contracting Officer.

4.2.2.2 Air pressure.-After completion of test specified in 4.2.2.1, the 475 cartridges shall be removed from their regular shipping containers and subjected to this test. If any assembly fails to comply with the applicable requirement, the first article quantity shall be rejected. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity. Until the first article quantity is accepted, the contractor is not authorized by the Government to proceed with regular production unless otherwise directed by the Contracting Officer.

4.2.3 Proving ground tests.-The cartridges shall be subjected to the following tests:

4.2.3.1 Functioning at Hot temperature (see 3.4.4).-Eighty (80) cartridges shall be subjected to this test.

4.2.3.2 Functioning at ambient temperature (see 3.4.5).-Three-hundred and fifteen (315) cartridges shall be subjected to this test.

4.2.3.3 Functioning at cold temperature (see 3.4.6).-Eighty (80) cartridges shall be subjected to this test.

4.2.4 Rejection.-The first article sample shall be rejected if:

a. Any critical defect occurs in any phase (see Table III).
b. Average altitude of the total sample fails the applicable requirement (See Table III).
c. A total of eight (8) or more in the hot phase fail any of the following:
(1) Less than 5 stars (See Table III)
(2) Item fails to function (see Table III).
Burning time should be reported for informational purposes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

d. A total of twenty-two (22) or more in the ambient phase fail any of the following:

(1) Burning time incorrect (see 3.4.2).
(2) Less than 5 stars (See Table III).
(3) Item fails to function (see Table III).

e. A total of eight (8) or more in the cold phase fail any of the following:

(1) Less than 5 stars (See Table III).
(2) Item fails to function (see Table III).

Burning time should be reported for informational purposes.

f. A total of twenty-two (22) or more of the combined sample fail any of the following:

(1) Burning time incorrect (See 3.4.2) (Ambient Only)
(2) Less than 5 stars (See Table III).
(3) Item fails to function (See Table III).

g. Two (2) or more of the total samples have an altitude less than 350 ft (see Table III).

In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity. Until the first article quantity is accepted, the contractor is not authorized by the Government to proceed with regular production unless otherwise directed by the Contracting Officer.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot of cartridges shall contain:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

a. Projectile metal parts from one interfix lot number from one manufacturer.
b. Black powder from not more than one lot number.
c. Delay composition from not more than one lot number.
d. Igniter composition from not more than one lot number.
e. Illuminant composition produced by one manufacturer under one continuous set of operating conditions and which consist of one or more batches that have been subjected to the same unit chemical or physical mixing process intended to make the final product homogeneous.
f. Cartridge case loaded assemblies from one interfix lot number from one manufacturer.

4.3.2 Examination.-The examination listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and shall be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Body assembly (See Dwg. 9207992 covering a detail of Dwg. 9207990).-

Categories	Defects	Method of Inspection	Code No. (See 6.2)
Critical:	None defined		
Major:	AQL 0.40 Percent		
101.	Concentricity of rotating band of end plug assembly with outside diameter of body	Gage	01001

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

Minor:	AQL 1.50 Percent		
201.	Total length	Gage	01002
202.	Excessive adhesive on exterior surfaces	Visual	01003
203.	Primer missing on indicated surfaces	Visual	01004
204.	Evidence of poor workmanship (see 3.5)	Visual	01005

4.3.2.2 White star pellet assembly (See Dwg. 9212688 covering a detail of Dwg. 9207991).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 Percent		
101.	First fire composition missing	Visual	02001
102.	Diameter	Gage	02002
Minor:	AQL 0.65 Percent		
201.	Tape missing	Visual	02003
202.	Evidence of poor workmanship (See 3.5)	Visual	02004

4.3.2.3 Projectile assembly, prior to assembling ogive (see dwg. 9207991 covering a detail of dwg. 9207987).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 Percent		
101.	Closing disc missing	Visual	03001
Minor:	None defined		

4.3.2.4 Projectile assembly after painting (see dwg. 9207991) covering a detail of dwg. 9207987).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.40 Percent		
101.	Body diameter	Gage	04001
Minor:	AQL 1.00 Percent		
201.	Total length	Gage	04002
202.	Evidence of poor workmanship (see 3.5)	Visual	04003

4.3.2.5 Cartridge (see dwg. 9207987).-

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Chamber gage failure	Gage	05001
2.	Incorrect ogive	Visual	05002
3.	Marking incorrect	Visual	05003
Major:	AQL 0.40 Percent		
101.	Marking unidentifiable	Visual	05004
Minor:	AQL 1.50 Percent		
201.	Total length	Gage	05005
202.	Excessive adhesive	Visual	05006
203.	Evidence of poor workmanship (See 3.5)	Visual	05007

4.3.2.6 Unsealed metal box (see dwg. 9209204).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 0.65 Percent		
101.	Incorrect number of cartridges	Visual	06001
102.	Desiccant bags missing	Visual	06002
103.	Rubber gasket damaged or improperly assembled	Visual	06003
Minor:	AQL 1.00 Percent		
201.	Fillers missing	Visual	06004
202.	Tube missing	Visual	06005

4.3.2.7 Sealed metal box (see dwg. 9209204).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor:	AQL 1.00 Percent		
201.	Marking misleading or unidentifiable	Visual	07001
202.	Contents loose	Manual	07002

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.3.2.8 Sealed wooden packing box (see dwg. 9209205).-

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major: None defined			
Minor:	AQL 1.50 Percent		
201.	Marking misleading or unidentifiable	Visual	08001
202.	Contents loose	Manual	08002
203.	ICC nomenclature missing	Visual	08003

4.3.3 Testing.-

4.3.3.1 Moisture content (see Table I), Major defect.-

TABLE I

Material	Code No.
Delay composition (see dwg. 9207998)	09001
Powder pellet (see dwg. 9209181)	09002
Disc, retaining (see dwg. 9208000)	09003
Illuminant composition (see dwg. 9212686)	09005
Igniter composition (see dwg . 9207998)	09006
Spacer, felt (see dwg. 9207997)	09007

The contractor shall provide adequate controls to insure compliance with the requirements and shall test for verification at least one sample of each material from each eight hours' production of cartridges. Composite samples shall not be used. If the moisture content of a sample exceeds the requirement, and loading has not begun, that quantity of material represented by the sample shall be rejected. If assemblies have been loaded with material containing excessive moisture, the remaining material that is represented by the sample together with all cartridges loaded with the non-conforming material shall be rejected. The tests shall be performed as specified in 4.4.1 using equipment in accordance with 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.3.3.2 Specific gravity of pellet powder (see dwg. 9209181), Major defect, Code No. (10001).-Four (4) pellets shall be selected from each four (4) hours' production and subjected to this test. If any pellet fails to comply with the applicable drawing requirement, the four (4) hours' production represented by the sample shall be rejected. The test shall be performed as specified in 4.4.2 using equipment in accordance with 4.3.4.

4.3.3.3 Candle power of pellet assembly (see dwg. 9212688), Major defect, Code No. (11001).-Beginning with the first lot produced and continuing until three (3) acceptable lots (lots not accepted by disposition) have been accepted, eighty (80) assemblies shall be selected from each lot for this test. If three (3) or more assemblies fail to comply with the requirement specified on the applicable drawing, the lot shall be rejected. The test shall be performed as specified in 4.4.3 using equipment in accordance with 4.3.4.

4.3.3.4 Candle power of pellet assembly (see dwg. 9212688), Regular Production, Major defect, Code No. (12001).-After three (3) acceptable lots have met the criteria of 4.3.3.3, the Government inspector shall select thirty-two (32) assemblies from each lot for this test. If two (2) or more assemblies fail to comply with the requirement specified on the applicable drawing, the lot shall be rejected. At the start of production, or when there has been a lapse of 90 days, or when a major design change occurs as determined by the Government inspector, the criteria of 4.3.3.3 shall apply. The test shall be performed as specified in 4.4.3 using equipment in accordance with 4.3.4.

4.3.3.5 Security of end plug assembly on body assembly (see dwg. 9207992), Major defect, Code No. (13001).-The sampling plan for this test shall be in accordance with MIL-STD-105, code Letter H, single plan, with an AQL of 2.50 percent. The test shall be performed as specified in 4.4.4 using equipment in accordance with 4.3.4. If material of body or end plug is cause of rejection, it shall be declared a "no test" and replaced with another unit and retested.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.3.3.6 Security of projectile assembly (See dwg. 9207992 or 9207987, as applicable), Major defect, Code No. (14001).-The sampling plan for this test shall be in accordance with MIL-STD-105, Code Letter H, single plan, with an AQL of 2.50 percent. The test shall be performed as specified in 4.4.5 using equipment in accordance with 4.3.4. If material of end plug is cause of rejection, it shall be declared a "no test" and replaced with another unit and retested.

4.3.3.7 Air pressure (see dwg. 9207987), Major defect, Code No. (15001).-This test shall be conducted 100 percent. Any cartridge which fails to comply with the requirement specified on the applicable drawing shall be classified defective and removed from the lot. The test shall be performed as specified in 4.4.6 using equipment in accordance with 4.3.4.

4.3.3.8 Transportation vibration (see 3.3), Major defect, Code No. (16001).-The cartridges shall be observed and examined visually without disassembly for any evidence of failure to comply with the requirements as classified in Table II when tested as specified in 4.4.7.

TABLE II

Defect	Classification	Code No.
Cartridge not safe to transport following test (see 3.3.1)	Critical	16002
Cartridge damaged after test (see 3.3.2)	Major	16003

4.3.3.8.1 After completion of test specified in 4.3.3.7 and beginning with the first lot produced and continuing until three (3) acceptable lots (lots not accepted by disposition) have complied with the acceptance criteria specified in Table II, three hundred (300) cartridges shall be selected from each lot, packed in their regular shipping containers and subjected to this test. The lot shall be rejected if any defect as classified in Table II occurs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.3.3.9 Air pressure (see dwg. 9207987), Major defect, Code No. (17001).-After completion of test specified in 4.3.3.8.1, the three hundred (300) samples from each lot shall be subjected to this test. If nine (9) or more cartridges fail to comply with the requirements specified on the applicable drawing, the lot shall be rejected. The test shall be performed as specified in 4.4.6 using equipment in accordance with 4.3.4. Cartridges which fail this test shall be discarded and replaced with units which have been subjected to test specified in 4.3.3.8 prior to subsequent testing.

4.3.3.10 Functioning (see 3.4), Major defect, Code No. (18001).-The cartridges shall be observed for any evidence of failure to comply with the requirements as classified in Table III when tested as specified in 4.4.8.

TABLE III

Defect	Classification	Code No.
Any projectile assembly stick in the gun bore (see 3.4.3)	Critical	18002
Burning time incorrect (see 3.4.2)	Major	18003
The first emission of light shall be at an average altitude of 600 ± 100 ft	Major	18004
Less than 5 stars	Major	18005
Altitude less than 350 ft.	Major	18006
Item fails to function	Major	18007

4.3.3.10.1 Hot temperature.-After completion of test specified in 4.3.3.9 and beginning with the first lot produced and continuing until three (3) acceptable lots (lots not accepted by disposition) have complied with the acceptance criteria specified in Table III, fifty (50) of the samples from each lot shall be subjected to this test.

4.3.3.10.2 Ambient temperature.-After completion of test specified in 4.3.3.9 and beginning with the first lot produced and continuing until three (3) acceptable lots (lots not accepted by disposition)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

have complied with the acceptance criteria specified in Table III, two-hundred (200) of the samples from each lot shall be subjected to this test.

4.3.3.10.3 Cold temperature.-After completion of test specified in 4.3.3.9 and beginning with the first lot produced and continuing until three (3) acceptable lots (lots not accepted by disposition) have complied with the acceptance criteria specified in Table III, fifty (50) of the samples from each lot shall be subjected to this test.

4.3.3.10.4 Rejection.-The lot shall be rejected if:

a. Any critical defects occurs in any phase (see Table III).
b. Average altitude of the total sample fails the applicable requirement (see Table III).
c. A total of eight (8) or more in the hot phase fail any of the following:
(1) Less than 5 stars (See Table III).
(2) Item fails to function (see Table III).
Burning time should be reported for informational purposes.

d. A total of eleven (11) or more in the ambient phase fail any of the following:
(1) Burning time incorrect (see 3.4.2).
(2) Less than 5 stars (See Table III).
(3) Item fails to function (see Table III).

e. A total of six (6) or more in the cold phase fail any of the following:
(1) Less than 5 stars (See Table III).
(2) Item fails to function (see Table III).
Burning time should be reported for informational purposes.

f. A total of fifteen (15) or more of the combined sample fail any of the following:
(1) Burning time incorrect (See 3.4.2) (Ambient Only)
(2) Less than 5 stars (See Table III).
(3) Item fails to function (See Table III).

g. Two (2) or more of the total samples have an altitude less than 350 ft (See Table III).

4.3.3.11 Transportation vibration (see para. 3.3), Regular Production, Major defect, Code No. (19001).-The cartridge shall be observed and examined visually without disassembly for any evidence of failure to comply with the requirements as classified in Table II when tested as specified in 4.4.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.3.3.11.1 After three (3) acceptable lots have complied with 4.3.3.8.1 and 4.3.3.10, one hundred and eight-nine (189) of the samples subjected to test specified in 4.3.3.7 shall be selected from each lot, packed in their regular shipping containers and subjected to this test. The lot shall be rejected if any defect as classified in Table II occurs.

4.3.3.12 Air pressure (see dwg. 9207987), Major defect, Regular Production, Code No. (20001).-After completion of test specified in 4.3.3.11.1, the one hundred and eighty-nine (189) samples shall be removed from their shipping containers and subjected to this test. If eight (8) or more samples fail to comply with the requirement specified on the applicable drawing, the lot shall be rejected. The test shall be performed as specified in 4.4.6 using equipment in accordance with 4.3.4. Cartridges which fail this test shall be discarded and replaced with units which have been subjected to test specified in 4.3.3.11 prior to subsequent testing.

4.3.3.13 Functioning (see 3.4), Major defect, Regular Production, Code No. (21001).-The cartridge shall be observed for any evidence of failure to comply with the requirements as classified in Table III when tested as specified in 4.4.8.

4.3.3.13.1 Hot temperature.-After three (3) acceptable lots have complied with 4.3.3.10, thirty-two (32) of the samples subjected to test specified in 4.3.3.12 shall be subjected to this test.

4.3.3.13.2 Ambient temperature.-After three (3) acceptable lots have been complied with 4.3.3.10, one-hundred and twenty-five (125) of the samples subjected to test specified in 4.3.3.12 shall be subjected to this test.

4.3.3.13.3 Cold temperature.-After three (3) acceptable lots have complied with 4.3.3.10, thirty-two (32) of the samples subjected to test specified in 4.3.3.12 shall be subjected to this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.3.3.13.4 Rejection.-The lot shall be rejected if:

a. Any critical defect occurs in any phase (see Table III).
b. Average altitude of the total sample fails the applicable requirement (see Table III).
c. A total of four (4) or more in the hot phase fail any of the following:
(1) Less than 5 stars (see Table III).
(2) Item fails to function (see Table III).
Burning time should be reported for informational purposes

d. A total of eight (8) or more in the ambient phase fail any of the following:
(1) Burning time incorrect (see 3.4.2).
(2) Less than 5 stars (See Table III).
(3) Item fails to function (see Table III).

e. A total of four (4) or more in the cold phase fail any of the following:
(1) Less than 5 stars (See Table III).
(2) Item fails to function (see Table III).
Burning time should be reported for informational purposes.

f. A total of eleven (11) or more of the combined sample fail any of the following:
(1) Burning time incorrect (See 3.4.2) (Ambient Only)
(2) Less than 5 stars (See Table III).
(3) Item fails to function (See Table III).

g. Two (2) or more of the total samples have an altitude less than 350 ft (See Table III).

4.3.3.14 Suitability test plan (Informational test only), Code No. 22001).-Beginning with the first lot produced by each producer and continuing until that producer has submitted three (3) acceptable lots (lots not accepted by disposition) that are accepted in accordance with 4.3.3.10.1, 4.3.3.10.2 and 4.3.3.10.3, an extra sample of eighty-eight (88) rounds shall be selected from each lot and pre-conditioned and tested as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

a. The eighty-eight (88) rounds shall be packaged in their regular shipping containers and subjected to transportation vibration environment test in accordance with MIL-STD-331, Test No. 104.

b. After transportation vibration, the rounds shall be unpacked and subjected to the JAN temperature and humidity cycle (14 days) specified in MIL-STD-331, Test No. 105.

c. After temperature and humidity cycle, the rounds shall be temperature conditioned and fired as follows:

30 rounds +165 degrees F. ± 5 degrees F.
28 rounds ambient (between +40 and +110 degrees F.)
30 rounds -65 degrees F. ± 5 degrees F.

d. The rounds shall be fired in accordance with 4.4.8 and with TECOM Material Test Procedure, TECP 700-700 Volume 4. Test results, failure analysis reports, and other information as requested shall be forwarded to Picatinny Arsenal, ATTN: SMUPA-ND3 for evaluation.

4.3.3.15 Air pressure test of packaged, sealed metal box (see dwg. 9209204), Major defect, Code No. (23001).-One (1) packed, sealed metal box shall be selected from each twenty (20) boxes packed. If the metal box fails to comply with the requirement specified on the applicable drawing, the quantity represented by the sample shall be rejected. The test shall be performed as specified in 4.4.9 using equipment in accordance with 4.3.4.

4.3.4 Inspection equipment.-Equipment Tabulation (ET) number 9207987 and Equipment Lists (EL's) referenced thereon identify the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of this specification may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey, and whenever inspection equipment drawings are needed. Supply and maintenance of the equipment listed on the EL's shall be in accordance with MIL-I-45607.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.4 Test methods and procedures.-

4.4.1 Moisture content.-

4.4.1.1 Delay composition.-The moisture content of the delay composition at the time and place of loading shall be determined in accordance with Method 101.5 of MIL-STD-650.

4.4.1.2 Powder pellet.-The moisture content of the powder pellet at the time and place of loading shall be determined in accordance with para. 4.4.3 of MIL-P-223.

4.4.1.3 Disc, retaining, and spacer, felt.-An accurately weighed portion of at least 10 grams of the material weighed to the nearest milligram shall be transferred to a tared weighing dish and placed in an oven and heated at a temperature of 100 degrees Centigrade (°C) plus or minus 2 degrees C for 2 hours. The dish and contents shall be removed from the oven and placed in a desiccator, cooled and weighed. The difference in weight shall be calculated to percentage of moisture in the sample.

4.4.1.4 Illuminant composition.-The Karl Fischer method as stated in Standard MIL-STD-1234, Method 101.2 up to paragraph 5.3 shall be used. A fifty-gram sample plus or minus 0.1 gram shall be added to a 500 milliliter (ml) volumetric flash containing approximately 300 to 400 ml. methanol and 25 grams of dry sodium nitrate. The flask shall be stoppered and the contents swirled cautiously for several minutes until the material is thoroughly dispersed. The sample shall be allowed to remain in contact with the methanol for approximately two hours. Then the 500 ml. volumetric flask shall be filled up to the 500 ml. mark with methanol and swirled again. A blank without the sample shall be put through the same procedure. After the sample has settled, a 50 ml. aliquot of the clear supernatant liquid shall be withdrawn and immediately transferred to the standard titration vessel containing approximately 100 ml. of methanol which has just been titrated to the preliminary end point as described in Standard MIL-STD-1234, Method 101.2, paragraph 5.1. The final end point shall be reached in 3.5 minutes in the manner described in Standard MIL-STD-1234, Method 101.2, paragraph 5.4. A 50 ml. aliquot of the blank shall be titrated in the same manner. The water content shall be calculated as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

Percent water equals (VR-S) - (V'R-S')
Multiply the result by 100F and divide by W

where:

F = grams of water per ml. of standard water in methanol solution
V = ml. of Karl Fischer reagent added to the sample
V' = ml. of Karl Fischer reagent added to the blank
R = ml. of standard water in methanol solution per ml. of Karl Fischer reagent
S = ml. of standard water in methanol solution for titration of sample
S' = ml. of standard water in methanol solution with back titration of blank
W = weight of sample in grams

4.4.1.5 Igniter composition.-The moisture content of the igniter composition at the time and place of loading shall be determined in accordance with 4.6.4 of MIL-P-22264.

4.4.2 Specific gravity of pellet powder.-This test shall be performed as specified in MIL-STD-650, Method 203.1. This test is a destructive test. Samples so tested shall not be returned to the lot.

4.4.3 Candle power of pellet assembly.-This test shall be conducted in accordance with the procedure shown on the Equipment List.

4.4.4 Security of end plug assembly on body assembly.-The body assembly shall be placed in the fixture shown on the Equipment List and the force specified on dwg. 9207992 shall be applied. Assembly shall be pulled until separation occurs and data recorded. This test is a destructive test. Parts so tested shall not be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.4.5 Security of projectile assembly.-The cartridge shall be placed in the fixture shown on the Equipment List and the axial force specified on dwg. 9207992 or 9207987, as applicable, shall be applied. Assembly shall be pulled until total separation occurs and data shall be recorded. This test is a destructive test. Parts so tested shall not be returned to the lot.

4.4.6 Air pressure.-The cartridge shall be placed in the fixture shown on the Equipment List and a measured quantity of air shall be applied to produce the required air pressure. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.4.7 Transportation vibration.-The cartridges shall be packaged and packed in accordance with dwgs. 9209204 and 9209205 and tested in accordance with Test No. 104 of MIL-STD-331, except that each box shall be vibrated at the specified amplitudes for four (4) hours in each of three (3) different positions (i.e., box positioned so that the cartridges are vertical with end plug down, box positioned so that the cartridges are horizontal, and box positioned so that the cartridges are vertical with end plug up). After the test, the box packing and the cartridges shall be examined so determine compliance with the requirements. This test is a destructive test. Parts so tested shall not be returned to the lot.

4.4.8 Functioning.-The following tests shall be performed at a Government-owned proving ground:

4.4.8.1 Hot temperature (160 degrees F. plus or minus 5 degrees F.).-The cartridges shall be packed in their regular shipping containers and conditioned for a minimum of 16 hours at a temperature of 160 degrees F. plus or minus 5 degrees F. The cartridges shall be taken from the conditioning chamber, removed from the packing container, and fired from an approved launcher placed on an approved mount at 90 degrees quadrant elevation before the temperature of the cartridge changes. Observation shall be made for proper functioning and the requirements of paragraph 3.4.4.

4.4.8.2 Ambient temperature (70 degrees F. plus or minus 5 degrees F.).-The cartridges shall be packed in their regular shipping containers and conditioned for a minimum of 16 hours at a temperature of 70 degrees F. plus or minus 5 degrees F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

The cartridges shall be taken from the conditioning chamber, removed from the packing container, and fired from an approved launcher placed on an approved mount at 90 degrees quadrant elevation before the temperature of the cartridge changes. Observation shall be made for proper functioning and the requirements of paragraphs 3.4.5.

4.4.8.3 Cold temperature (-65 degrees F. plus or minus 5 degrees F.).-The cartridges shall be packed in their regular shipping containers and conditioned for a minimum of 16 hours at a temperature of -65 degrees F. plug or minus 5 degrees F. The cartridges shall be taken from the conditioning chamber, removed from the packing container, and fired from an approved launcher placed on an approved mount at 90 degrees quadrant elevation before the temperature of the cartridge changes. Observation shall be made for proper functioning and the requirements of paragraphs 3.4.6.

4.4.8.4 Test Validity.-If for any reason the proving ground considers that the test conditions have detrimentally affected the test results, the test shall be declared invalid and a new test shall be performed with additional samples.

4.4.9 Air pressure of packed, sealed metal box.-The metal box shall be placed in the fixture shown on the Equipment List and a measured quantity of air shall be applied to produce the required air pressure. Observation shall be made for leakage. This test is a non-destructive test. Boxes so tested may be returned to the lot.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.-

5.1.1 Level A.-The cartridges shall be preserved and packaged in accordance with dwg. 9209204.

5.2 Packing.-

5.2.1 Level A.-The cartridge preserved and packaged as specified in 5.1.1 shall be packed in accordance with dwg. 9209204.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

5.3 Marking.-Marking shall be in accordance with dwgs. 9209204, and 9209205, MIL-STD-1169 and Code of Federal Regulations, Title 49, Parts 171-179.

5.4 Shipping.-When shipments from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

c. Provisions for submission of First Article Samples.

6.2 Inspection code numbers.-The five-digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are also used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. These code numbers shall be listed on drawings of equipment designs submitted by the contractor (see 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Equipment Lists.-Equipment lists indicate the availability of inspection equipment designs by showing in the "Part Number" column of the list of inspection equipment (Form SMUPA 1010) the number of drawings for Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the "Part Number" column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

6.3.2 Equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications: mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an equipment list references mandatory Army designs, the contractor shall comply with and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor-prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finishes, notes, and operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to Specification MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high-contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five-digit code number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND3. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract. Submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished, normally, within one month after receipt.

6.4 Submission of test data.-In addition to the normal distribution of records, when the cartridge is procured by the U.S. Army Munitions Command, one (1) copy of all ballistic data shall be forwarded to: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND3.

6.5 Submission of results of contractor-conducted examinations and tests.-Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND3.

6.6 The cartridge will be considered safe to transport providing no evidence exists of loose powder or composition in the box.

6.7 The cartridge will be considered free of damage that will affect the intended function provided the top seal has not been broken by movement or displacement of the top, or the case side has not been distorted sufficiently to prevent ejection of the illuminant assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

6.8 Supersession data.-This specification includes the requirements of, and supersedes, Purchase Specification AEI-379, dated 27 March 1967.

6.9 Proving ground test summary:

TEST	SAMPLE SIZE	REQUIREMENTS
First Article		
a. Hot	80	See 3.4.4 & 4.2.4
b. Ambient	315	See 3.4.5 & 4.2.4
c. Cold	80	See 3.4.6 & 4.2.4
First 3 Lots		
a. Hot	50	See 3.4.4 & 4.3.3.10.4
b. Ambient	200	See 3.4.5 & 4.3.3.10.4
c. Cold	50	See 3.4.6 & 4.3.3.10.4
Regular Production		
a. Hot	32	See 3.4.4 & 4.3.3.13.4
b. Ambient	125	See 3.4.5 & 4.3.3.13.4
c. Cold	32	See 3.4.6 & 4.3.3.13.4

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1310-A-163

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
PICATINNY ARSENAL
DOVER, NEW JERSEY 07801

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

COMMANDING OFFICER
United States Army
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.