MILITARY SPECIFICATION

CARTRIDGE, 40MM, WHITE STAR, CLUSTER, M585A1

METAL PARTS FOR

AND

LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the metal parts and loading, assembling and packing for one type of cartridge designated as Cartridge, 40MM, White Star, Cluster, M585A1.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-A-2550	-	Ammunition and Special Weapons, General Specification for
MIL-C-5541	-	Chemical Films and Chemical Film Materials for Aluminum and Aluminum Alloys
MIL-P-22264	-	Powders, Ignition, Gasless

FSC: 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

MIL-I-45607 - Inspection Equipment, Supply and Maintenance of

STANDARDS

FEDERAL

FED-STD-151 - Metals; Test Methods

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

MIL-STD-109 - Quality Assurance Terms and Definitions

MIL-STD-331 - Fuze and Fuze Components, Environmental and Performance Tests for

MIL-STD-650 - Explosive: Sampling, Inspection and Testing

MIL-STD-1168 - Lot Numbering of Ammunition

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

9243880 - Cartridge, 40MM, White Star, Cluster, M585A1

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

PUBLICATIONS
ARMY

ET-9243880 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

2.2 Other publications.-The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

CODE OF FEDERAL REGULATIONS

Title 49 - Transportation, Parts 0-190

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders should specify, "49 CFR 0-190 (latest revision)".)

3. REQUIREMENTS

3.1 Material.-Materials shall be in accordance with the applicable drawings and specifications.

3.2 Cartridge.-The cartridge shall comply with all requirements specified on Drawing (Dwg.) 9243880, all associated drawings, and with all requirements specified in applicable specifications.

3.3 Transportation - vibration.-The cartridge shall comply with the following requirements when tested as specified in 4.4.5.

3.3.1 The cartridge shall be safe to transport following this test (See 6.6).

3.3.2 There shall be no evidence of external damage to the cartridge that will affect the intended function (see 6.7).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

3.4 Functioning.-The cartridge shall comply with the following requirements when tested as specified in 4.4.6:

3.4.1 Altitude.-The projectile shall function at an average altitude of 600 ± 100. feet.

3.4.2 Burning time of each White Star pellet.-All White Star pellets shall burn a minimum (min.) of six (6) seconds.

3.4.3 Firing.-No projectile shall stick in the gun bore.

3.4.4 Hot temperature (160 degrees F. plus or minus 5 degrees F.).-The cartridge shall comply with the requirements of 3.4.1, 3.4.2, 3.4.3.

3.4.5 Ambient temperature (70 degrees F. plus or minus 5 degrees F.).-The cartridge shall comply with the requirements of 3.4.1, 3.4.2, 3.4.3.

3.4.6 Cold temperature (-65 degrees F. plus or minus 5 degrees F.).-The cartridge shall comply with the requirements of 3.4.1, 3.4.2, 3.4.3.

3.5 Workmanship.-All parts and assemblies shall be fabricated, loaded and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required marking and stamping shall be neat and sharply defined.

3.6 Submission of results of contractor-conducted examinations and tests.-The contractor shall forward copies of the results of any of his examinations or tests to the designated address as required by the contract. (see 6.5).

3.7 First article testing.-This specification makes provisions for first article testing. Submission of first article quantity by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First article inspection.-Prior to initiation of regular production, the contractor shall submit a first article quantity as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.2.2 (See 6.1). The first article shall consist of the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

a. Twenty-five (25) body assemblies, five (5) painted (See Dwg. 9243900).
b. Twenty-five (25) ogives (See Dwg. 9243895).
c. Twenty-five (25) cups (See Dwg. 9243908).
d. Twenty-five (25) carrier delays (See Dwg. 9243886).
e. Three (3) test panels of body for salt spray.
f. Three (3) test panels of carrier delay for salt spray.
g. Twenty-five (25) white star pellet assemblies (See Dwg. 9243901).
h. Twenty-five (25) cartridge assemblies (See Dwg. 9243880).
i. Four-hundred and seventy-five (475) cartridges (See Dwg. 9243880) to a Government proving ground for functioning tests.

All parts and completed assemblies submitted shall have been produced by the contractor (or furnished by a supplier) using the same production processes, procedures and equipment as will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same sources of supply as will be used in regular production. The sample shall be accompanied by certificates of conformance. A first article quantity, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, material used, drawing, specification or source of supply as to significantly affect product uniformity as determined by the Government. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer.

4.2.2 Inspections to be performed.-Assemblies and components will be subjected by the Government to any or all of the examinations or tests specified in this specification and any or all requirements of the applicable drawings.

4.2.2.1 Quantities for first article inspection.-After classification of defects and other inspection have been performed as specified in 4.2.2, the following quantities shall be subjected to the indicated tests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

4.2.2.1.1 Candle power of white star pellet assembly (See Dwg. 9243901).-The twenty-five (25) white star pellet assemblies shall be subjected to this test.

4.2.2.1.2 Security of projectile assembly (See Dwg. 9243880).-The twenty-five (25) cartridges shall be subjected to this test.

4.2.2.1.3 Salt spray.-The three (3) test panels of body and carrier delay shall be subjected to this test.

4.2.3 Rejection.-If any assembly or component fails to comply with any of the applicable requirements, the first article quantity shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity or portion thereof. Until a first article quantity is accepted, the contractor is in no way authorized by the Government to resume regular production unless otherwise directed by the Contracting Officer.

4.2.4 Remaining first article inspection samples.-Unless otherwise specified by the Contracting Officer, loaded cartridges shall not be submitted for proving ground tests until the inert components and sub-assemblies submitted in accordance with 4.2 have been accepted.

4.2.4.1 Prior to submission.-Prior to submission of the four hundred and seventy-five (475) cartridges to a Government proving ground for functioning tests, the 475 cartridges shall be inspected at the contractor's plant for the following tests:

4.2.4.1.1 Transportation-vibration (see 3.3).-The 475 cartridges packed in their regular shipping containers shall be subjected to this test.

4.2.4.1.2 Air pressure (see dwg. 9243881).-After completion of test specified in 4.2.4.1.1, the 475 cartridges shall be removed from their regular shipping containers and subjected to this test.

4.2.5 Rejection.-If any assembly fails to comply with any of the applicable requirement, the first article quantity shall be rejected. The Government reserves the right to terminate its

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

inspection upon any failure to an assembly or component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity or portion thereof. Until a first article quantity is accepted, the contractor is in no way authorized by the Government to resume regular production unless otherwise directed by the Contracting Officer.

4.2.6 Proving ground tests.-The cartridges shall be subjected by the Government to the following tests:

a. Functioning at hot temperature (see 3.4.5).-Eighty (80) cartridges shall be subjected to this test (see 4.4.6).
b. Functioning at ambient temperature (see 3.4.6).-Three-hundred and fifteen (315) cartridges shall be subjected to this test (see 4.4.6).
c. Functioning at cold temperature (see 3.4.7).-Eighty (80) cartridges shall be subjected to this test (see 4.4.6).

4.2.6.1 Rejection.-The first article sample shall be rejected if:

a. Any critical defect occurs in any phase (see Table III).
b. Average altitude of the total sample fails the applicable requirement (see Table III).
c. A total of eight (8) or more in the hot phase fail any of the following:
(1) Less than five (5) stars (See Table III).
(2) Item fails to function (see Table III).
Burning time should be recorded for informational purposes.
d. A total of twenty-two (22) or more in the ambient phase fail any of the following:
(1) Burning time incorrect (see 3.4.2).
(2) Less than five (5) stars (See Table III).
(3) Item fails to function (see Table III).
e. A total of eight (8) or more in the cold phase fail any of the following:
(1) Less than five (5) stars (See Table III).
(2) Item fails to function (see Table III).
Burning time should be recorded for informational purposes.
f. A total of twenty-two (22) or more of the combined sample fail any of the following:
(1) Burning time incorrect (See 3.4.2) (Ambient only).
(2) Less than five (5) stars (See Table III).
(3) Item fails to function (See Table III).
g. Two (2) or more of the total sample are below an altitude of 350 ft (see Table III).

In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new first article quantity. Until the first article quantity is accepted, the contractor is not authorized by the Government to proceed with regular production unless otherwise directed by the Contracting Officer.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the currentversion before use.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot shall contain:

a. Projectile metal parts from one interfix lot number from one manufacturer.
b. Delay composition from not more than one lot number.
c. Igniter composition from not more than one lot number.
d. Illuminant composition produced by one manufacturer under one continuous set of operating conditions and which consist of one or more batches that have been subjected to the same unit chemical or physical mixing process intended to make the final product homogeneous.
e. Cartridge case loaded assemblies from one interfix lot number from one manufacturer.
f. Ignition pellet from not more than one lot number.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (See 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed,

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the currentversion before use.

the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Body, prior to painting (see dwg. 9243900).-

Categories	Defects	Method of Inspection	Code No (See 6.2)
Critical:	None defined		
Major	AQL 1.00 Percent		
101.	Largest outside diameter	Gage	01001
102.	Concentricity of largest outside diameter with second largest outside diameter	Gage	01002
103.	Second largest outside diameter	Gage	01003
104.	Concentricity of second largest outside diameter with smallest inside diameter	Gage	01004
105.	Concentricity of largest inside diameter with smallest inside diameter	Gage	01005
106.	Pitch diameter of thread	Gage	01006
107.	Minor diameter of thread, maximum (max)	Gage	01007
108.	Perpendicularity of open end with smallest inside diameter	Gage	01008
109.	Metal defective (see 3.5 and 6.9)	Visual	01009
Minor	AQL 2.50 Percent		
201.	Smallest outside diameter	Gage	01010
202.	Groove diameter	Gage	01011
203.	Width of rotating bands	Gage	01012
204.	Total length	Gage	01013

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

205.	Width of flange	Gage	01014
206.	Distance to rotating band	Gage	01015
207.	Evidence of poor workmanship (see 3.5)	Visual	01016

4.3.2.2 Body after painting (See Dwg. 9243900).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 0.40 Percent		
101.	Second largest outside diameter	Gage	02001
Minor	AQL 0.65 Percent		
201.	Color incorrect	Visual	02002

4.3.2.3 Ogive (See Dwg. 9243895).-

Categories	Defects	Method of Inspection	Code No.
Critical			
1.	Incorrect letter	Visual	03001
2.	Flutes missing	Visual	03002
Major	AQL 0.65 Percent		
101.	Large outside diameter	Gage	03003
102.	Concentricity of large outside diameter with second largest outside diameter	Gage	03004
103.	Second largest outside diameter	Gage	03005
104.	Inside diameter	Gage	03006
Minor	AQL 2.50 Percent		
201.	Total length	Gage	03007
202.	Width of slots	Gage	03008
203.	Diameter of groove	Gage	03009
204.	Width of groove	Gage	03010
205.	Evidence of poor workmanship (see 3.5)	Visual	03011

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

4.3.2.4 Cup (See Dwg. 9243908).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 0.40 Percent		
101.	Outside diameter	Gage	04001
102.	Thickness	Gage	04002
Minor	AQL 1.50 Percent		
201.	Height	Gage	04003
202.	Hole diameter	Gage	04004
203.	Evidence of poor workmanship (see 3.5)	Visual	04005

4.3.2.5 Carrier delay (See Dwg. 9243886).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 1.00 Percent		
101.	Pitch diameter of thread	Gage	05001
102.	Major diameter of thread	Gage	05002
103.	Small inside diameter	Gage	05003
104.	Large inside diameter	Gage	05004
105.	Concentricity of small inside diameter with large inside diameter	Gage	05005
Minor	AQL 1.50 Percent		
201.	Length to flange	Gage	05006
202.	Concentricity of body diameter with large inside diameter	Gage	05007
203.	Diameter of thread undercut	Gage	05008
204.	Evidence of poor workmanship (see 3.5)	Visual	05009

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

4.3.2.6 White Star Pellet Assembly (See Dwg. 9243901).-

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major	AQL 0.40 Percent		
101.	Ignition pellet missing	Visual	06001
102.	Outside diameter	Gage	06002
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.5)	Visual	06003

4.3.2.7 Projectile assembly, prior to assembling ogive (see dwg. 9243884).-

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major	AQL 0.40 Percent		
101.	Spacer missing	Visual	07001
102.	O-ring missing	Visual	07002
Minor: None defined			

4.3.2.8 Projectile assembly (See Dwg. 9243884).-

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			
Major	AQL 0.40 Percent		
101.	Gap present between delay assembly and body	Visual	08001
102.	Color incorrect	Visual	08002
Minor	AQL 0.65 Percent		
201.	Evidence of poor workmanship (See 3.5)	Visual	08003

4.3.2.9 Cartridge (See Dwg. 9243880).-

Categories	Defects	Method of Inspection	Code No.
Critical			
1.	Chamber gage failure	Gage	09001

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

2.	Incorrect ogive	Visual	09002
3.	Marking incorrect	Visual	09003
Major	AQL 0.40 Percent		
101.	Marking unidentifiable	Visual	09004
Minor	AQL 0.65 Percent		
201.	Total length	Gage	09005
202.	Evidence of poor workmanship (See 3.5)	Visual	09006

4.3.2.10 Unsealed metal box (see dwg. 9209204).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major	AQL 0.65 Percent		
101.	Incorrect number of cartridges	Visual	10001
102.	Desiccant bags missing	Visual	10002
103.	Rubber gasket damaged or improperly assembled	Visual	10003
Minor	AQL 1.00 Percent		
201.	Fillers missing	Visual	10004
202.	Tube missing	Visual	10005

4.3.2.11 Sealed metal box (see dwg. 9209204).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		
Minor:	AQL 1.00 Percent		
201.	Marking misleading of unidentifiable	Visual	11001
202.	Contents loose	Manual	11002

4.3.2.12 Sealed wooden packing box (see Dwg. 9209205).-

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	None defined		

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

Minor:	AQL 1.50 Percent		
201.	Marking misleading or unidentifiable	Visual	12001
202.	Contents loose	Manual	12002
203.	ICC nomenclature missing	Visual	12003

4.3.3 Testing.-

4.3.3.1 Dimensional control of molded parts.-In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, and after a curing time for the parts has been approved (See Note 1), a sample of three (3) parts (as molded) from each cavity may be dimensionally inspected to qualify a new or reworked cavity for use in production or as a control of each cavity during production.

The inspection of the parts shall be performed only when the curing time for the parts has been reached. The inspection for control of each cavity during production shall be performed on the above quantities from each cavity after production of each 5000 parts or at the end of each shift, providing the number of parts produced during that shift is less than 5000 parts. Of the three (3) samples, one (1) sample shall be the last part produced. Parts that fail to comply with dimensional requirements after dimensional stability has been attained shall be classed defective.

If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for corrective action.

All cavities formerly removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test as above. The contractor may request a change of inspection frequency providing he presents objective evidence to substantiate the request to the Contracting Officer.

(NOTE 1) - In establishing a curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g. every 30, 60, etc. mins.) until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determining the curing time shall be sent to Picatinny Arsenal, SMUPA-ND3. If any new change in material, cycle time, a reworked cavity, or new cavity is used, a new curing time shall be established and approved.

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:02Z
Check the source to verify that this is the current version before use.

4.3.3.2 Moisture content (See Table I), Major defect.-

TABLE I

Material	Code No.
Delay Composition (See dwg. 9243885)	13001
Igniter (See Dwg. 9243885)	13002
Illuminant composition (see dwg. 9243901)	13003
Ignition pellet (see dwg. 9243901)	13004

The contractor shall provide adequate controls to insure compliance with the requirements and shall test for verification at least one sample of each material from each eight hour' production of cartridges. Composite samples shall not be used. If the moisture content of a sample exceeds the requirement, and loading has not begun, that quantity of material represented by the sample shall be rejected. If assemblies have been loaded with material containing excessive moisture, the remaining material that is represented by the sample together with all cartridges loaded with the non-conforming material shall be rejected. The tests shall be performed as specified in 4.4.1 using equipment in accordance with 4.3.4.

4.3.3.3 Candle power of White Star pellet assembly (see dwg. 9243901), Major defect, Code No. 14001.-Beginning with the first lot produced and continuing until three (3) acceptable lots (lots not accepted by disposition) have been accepted, eighty (80) assemblies shall be selected from each lot for this test. If three (3) or more assemblies fail to comply with the requirement specified on the applicable drawing, the lot shall be rejected. The test shall be performed as specified in 4.4.2 using equipment in accordance with 4.3.4.

4.3.3.4 Candle power of White Star pellet assembly (see dwg. 9243901), Major defect, Regular Production, Code No. 14002.- After three (3) acceptable lots have met the criteria of 4.3.3.3, the Government inspector shall select thirty-two (32) assemblies from each lot for this test. If two (2) or more assemblies fail to comply with the requirement specified on the applicable drawing, the lot shall be rejected. At the start of production, or when there has been a lapse in 90 days, or when a major design change occurs as determined by the Government inspector, the criteria of 4.3.3.3 shall apply. The test shall be performed as specified in 4.4.2 using equipment in accordance with 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

4.3.3.5 Security of projectile assembly (see dwg. 9243880) Major defect, Code No. (15001).-The sampling plan for this test shall be in accordance with MIL-STD-105, Code Letter H, single plan, with an AQL of 2.50 percent. This test shall be performed as specified in 4.4.3 using equipment in accordance with 4.3.4.

4.3.3.6 Air pressure (see dwg. 9243880), Major defect, Code No. (16001).-This test shall be conducted 100 percent. Any cartridge which fails to comply with the requirement specified on the applicable drawing shall be classified defective and removed from the lot. The test shall be performed as specified in 4.4.4 using equipment in accordance with 4.3.4.

4.3.3.7 Transportation vibration (see 3.3), Major defect, Code No. (17001).-The cartridges shall be observed and examined visually without disassembly for any evidence of failure to comply with the requirements as classified in Table II when tested as specified in 4.4.5.

TABLE II

Defect	Classification	Code No.
Cartridge not safe to transport following test (see 3.3.1)	Critical	17002
Cartridge damaged after test (see 3.3.2)	Major	17003

4.3.3.7.1 After completion of test specified in 4.3.3.6 and beginning with the first lot produced and continuing until three (3) acceptable lots (lots not accepted by disposition) have complied with the acceptance criteria specified in Table II, three hundred (300) cartridges shall be selected from each lot, packed in their regular shipping containers and subjected to this test. The lot shall be rejected if any defect as classified in Table II occurs.

4.3.3.8 Air pressure (see dwg. 9243880), Major defect, Code No. (18001).-After completion of test specified in 4.3.3.7.1, the three hundred (300) samples from each lot shall be subjected to this test. If nine (9) or more cartridges fail to comply with the requirements specified on the applicable drawing, the lot shall be rejected. The test shall be performed as specified in 4.4.4 using equipment in accordance with 4.3.4. Cartridges

Source: https://assist.dla.mil -- Downloaded: 202640-26T04:02Z
Check the source to verify that this is the currentversion before use.

which fail this test shall be discarded and replaced with units which have been subjected to test specified in 4.3.3.7 prior to subsequent testing.

4.3.3.9 Functioning (see 3.4), Major defect, Code No. (19001).- The cartridges shall be observed for any evidence of failure to comply with the requirements as classified in Table III when tested as specified in 4.4.6.

TABLE III

Defect	Classification	Code No.
Any projectile assembly sticks in the gun bore (see 3.4.3)	Critical	19002
Burning time incorrect (see 3.4.2)	Major	19003
The first emission of light shall be at an average altitude of 600 + 100 ft.	Major	19004
Less than 5 stars	Major	19005
Altitude less than 350 ft.	Major	19006
Item fails to function	Major	19007

4.3.3.9.1 Hot temperature.-After completion of test specified in 4.3.3.8 and beginning with the first lot produced and continuing until three (3) acceptable lots (lots not accepted by disposition) have complied with the acceptance criteria specified in Table III, fifty (50) of the samples from each lot shall be subjected to this test.

4.3.3.9.2 Ambient temperature.-After completion of test specified in 4.3.3.8 and beginning with the first lot produced and continuing until three (3) acceptable lots (lots not accepted by disposition) have complied with the acceptance criteria specified in Table III, two hundred (200) of the samples from each lot shall be subjected to this test.

4.3.3.9.3 Cold temperature.-After completion of test specified in 4.3.3.8 and beginning with the first lot produced and continuing until three (3) acceptable lots (lots not accepted by disposition) have complied with the acceptance criteria specified in Table III, fifty (50) of the samples from each lot shall be subjected to this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

4.3.3.9.4 Rejection.-The lot shall be rejected if:

a. Any critical defects occurs in any phase (see Table III).
b. Average altitude of the total sample fails the applicable requirement (see Table III).
c. A total of eight (8) or more in the hot phase fail any of the following:
(1) Less than 5 stars (See Table III).
(2) Item fails to function (see Table III).
Burning time should be reported for informational purposes.
d. A total of eleven (11) or more in the ambient phase fail any of the following:
(1) Burning time incorrect (see 3.4.2).
(2) Less than 5 stars (See Table III).
(3) Item fails to function (see Table III).
e. A total of six (6) or more in the cold phase fail any of the following:
(1) Less than 5 stars (See Table III)
(2) Item fails to function (see Table III).
Burning time should be reported for informational purposes.
f. A total of fifteen (15) or more of the combined sample fail any of the following:
(1) Burning time incorrect (see 3.4.2) (Ambient Only)
(2) Less than 5 stars (See Table III).
(3) Item fails to function (See Table III).
g. Two (2) or more of the total samples have an altitude less than 350 ft (See Table III).

4.3.3.10 Transportation vibration (see para. 3.3), Regular Production, Major defect, Code No. (20001).-The cartridge shall be observed and examined visually without disassembly for any evidence of failure to comply with the requirements as classified in Table II when tested as specified in 4.4.5.

4.3.3.10.1 After three (3) acceptable lots have complied with 4.3.3.7.1, and 4.3.3.9 one hundred and eighty-nine (189) of the samples subjected to test specified in 4.3.3.6 shall be selected from each lot, packed in their regular shipping containers and subjected to this test. The lot shall be rejected if any defect as classified in Table II occurs.

4.3.3.11 Air pressure (see dwg. 9243880), Major defect, Regular Production, Code No. (21001).-After completion of test specified in 4.3.3.10.1, the one hundred and eighty-nine (189) samples shall be removed from their shipping containers and subjected to this test. If eight (8) or more samples fail to comply with the requirement

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

specified on the applicable drawing, the lot shall be rejected. The test shall be performed as specified in 4.4.4 using equipment in accordance with 4.3.4. Cartridges which fail this test shall be discarded and replaced with units which have been subjected to test specified in 4.3.3.10 prior to subsequent testing.

4.3.3.12 Functioning (see 3.4), Regular Production, Major defect, Code No. (22001).-The cartridges shall be observed for any evidence of failure to comply with the requirements as classified in Table III when tested as specified in 4.4.6.

4.3.3.12.1 Hot temperature.-After three (3) acceptable lots have complied with 4.3.3.9, thirty-two (32) of the samples subjected to test specified in 4.3.3.11 shall be subjected to this test.

4.3.3.12.2 Ambient temperature.-After three (3) acceptable lots have complied with 4.3.3.9, one hundred and twenty-five (125) of the samples subjected to test specified in 4.3.3.11 shall be subjected to this test.

4.3.3.12.3 Cold temperature.-After three (3) acceptable lots have complied with 4.3.3.9, thirty-two (32) of the samples subjected to test specified in 4.3.3.11 shall be subjected to this test.

4.3.3.12.4 Rejection.-The lot shall be rejected if:

a. Any critical defect occurs in any phase (see Table III).
b. Average altitude of the total sample fails the applicable requirement (see Table III).
c. A total of four (4) or more in the hot phase fail any of the following:
(1) Less than 5 stars (see Table III).
(2) Item fails to function (see Table III).
Burning time should be reported for informational purposes.
d. A total of eight (8) or more in the ambient phase fail any of the following:
(1) Burning time incorrect (see 3.4.2).
(2) Less than 5 stars (See Table III).
(3) Item fails to function (see Table III).
e. A total of four (4) or more in the cold phase fail any of the following:
(1) Less than 5 stars (See Table III).
(2) Item fails to function (see Table III).
Burning time should be recorded for informational purposes.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

f. A total of eleven (11) or more of the combined sample fail any of the following:

(1) Burning time incorrect (See 3.4.2) (Ambient Only)
(2) Less than 5 stars (See Table III).
(3) Item fails to function (See Table III).

g. Two (2) or more of the total samples have an altitude less than 350 ft. (See Table III).

4.3.3.13 Suitability test plan (Information test only), Code No. (23001).-Beginning with the first lot produced by each producer and continuing until that producer has submitted three (3) acceptable lots (lots not accepted by disposition) that are accepted in accordance with 4.3.3.9.1, 4.3.3.9.2 and 4.3.3.9.3, an extra sample of eighty-eight (88) rounds shall be selected from each lot and preconditioned and tested as follows:

a. The eighty-eight (88) rounds shall be packaged in their regular shipping containers and subjected to transportation vibration environmental in accordance with MIL-STD-331, Test No. 104.

b. After transportation vibration, the rounds shall be unpacked and subjected to the JAN temperature and humidity cycle (14 days) specified in MIL-STD-331, Test No. 105.

c. After temperature and humidity cycle, the rounds shall be temperature conditioned and fixed as follows:

30 rounds +165 degrees F. + 5 degrees F.
28 rounds ambient (between +40 and +110 degrees F.)
30 rounds -65 degrees F. ± 5 degrees F.

d. Fire the rounds in accordance with paragraph 4.4.6 and with TECOM Material Test Procedure, TECP 700-700 Volume 4. Test results, failure analysis reports, and other information as requested shall be forwarded to Picatinny Arsenal, ATTN: SMUPA-ND3 for evaluation.

4.3.3.14 Salt spray of body and carrier delay (See Dwg. 9243900 and 9243886), Major defect, Code No. 24001.-Sampling and rejection shall be in accordance with MIL-C-5541. The test shall be performed as specified in 4.4.7 using equipment in accordance with 4.3.4.

4.3.3.15 Air pressure test of packed, sealed metal box (see dwg. 9209204), Major defect, Code No. (25001).-One (1) packed, sealed metal box shall be selected from each twenty (20)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

boxes packed. If the metal box fails to comply with the requirement specified on the applicable drawing, the quantity represented by the sample shall be rejected. The test shall be performed as specified in 4.4.8 using equipment in accordance with 4.3.4.

4.3.4 Inspection equipment.-Equipment Tabulation (ET) number 9243880 and Equipment Lists (EL's) referenced thereon identify the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of this specification may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey, and whenever inspection equipment drawings are needed. Supply and maintenance of the equipment listed on the EL's shall be in accordance with MIL-I-45607.

4.4 Test methods and procedures.-

4.4.1 Moisture content.-

4.4.1.1 Delay composition.-The moisture content of the delay composition at the time and place of loading shall be determined in accordance with Method 101.5 of MIL-STD-650.

4.4.1.2 Ignition composition.-The moisture content of the ignition composition at the time and place of loading shall be determined by any method satisfactory to the Contracting Officer.

4.4.1.3 Illuminant composition.-The Karl Fischer method as stated in Standard MIL-STD-1234, Method 101.2 up to paragraph 5.3 shall be used. A fifty-gram sample plus or minus 0.1 gram shall be added to a 500 milliliter (ml) volumetric flash containing approximately 300 to 400 ml. methanol and 25 grams of dry sodium nitrate. The flask shall be stoppered and the contents swirled cautiously for several minutes until the material is thoroughly dispersed. The sample shall be allowed to remain in contact with the methanol for approximately two hours. Then the 500 ml. volumetric flask shall be filled up to the 500 ml. mark with methanol and swirled again. A blank without the sample shall be put through the same procedure. After the sample has settled, a 50 ml. aliquot of the clear supernatant liquid shall be withdrawn and immediately transferred to the standard

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

titration vessel containing approximately 100 ml. of methanol which has just been titrated to the preliminary end point as described in Standard MIL-STD-1234, Method 101.2, paragraph 5.1. The final end point shall be reached in 3.5 minutes in the manner described in Standard MIL-STD-1234, Method 101.2, paragraph 5.4. A 50 ml. aliquot of the blank shall be titrated in the same manner. The water content shall be calculated as follows:

Percent water equals (VR-S) - (V'R-S')
Multiply the result by 100 F and divide by W

where:

F = grams of water per ml. of standard water in methanol solution
V = ml. of Karl Fischer reagent added to the sample
V' = ml. of Karl Fischer reagent added to the blank
R = ml. of standard water in methanol solution per ml. of Karl Fischer reagent
S = ml. of standard water in methanol solution for titration of sample
S' = ml. of standard water in methanol solution with back titration of blank
W = weight of sample in grams

4.4.1.4 Igniter composition.-The moisture content of the igniter composition at the time and place of loading shall be determined in accordance with 4.6.6 of MIL-P-22264.

4.4.2 Candle power of white star pellet assembly.-This test shall be conducted in accordance with the procedure shown on the Equipment List.

4.4.3 Security of projectile assembly.-The cartridge shall be placed in the fixture shown on the Equipment List and the axial force specified on dwg. 9243880 shall be applied. Assembly shall be pulled until total separation occurs and data shall be recorded. This test is a destructive test. Parts so tested shall not be returned to the lot.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the currentversion before use.

4.4.4 Air pressure.-The cartridge shall be placed in the fixture shown on the Equipment List and a measured quantity of air shall be applied to produce the required air pressure. This test is a non-destructive test. Parts so tested may be returned to the lot.

4.4.5 Transportation vibration.-The cartridges shall be packaged and packed in accordance with dwgs. 9209204 and 9209205 and tested in accordance with Test No. 104 of MIL-STD-331, except that each box shall be vibrated at the specified amplitudes for four (4) hours in each of three (3) different positions (i.e., box positioned so that the cartridges are vertical with case end down, box positioned so that the cartridges are horizontal, and box positioned so that the cartridges are vertical with case end up. After the test, the box packing and the cartridges shall be examined to determine compliance with the requirements. This test is a destructive test. Parts so tested shall not be returned to the lot.

4.4.6 Functioning.-The following tests shall be performed at a Government-owned proving ground:

4.4.6.1 Hot temperature (160 degrees F. plus or minus 5 degrees F.).-The cartridges shall be packed in their regular shipping containers and conditioned for a minimum of 16 hours at a temperature of 160 degrees F. plus or minus 5 degrees F. The cartridge shall be taken from the conditioning chamber, removed from the packing container, and fired from an approved launcher placed on an approved mount at 90 degrees quadrant elevation before the temperature of the cartridge changes. Observation shall be made for proper functioning and the requirements of 3.4.4.

4.4.6.2 Ambient temperature (70 degrees F. plus or minus 5 degrees F.).-The cartridges shall be packed in their regular shipping containers and conditioned for a minimum of 16 hours at a temperature of 70 degrees F. plus or minus 5 degrees F. The cartridge shall be taken from the conditioning chamber, removed from the packing container, and fired from an approved launcher placed on an approved mount at 90 degrees quadrant elevation before the temperature of the cartridge changes. Observation shall be made for proper functioning and the requirements of 3.4.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

4.4.6.3 Cold temperature (-65 degrees F. plus or minus 5 degrees F.).-The cartridges shall be packed in their regular shipping containers and conditioned for a minimum of 16 hours at a temperature of -65 degrees F. plus or minus 5 degrees F. The cartridge shall be taken from the conditioning chamber, removed from the packing container, and fired from an approved launcher placed on an approved mount at 90 degrees quadrant elevation before the temperature of the cartridge changes. Observation shall be made for proper functioning and the requirements of 3.4.6.

4.4.7 Air pressure of packed, sealed metal box.-The metal box shall be placed in the fixture shown on the Equipment List and a measured quantity of air shall be applied to produce the required air pressure. Observation shall be made for leakage. This test is a non-destructive test. Boxes so tested may be returned to the lot.

4.4.8 Salt spray of body and carrier delay.-This test shall be conducted in accordance with FED-STD-151, Method 811.1. Specimens so tested shall not be returned to the lot. Salt solution shall be 5 percent.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.-

5.1.1 Level A.-The cartridges shall be preserved and packaged in accordance with dwg. 9209204.

5.2 Packing.-

5.2.1 Level A.-The cartridges, preserved and packaged as specified in 5.1.1, shall be packed in accordance with dwg. 9209204.

5.3 Marking.-Marking shall be in accordance with dwgs. 9209204, and 9209205, MIL-STD-1169 and Code of Federal Regulations, Title 49, Parts 0-190.

5.4 Shipping.-When shipments from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

c. Provisions for submission of First Article Samples.

6.2 Inspection code numbers.-The five-digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are also used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. These code numbers shall be listed on drawings of equipment designs submitted by the contractor (see 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

6.3.1 Equipment lists.-Equipment lists indicate the availability of inspection equipment designs by showing in the "Part Number" column of the list of inspection equipment (Form SMUPA 1010) the number of drawings for Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the "Part Number" column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications: mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an equipment list references mandatory Army designs, the contractor shall comply with and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor-prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finishes, notes, and operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to Specification MIL-D-1000, Category E, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high-contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five-digit code number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the currentversion before use.

of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal ATTN: SMUPA-ND3. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract. Submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished, normally, within one month after receipt.

6.4 Submission of test data.-In addition to the normal distribution of records, when the cartridges are procured by the U.S. Army Munitions Command, one (1) copy of all ballistic data shall be forwarded to: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND3.

6.5 Submission of results of contractor-conducted examinations and tests.-Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of examinations or tests to: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND3.

6.6 The cartridges will be considered safe to transport providing no evidence exists of loose powder or composition in the box.

6.7 The cartridges will be considered free of damage that will affect the intended function provided the top seal has not been broken by movement or displacement of the top, or the case side has not been distorted sufficiently to prevent ejection of the illuminant assembly.

6.8 Proving ground test.-Initial production testing shall be conducted in accordance with U.S. Army Test and Evaluation Command Initial Production Test Plan No. CART-40GL-VAR.

6.9 Metal defective.-Nick, crack, dent or sharp edge which might interfere with the proper assembly or end item performance of the item.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

6.10 Proving ground test summary:

TEST	SAMPLE SIZE	REQUIREMENTS
Functioning		
(1) First article		
a. Hot	80	See 3.4.4 & 4.2.4
b. Ambient	315	See 3.4.5 & 4.2.4
c. Cold	80	See 3.4.6 & 4.2.4
(2) First 3 lots		
a. Hot	50	See 3.4.4 & 4.3.3.9.4
b. Ambient	200	See 3.4.5 & 4.3.3.9.4
c. Cold	50	See 3.4.6 & 4.3.3.9.4
(3) Regular Production		
a. Hot	32	See 3.4.4 & 4.3.3.12.4
b. Ambient	125	See 3.4.5 & 4.3.3.12.4
c. Cold	32	See 3.4.6 & 4.3.3.12.4

Custodian:
Army-MU

Preparing activity:
Army-MU

Project Number: 1310-A-112

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER
ATTN: SMCAR-ESC-S
DOVER NJ. 07806-5000

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.