MILITARY SPECIFICATION

FUZE, MINE, AT, M608
PARTS FOR

1. SCOPE

1.1 This specification covers the parts for one type of mine fuze designated as Fuze, Mine, AT, M608.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-P-416 - Plating, Cadmium (Electrodeposited)

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification for.
MIL-C-5541 - Chemical Films and Chemical Film Materials for Aluminum and Aluminum Alloys.
MIL-A-8625 - Anodic Coatings, for Aluminum and Aluminum Alloys

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions.
MIL-STD-171 - Finishing of Metal and Wood Surfaces
MIL-STD-1168 - Lot Numbering of Ammunition.

FSC: 1345

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY MUNITIONS COMMAND

8889499 - Spring, Helical, Torsion
8889501 - Arm, Fuze Safing
8889502 - Spring, Helical Compression (Output Piston Return)
8889503 - Spring, Helical Compression
8889504 - Diaphragm, Special Shape (Input)
8889505 - Diaphragm, Special Shape (Output)
8889508 - Housing, Lead
8889510 - Housing, Detonator
8889512 - Cap, Output Piston
8889513 - Piston, Output
8889514 - Piston, Input
8889515 - Guide, Input Piston
8889516 - Chamber, Firing Pin
8889519 - Pin, Fuze Safing
8889520 - Pin, Firing
8889521 - Spacer, Sleeve
8889522 - Body, Fuze
9204010 - Knob Assembly, Arming
9204013 - Spring, Helical Compression (Plunger)
9204014 - Knob, Arming
9204019 - Orifice, Cup Assembly
9204020 - Ring, Locking
9204021 - Ring, Retaining
9204022 - Body, Arming Cap

PUBLICATIONS

U.S. ARMY MUNITIONS COMMAND

ET - 9204009 - Equipment Tabulation

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-The material shall be in accordance with applicable specifications and drawings.

3.2 Parts and assemblies.-The parts and assemblies shall comply with all requirements of applicable drawings (dwgs.) and applicable specifications.

3.3 Embrittlement.-The spring (see applicable dwg.) shall not break when stressed to the minimum (min.) point of permanent distortion when tested as specified in 4.4.1.

3.4 Workmanship.-All parts and assemblies shall be fabricated and assembled in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, porosity, dirt, unblended radii, grease, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

3.5 First article inspection.-This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.1.1 Submission of product.-At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number and date, together with identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificate of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 First article inspection

4.2.1 Submission.-Prior to the start of regular production, the contractor shall submit a first article sample (see 6.1c) to a Government approved facility as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2. The first article sample shall consist of 25 complete sets of parts (i.e., 25 each of every component and every sub-assembly) except that 40 of each plated or coated component shall be submitted. The first article sample shall have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing, shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including certificates of conformance for materials. A sample containing known defects will not be submitted unless specifically authorized by the contracting officer. A first article sample, or portion thereof, as

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

directed by the contracting officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed.-Assemblies and components will be subjected by the Government to any of all of the examinations or tests specified in 4.3.2 and 4.3.3 of this specification and any or all requirements of the applicable drawings. Testing for determination of compliance with plating or coating requirements shall be in accordance with the applicable references of MIL-STD-171 except that sample sizes shall be in accordance with Table I as follows:

TABLE I

Component and Applicable dwg.	Test and Sample Size		
	Plating Thickness	Salt Spray	Plating Adhesion
Spring, dwg. 8889499	5	5	5
Spring, dwg. 8889502	5	5	5
Spring, Dwg. 8889503	5	5	5
Pin, fuze, safing, dwg. 8889519	5	5	5
Spring, dwg. 9204013	5	5	5
Housing, lead, dwg. 8889506	-	10	-
Cap, output piston, dwg. 8889512	-	10	-
Piston, output, dwg. 8889513	-	10	-
Piston, input, dwg. 8889514	-	10	-
Guide, input piston, dwg. 8889515	-	10	-
Body, fuze, dwg. 8889522	-	10	-
Knob, arming, dwg. 9204014	-	10	-
Ring, locking, dwg. 9204020	-	10	-
Body, arming cap, dwg. 9204022	-	10	-

4.2.3 Rejection.-If any sub-assembly or component fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of any assembly or component in the sample to comply with any of the stated requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.3 Inspection provisions

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer in one unchanged process using the same materials and methods in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specifications, or drawings not affecting safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.3.2.1 Spacer, sleeve (see dwg. 8889521).

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Outside diameter	Gage	01001
102.	True position of inside diameter with outside diameter	Gage	01002
Minor:	AQL 1.5 percent		
201.	Thickness	Gage	01003
202.	Inside diameter	Gage	01004
203.	Finish improper	Visual	01006
204.	Evidence of poor workmanship (see 3.4)	Visual	01007

4.3.2.2 Pin, firing (see dwg. 8889520).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Profile of point	Gage	02001
102.	Length of point	Gage	02002
103.	Small outside diameter	Gage	02003
104.	Angle between large and small diameters	Gage	02004
105.	Concentricity of small diameter, point, and angle with large outside diameter	Gage	02005
Minor:	AQL 4.0 percent		
201.	Intermediate outside diameter	Gage	02006
202.	Large outside diameter	Gage	02007
203.	Total length	Gage	02008
204.	Distance from Datum on Angle to end of large diameter	Gage	02009
205.	Distance from datum on angle to point	Gage	02013
206.	Finish improper	Visual	02010
207.	Protective finish missing or contains bare spot	Visual	02011
208.	Evidence of poor workmanship (see 3.4)	Visual	02012

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.3.2.3 Diaphragm, special shape (output) and diaphragm, special shape (input) (see dwgs. 8889505 and 8889504).

Categories	Defects	Method of Inpsection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Hole, tear or other damage that may affect function	Visual	03001
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	03002

4.3.2.4 Piston, output (see dwg. 8889513).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.5 percent		
101.	Length of narrow slot	Gage	04001
102.	Total length	Gage	04002
103.	Large outside diameter	Gage	04003
104.	Runout of small outside diameter with large outside diameter	Gage	04004
105.	Location of keyhole with relation to large outside diameter	Gage	04005
106.	Location of narrow slot	Gage	04006
107.	Small width of keyhole	Gage	04007
108.	Length of keyhole	Gage	04008
109.	Length of flat on large outside diameter	Gage	04009
110.	Depth of flat on large outside diameter	Gage	04010
111.	Large width of keyhole	Gage	04011
112.	Location of large groove	Gage	04012
113.	Protective finish missing or contains bare spot	Visual	04013

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

Minor:	AQL 4.0 percent		
201.	Small outside diameter	Gage	04014
202.	Width of narrow slot	Gage	04015
203.	Length between keyhole and end	Gage	04016
204.	Width of large groove	Gage	04017
205.	Depth of large groove	Gage	04018
206.	Radius missing	Visual	04019
207.	Finish improper	Visual	04020
208.	Evidence of poor workmanship (see 3.4)	Visual	04021

4.3.2.5 Spring, helical compression (see dwg. 8889502).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Total length of projected end	Gage	05001
102.	Solid height, maximum (max)	Gage	05002
103.	Load at initial position compressed length	Gage	05003
104.	Load at final position compressed length	Gage	05004
Minor:	AQL 1.5 percent		
201.	Length of projected end above bend	Gage	05006
202.	Length to bend of projected end	Gage	05007
203.	Projective finish missing or contains bare spot	Visual	05008
204.	Evidence of poor workmanship (see 3.4)	Visual	05009

4.3.2.6 Cap, output piston (see dwg. 8889512).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Outside diameter	Gage	06001
102.	Location of rounded groove	Gage	06002
103.	Diameter of flat bottomed groove	Gage	06003
104.	Width of flat bottomed groove	Gage	06004
105.	Diameter of holes	Gage	06005

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Minor:	AQL 4.0 percent		
201.	Diameter of rounded groove	Gage	06006
202.	Diameter of cavity	Gage	06008
203.	Depth of cavity	Gage	06009
204.	Location of flat bottomed groove	Gage	06010
205.	Length	Gage	06011
206.	Location of holes	Gage	06012
207.	Distance from bottom to intersection of outside diameter and spherical radius	Gage	06013
208.	Runout of inside diameter with outside diameter	Gage	06014
209.	Runout of groove with outside diameter	Gage	06015
210.	Finish improper	Visual	06016
211.	Protective finish missing or contains bare spot	Visual	06017
212.	Evidence of poor workmanship (see 3.4)	Visual	06018
213.	Concentricity of 5 grooves	Visual	06019

4.3.2.7 Housing, lead (see dwg. 8889508).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Location of hole counterbore and small outside diameter with large outside diameter	Gage	07001
102.	Large outside diameter	Gage	07002
103.	Diameter of hole	Gage	07003
104.	Diameter of hole counterbore	Gage	07004
105.	Depth of hole counterbore	Gage	07005
106.	Length	Gage	07006
107.	Location of hole with hole counterbore	Gage	07016
Minor:	AQL 4.0 percent		
201.	Small outside diameter	Gage	07007
202.	Large diameter of recess	Gage	07008
203.	Small diameter of recess	Gage	07009
204.	Depth of recess	Gage	07010
205.	Length of small outside diameter	Gage	07011

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

206.	Length and angle of chamfer	Gage	07012
207.	Finish improper	Visual	07013
208.	Protective finish missing or contains bare spot	Visual	07014
209.	Evidence of poor workmanship (see 3.4)	Visual	07015

4.3.2.8 Ring, locking (see dwg. 9204020).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Pitch diameter of thread	Gage	08001
102.	Minor diameter of thread	Gage	08002
103.	Length from top of thread to bottom of ring	Gage	08003
Minor:	AQL 4.0 percent		
201.	Inside diameter	Gage	08004
202.	Length	Gage	08005
203.	Thickness of tabs	Gage	08006
204.	Outside diameter	Gage	08007
205.	Length across tabs	Gage	08008
206.	Width of tabs	Gage	08009
207.	Finish improper	Visual	08010
208.	Protective finish missing or contains bare spot	Visual	08011
209.	Evidence of poor workmanship (see 3.4)	Visual	08012

4.3.2.9 Housing, detonator (see dwg. 8889510).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Diameter of boss	Gage	09001
102.	Location of hole in boss	Gage	09002
103.	Location of boss	Gage	09003
104.	Location of counterbored hole	Gage	09004
105.	Width	Gage	09005
106.	Thickness excluding boss	Gage	09006
107.	Diameter of counterbore	Gage	09007
108.	Diameter of counterbored hole	Gage	09008
109.	Slot length insufficient	Visual	09009

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

Minor:	AQL 4.0 percent		
201.	Diameter of hole in boss	Gage	09010
202.	Width of slot in boss	Gage	09011
203.	Length of boss	Gage	09012
204.	Total length	Gage	09013
205.	Depth of counterbore	Gage	09014
206.	Chamfer missing	Visual	09015
207.	Radius missing	Visual	09016
208.	Finish improper	Visual	09018
209.	Evidence of poor workmanship (see 3.4)	Visual	09019

4.3.2.10 Ring, retaining (see dwg. 9204021).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	None defined.		
Minor:	AQL 1.5 percent		
201.	Diameter of wire	Gage	10001
202.	Outside diameter	Gage	10002
203.	Width of slot, max	Gage	10003
204.	Evidence of poor workmanship (see 3.4)	Visual	10004

4.3.2.11 Guide, input piston (see dwg. 8889515).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Diameter of counterbore	Gage	11001
102.	Thickness through bottom of counterbore	Gage	11002
103.	True position of hole, and hole counterbore with outside diameter	Gage	11003
104.	Outside diameter	Gage	11004

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

Minor:	AQL 2.5 percent		
201.	Length	Gage	11005
202.	Diameter of hole	Gage	11006
203.	Chamfer incorrect	Visual	11007
204.	Finish improper	Visual	11008
205.	Protective finish missing or contains bare spot	Visual	11009
206.	Evidence of poor workmanship (see 3.4)	Visual	11010
207.	Concentricity of grooves	Visual	11011

4.3.2.12 Piston, input (see dwg. 8889514).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Large outside diameter	Gage	12001
102.	Runout of small outside diameter with large outside diameter	Gage	12002
103.	Short length to flange, max	Gage	12003
104.	Long length to flange, max	Gage	12004
Minor:	AQL 2.5 percent		
201.	Thickness of flange	Gage	12005
202.	Small outside diameter	Gage	12006
203.	Protective finish missing or contains bare spot	Visual	12007
204.	Finish improper	Visual	12008
205.	Evidence of poor workmanship (see 3.4)	Visual	12009

4.3.2.13 Body, arming cap (see dwg. 9204022).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.5 percent		
101.	Pitch diameter of thread, min	Gage	13001
102.	Major diameter of thread, min	Gage	13002
103.	Total length	Gage	13003
104.	Width of outside groove	Gage	13004
105.	Diameter of outside groove	Gage	13005

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

106.	Distance to outside groove from small end	Gage	13006
107.	Small inside diameter	Gage	13007
108.	Distance from inside groove to bottom of arming knob cavity	Gage	13008
109.	Diameter of arming knob cavity	Gage	13009
110.	True position of slot with arming knob cavity	Gage	13010
111.	Angular location of slots	Gage	13011
112.	Width of slots	Gage	13012
113.	Length of slots	Gage	13013
114.	Location of recess between SAFE and ARMED	Gage	13014
115.	Location of hole through both walls of body	Gage	13015
116.	Marking missing or incorrect	Visual	13016
Minor:	AQL 4.0 percent		
201.	Diameter of fuze body cavity	Gage	13017
202.	Depth of cavity to surface of small inside diameter	Gage	13018
203.	Depth of recess between SAFE and ARMED	Gage	13019
204.	Radius of recess between SAFE and ARMED	Gage	13020
205.	Width of inside groove	Gage	13021
206.	Chamfer missing	Visual	13022
207.	Hole or slot missing in recess between SAFE and ARMED	Visual	13023
208.	Finish improper	Visual	13024
209.	Protective finish missing or contains bare spot	Visual	13025
210.	Evidence of poor workmanship (see 3.4)	Visual	13026

4.3.2.14 Body, fuze (see dwg. 8889522).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 2.5 percent		
101.	Large outside diameter	Gage	14001
102.	Diameter of three blind holes inside wall	Gage	14002
103.	Location of counterbored cavity in flat side of outside diameter	Gage	14003

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

104.	Thickness between bottom of counterbored cavity in flat side of outside diameter and outside diameter	Gage	14004
105.	Diameter of counterbored cavity in flat side of outside diameter	Gage	14005
106.	Diameter of counterbore in flat side	Gage	14006
107.	Distance from outside diameter to counterbore in flat side	Gage	14007
108.	Location of counterbore in the flat side with cavity	Gage	14008
109.	Diameter of intersecting hole in counterbore of cavity on the flat side	Gage	14009
110.	Location of intersecting hole in counterbore of cavity on flat side	Gage	14010
111.	Small outside diameter	Gage	14011
112.	Diameter of small center hole	Gage	14012
113.	Length across radiused slot of center hole	Gage	14013
114.	Length of large oval slot in large counterbore of center hole	Gage	14014
115.	Distance to large oval slot in large counterbore from top surface	Gage	14015
116.	Width of large oval slot in large counterbore of center hole	Gage	14016
117.	Location of large oval slot in large counterbore of center hole	Gage	14017
118.	Width of small slot within large oval slot	Gage	14018
119.	Length of small slot	Gage	14019
120.	Pitch diameter of thread, max	Gage	14020
121.	Minor diameter of thread, max	Gage	14021
122.	Location of threaded hole	Gage	14022
123.	Location of recessed segment in top surface	Gage	14023
124.	Location of hole intersecting recessed segment in top surface	Gage	14024
125.	Depth of hole intersecting recessed segment in top surface	Gage	14025

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

126.	Diameter of hole at apex of recessed segment in top surface...	Gage	14026
127.	Depth of hole at apex of recessed segment in top surface...	Gage	14027
128.	Location of hole at apex of recessed segment in top surface...	Gage	14028
129.	Diameter of cavity intersected by threaded hole.....	Gage	14029
130.	Depth from top surface to bottom cavity intersected by threaded hole.....	Gage	14030
131.	Depth of counterbore of cavity intersected by threaded hole.....	Gage	14031
132.	Diameter of counterbore of cavity intersected by threaded hole.....	Gage	14032
133.	Depth of hole beneath thread.....	Gage	14033
134.	Runout of cavity intersected by threaded hole with counterbore....	Gage	14034
135.	Location of three blind holes in side wall.....	Gage	14035

Minor: AQL 4.0 percent

201.	Depth of three blind holes in side wall.....	Gage	14036
202.	Diameter of large counterbore of center hole.....	Gage	14037
203.	Distance to large counterbore of center hole from top surface.....	Gage	14038
204.	Diameter of small counterbore of center hole.....	Gage	14039
205.	Depth of small counterbore of center hole.....	Gage	14040
206.	Diameter of hole below threads, min.....	Gage	14041
207.	Diameter of hole intersecting recessed segment in top surface...	Gage	14042
208.	Length of large outside diameter..	Gage	14043
209.	Total length.....	Gage	14044
210.	Distance from outside diameter to flat side.....	Gage	14049
211.	Diameter of counterbore in hole at apex of recessed segment.....	Gage	14050
212.	Depth of counterbore in hole at apex of recessed segment.....	Gage	14051
213.	Location of counterbore with hole at apex of recessed segment.....	Gage	14052
214.	Presence of spring recess intersecting large oval slot.....	Visual	14045

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

215.	Finish improper	Visual	14046
216.	Protective finish missing or contains bare spot	Visual	14047
217.	Evidence of poor workmanship (see 3.4)	Visual	14048

4.3.2.15 Spring, helical compression (see dwg. 8889503).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Solid height, max	Gage	15001
102.	Load at initial position compressed length	Gage	15002
103.	Load at final position compressed length	Gage	15003
Minor:	AQL 1.0 percent		
201.	Protective finish missing or contains bare spot	Visual	15004
202.	Evidence of poor workmanship (see 3.4)	Visual	15005

4.3.2.16 Pin, fuze safing (see dwg. 8889519).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Length from large diameter end to start of large notch	Gage	16001
102.	Thickness of flat on large diameter	Gage	16002
103.	Runout of small outside diameter, groove diameter with large outside diameter	Gage	16003
104.	Parallelism of large notch with small notch	Gage	16004
105.	Distance from large diameter end to top of large notch	Gage	16015
Minor:	AQL 4.0 percent		
201.	Large outside diameter	Gage	16005
202.	Small outside diameter	Gage	16006
203.	Total length	Gage	16007
204.	Length of large diameter	Gage	16008

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

205.	Length to notch on small diameter.	Gage	16009
206.	Length of notch on small diameter.	Gage	16010
207.	Thickness of notch on small diameter	Gage	16011
208.	Diameter of groove	Gage	16016
209.	Length to groove from large diameter	Gage	16017
210.	Length of groove	Gage	16018
211.	Chamfer missing	Visual	16012
212.	Finish improper	Visual	16013
213.	Evidence of poor workmanship (see 3.4)	Visual	16014

4.3.2.17 Arm, fuze safing (see dwg. 8889501).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Pitch diameter of thread, max.	Gage	17001
102.	Minor diameter of thread, max.	Gage	17002
103.	True position of counterbore with threads	Gage	17003
104.	Location of threaded hole	Gage	17004
105.	Thread length, minimum	Gage	17005
106.	Location of hole	Gage	17006
Minor:	AQL 4.0 percent		
201.	Diameter of hole	Gage	17007
202.	Distance from radiused end to hole	Gage	17008
203.	Width of side parallel to hole axis	Gage	17009
204.	Width of side perpendicular to hole axis	Gage	17010
205.	Diameter of counterbore	Gage	17011
206.	Depth of threaded hole counterbore	Gage	17012
207.	Cut-out missing or incorrectly located with respect to hole	Visual	17013
208.	Protective finish missing or contains bare spot	Visual	17014
209.	Finish improper	Visual	17015
210.	Evidence of poor workmanship (see 3.4)	Visual	17016

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.3.2.18 Knob, arming (see dwg. 9204014 covering a detail of dwg. 9204010).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.5 percent		
101.	Diameter of blind hole in boss	Gage	18001
102.	Depth of blind hole in boss	Gage	18002
103.	Location of blind hole in boss	Gage	18003
104.	Outside diameter	Gage	18004
105.	Pitch diameter of threaded holes	Gage	18005
106.	Minor diameter of threaded holes, max	Gage	18006
107.	Location of threaded holes	Gage	18007
108.	Diameter of flange forward of small groove	Gage	18008
109.	Diameter of large groove	Gage	18009
110.	Width of large groove	Gage	18010
111.	Diameter of threaded hole counterbore	Gage	18011
112.	Depth of threaded hole counterbore	Gage	18012
113.	Diameter of blind hole in bottom	Gage	18013
114.	Depth of blind hole in bottom	Gage	18014
115.	Location of blind hole in bottom	Gage	18015
116.	Runout of large and small grooves with outside diameter	Gage	18016
117.	Position of threaded hole counterbore with threads	Gage	18017
118.	Location of arrow	Visual	18018
Minor:	AQL 4.0 percent		
201.	Diameter of small groove	Gage	18019
202.	Length from flange forward of small groove to top of boss	Gage	18020
203.	Width of small groove	Gage	18021
204.	Thickness of flange between large and small grooves	Gage	18022
205.	Length from top of boss to flange between large and small grooves	Gage	18023
206.	Length from flange between large and small grooves to base	Gage	18024
207.	Chamfer missing	Visual	18025

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

208.	Finish improper	Visual	18026
209.	Protective finish missing or contains bare spot	Visual	18027
210.	Evidence of poor workmanship (see 3.4)	Visual	18028

4.3.2.19 Guide plunger (see dwg. 9204012 covering a detail of dwg. 9204010).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Pitch diameter of thread	Gage	19001
102.	Major diameter of thread, min.	Gage	19002
103.	Length of effective thread, min.	Gage	19003
104.	Diameter of head	Gage	19004
105.	True position of head with thread	Gage	19005
Minor:	AQL 2.5 percent		
201.	Total length	Gage	19006
202.	Length to head	Gage	19007
203.	Slot missing	Visual	19008
204.	Finish improper	Visual	19010
205.	Evidence of poor workmanship (see 3.4)	Visual	19011

4.3.2.20 Plunger (see dwg. 9204011 covering a detail of dwg. 9204010).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.40 percent		
101.	Location of head with hole	Gage	20001
102.	Location of counterbore with hole	Gage	20002
Minor:	AQL 4.0 percent		
201.	Length of head	Gage	20003
202.	Diameter of head	Gage	20004
203.	Diameter of shank	Gage	20005
204.	Diameter of hole	Gage	20006
205.	Diameter of hole counterbore	Gage	20007
206.	Length of hole counterbore	Gage	20008

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

207.	Angle on head missing	Visual	20009
208.	Finish improper	Visual	20010
209.	Evidence of poor workmanship (see 3.4)	Visual	20012

4.3.2.21 Spring, helical compression (see dwg. 9204013 covering a detail of dwg. 9204010).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Load at initial position, compressed height	Gage	21002
102.	Load at working position, compressed height	Gage	21003
Minor:	AQL 1.0 percent		
201.	Protective coating missing or contains bare spot	Visual	21004
202.	Evidence of poor workmanship (see 3.4)	Visual	21005

4.3.2.22 Knob assembly, arming (see dwg. 9204010).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Lengh of headless groove pin protrusion, min	Gage	22001
Major:	AQL 0.65 percent		
101.	Length of off-center plunger protrusion	Gage	22002
102.	Length of center plunger protrusion	Gage	22003
103.	Guide plunger loose or not sealed	Visual-Manual	22004
104.	Component missing or damaged to extent that function may be impaired	Visual	22005
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	22006

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.3.2.23 Spring, helical torsion (see dwg. 8889499).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Torque at initial position	Gage	23001
102.	Torque at final position	Gage	23002
103.	Free height, max	Gage	23003
104.	Solid height, max	Gage	23004
Minor:	AQL 2.5 percent		
201.	Length of straight leg	Gage	23005
202.	Length to offset leg	Gage	23006
203.	Length of offset	Gage	23007
204.	Protective finish missing or contains bare spot	Visual	23008
205.	Evidence of poor workmanship (see 3.4)	Visual	23009

4.3.2.24 Chamber, firing pin (see dwg. 8889516).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 1.0 percent		
101.	Diameter of cavity	Gage	24001
102.	Diameter of hole	Gage	24002
103.	Location of hole	Gage	24003
104.	Perpendicularity of slot with hole	Gage	24004
105.	Concentricity of cavity with small outside diameter	Gage	24005
106.	True position of large outside diameter	Gage	24006
Minor:	AQL 4.0 percent		
201.	Small outside diameter	Gage	24007
202.	Length below large outside diameter	Gage	24008
203.	Large outside diameter	Gage	24009
204.	Length of large outside diameter	Gage	24010

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

205.	Width of slot	Gage	24011
206.	Depth of slot	Gage	24012
207.	Depth of cavity	Gage	24013
208.	Finish improper	Visual	24015
209.	Evidence of poor workmanship (see 3.4)	Visual	24016
210.	Presence of undercut	Visual	24017

4.3.2.25 Holder, Orifice Disc (see dwg. 9241668 covering a detail of dwg. 9204019).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Small outside diameter	Gage	25001
102.	Diameter of hole, min	Gage	25002
103.	Location of hole with small outside diameter	Gage	25003
104.	Parallelism of flange with bottom	Gage	25004
Minor:	AQL 1.5 percent		
201.	Large outside diameter	Gage	25005
202.	Length from flange to bottom	Gage	25006
203.	Thickness of flange	Gage	25007
204.	Evidence of poor workmanship (see 3.4)	Visual	25008

4.3.2.26 Orifice Cup Assembly (see dwg. 9204019).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Disc missing or loose	Visual-Manual	26006
Major:	AQL 0.65 percent		
101.	Diameter of orifice in disc	Gage	26001
102.	Location of orifice with inside diameter of cup	Gage	26002
103.	Burrs in orifice	Visual	26003
104.	Sealant in or near hole	Visual	26004
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	26005

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.3.3 Testing:

4.3.3.1 Spring embrittlement (see 3.3) - Major defect - see Table I).

TABLE I

COMPONENT	CODE NO.
Spring, Helical, torsion (see dwg. 8889499)	28001
Spring, helical, compression (see dwg. 8889502)	28002
Spring, Helical, compression (see dwg. 8889503)	28003
Spring, helical, compression (see dwg. 9204013)	28004

4.3.3.1.1 Beginning with the first lot produced and continuing until three (3) consecutive lots have complied with the acceptance critera specified, the sampling plan for this test shall be in accordance with MIL-STD-105 using Code Letter K and an AQL of 0.40 percent. The test shall be performed as specified in 4.4.1, using equipment in accordance with 4.3.4. Any spring which fails to comply with the specified requirement shall be classed defective. Springs so tested shall be discarded as scrap.

4.3.3.3.2 After three (3) consecutive lots have met the criteria of 4.3.3.1.1, the sampling plan for this test shall be in accordance with MIL-STD-105 using Code Letter G and an AQL of 0.40 percent.

4.3.4 Inspection equipment.-Equipment Tabulation Number ET-9204009 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in 6.3.

4.3.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET amy be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.4 Test methods and procedures

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

4.4.1 Spring embrittlement.-The springs shall be stressed to the minimum point of permanent distortion and observation made to determine compliance with the applicable requirement. Test equipment shall be as specified in 4.3.4.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level C.-The fuze parts and subassemblies shall be packaged in accordance with MIL-STD-1169.

5.2 Packing

5.2.1 Level C.-The fuze parts and subassemblies shall be packed in accordance with MIL-STD-1169.

5.3 Marking.-Each unit, intermediate and exterior container shall be marked in accordance with MIL-STD-1169 requirements.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in MIL-STD-1167.
c. Provisions for submission of first article samples.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are also used to correlate the characteristics cited on Equipment Lists with the inspections listed in this specification. In addition, they should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraphs 6.3.1 through 6.3.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SPCPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design on controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are refelcted on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finishes, notes, operating and

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.

calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category A, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit three copies of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-MD15. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 1345-A-290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:01Z
Check the source to verify that this is the current version before use.