MIL-I-50362(MU)
28 November 1973
SUPERSEDING
RP-PD-121, Rev. 1
24 February 1956

MILITARY SPECIFICATION

INITIATOR, CARTRIDGE ACTUATED, M8, METAL PARTS ASSEMBLY

1. SCOPE

1.1 This specification covers Initiator, Cartridge Actuated, M8, Metal Parts Assembly. The assembly will ultimately be loaded and used in conjunction with other propellant actuated devices in aircrew emergency escape systems.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification for

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions

DRAWINGS

Armament Command

C8796726	- Container, Ammunition, Fiber M380 for Initiator, Cartridge Axtuated M8, with Cartridge M68
C8796707	- Box, Packing, Ammunition for Initiator, Cartridge Actuated, M8 with Cartridge, M68 in Fiber Container M380
C9241015	- Carton, Alternative Packing, Ammunition, for Initiator, Cartridge Actuated, M8 with Cartridge, M68 in Fiber Container, M380
F10534133	- Initiator, Cartridge Actuated M8 Metal Parts Assembly

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions shall be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.-The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bid or request for proposal shall apply.

ANSI B46.1 - Surface Texture

(Application for copies should be addressed to the American National Standards Institute (ANSI), 1430 Broadway, New York, N.Y. 10018.)

3. REQUIREMENTS

3.1 General.-Materials, parts, and assemblies shall comply with the requirements specified on the applicable drawings, referenced specifications, and the following:

3.2 Mechanical properties.-Mechanical properties required by the drawing shall be uniform throughout the part within specified tolerances. Requirements for all alloy steel parts shall be achieved by quenching and tempering.

3.3 Hydrostatic pressure.-The subassembly consisting of an initiator cap, plug simulating the firing pin housing without firing pin hole and with an "O" ring, body, filter and cap, shall withstand a hydrostatic pressure of 900 pounds per square inch (PSI), for 15 seconds, minimum (min.) without application of any external load other than that applied by the liquid pressure and shall show no evidence of leakage or mechanical failure (see 6.2).

3.4 Firing pin release.-The firing pin of the assembled initiator, pin, less safety pin, cartridge, body, filter and cap, shall release from the cocked position when the application of an axial load of 25 to 35 pounds has withdrawn the initiator pin 3/4 inches, maximum.

3.5 Initiator pin security.-The initiator pin of the assembled initiator less cartridge, body, filter and cap, shall not withdraw beyond the safety pin when subjected to an axial load of 200 to 220 pounds. Application of the load shall not cause permament deformation of the safety pin.

3.6 Metal parts assembly.-Parts shall be combined to produce an assembly which conforms to the requirements of the metal parts assembly drawing. All threaded joints shall be assembled handtight.

3.7 Protective finish.-The protective finish shall be in accordance with the applicable specifications, and shall apply to all surfaces of the component regardless of contour configuration.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

3.8 Residual magnetism.-The metal parts assembly shall not deflect the indicator of the compass more than three degrees in either direction, when passed in front of the compass at a distance of six inches.

3.9 Workmanship.-Requirements for workmanship are as specified on the applicable drawings, referenced specifications, and the following:

3.9.1 Metal defects.-All components shall be free from cracks, splits, cold shuts, inclusions, porosity, or any similar defect.

3.9.2 Burr.-The part shall not have a burr which might interfere with the assembly or function of the item, or be injurious to personnel handling the item.

3.9.3 Foreign matter.-The part or assembly shall not contain chips, dirt, grease, rust, corrosion, or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.-Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

4.1.2 Inspection.-Inspection shall be in accordance with MIL-A-2550.

4.2 First article sample.

4.2.1 Initial production sample.-At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 5 subassemblies for hydrostatic pressure test; and 10 sets of unassembled components for visual and dimensional examination and test.

The sample shall be manufactured using the same materials, equipment processes and procedures as used in regular production. All parts and materials, including packaging and packing shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and tests.-After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facilty specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

specified herein, unless disapproved by the Government. The

4.2.1.2 Initial production sample failure.-Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.-The product shall be submitted in accordance with MIL-STD-105

4.3.1.2 Size of lot.-Unless otherwise specified by the procuring agency, a lot of metal parts shall consist of an identifiable group of metal parts assemblies, produced by a homogeneous process.

4.3.2 Examination.-One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plan and associated criteria in Tables I and II. For an individual defect (single characteristic), the criteria in Table I shall be used. For total defects within a major or minor group, the criteria in Table II shall be used. All non-conforming material shall be rejected. Inspection for rubber O-rings shall be in accordance with MIL-STD-413. The Ordnance Standard Finish Blocks prescribed in ANSI B46.1 shall be used as a basis of comparison for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

TABLE I

Lot Size	Sample Size	Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% Examination	-	-	-	-
301 - 1300	110	1	2	2	3
1301 - 3200	150	2	3	3	4
3201 - 8000	225	3	4	4	5
8001 - 22000	300	4	5	5	6

TABLE II

	Total Allowable Defects Per Sample Size			
Sample Size for Major Defects - - - - - -	110	150	225	300
Number of Characteristics in Class				
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 - 19	3	4	5	7
20 - 43	4	5	8	10
Over 43	6	8	11	14

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

TABLE II (Cont'd)

	Total Allowable Defects Per Sample Size			
Sample Size for Minor Defects - - - - - -	110	150	225	300
Number of Characteristics in Class				
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
Over 48	8	11	17	20

4.3.2.1 Body, Drawing D10523310, covering a detail of Drawing F10534133.

Defect	Method of Inspection
CRITICAL	
1. Metal defective	Visual
MAJOR	
101. Concentricity of body (groove end) with bore	Gage
102. Concentricity of groove with body (groove end)	Gage
103. Concentricity of counterbore with bore	Gage
104. Concentricity of pitch diameter of thread (counterbore end) with bore	Gage
105. Concentricity of pitch diameter of thread with body (groove end)	Gage
106. Pitch diameter of thread (groove end), min.	Gage
107. Major diameter of thread (groove end), min.	Gage
108. Pitch diameter of thread (counterbore end), min.	Gage
109. Major diameter of thread (counterbore end), min.	Gage
110. Perpendicularity of face with body (groove end)	Gage
111. Diameter of bore	Gage
112. Diameter of groove, min.	Gage
113. Diameter of counterbore	Gage
114. Diameter of body (groove end), min.	Gage
115. Depth of counterbore	Gage
116. Permissable variation in wall groove	Measured
117. Diameter of body	Measured

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

Defect	Method of Inspection
118. Total length	Measured
119. Location of thread (groove end)	Measured
120. Location of groove	Measured
121. Width of groove	Measured
122. Length of thread pilot (groove end)	Gage
123. Depth and angle of bore chamfer (groove end)	Measured
124. Length of threads (counterbore end)	Measured
125. Radius of minor diameter of counterbore	Gage
126. Radius (2 radius) at top of groove	Gage
127. Threads damaged or not full	Visual
128. Protective finish inadequate or defective	Visual
129. Burr or sharp corner	Visual
130. Foreign matter	Visual
131. Radius and chamfer missing or incorrect	Visual
132. Surface finish 125 improper	Visual
133. Marking missing, incorrect or illegible	Visual

MINOR

None defined	1/

4.3.2.2 Filter, Drawing C10522667 covering a detail of Drawing F10534133.

CRITICAL

None defined

MAJOR

101. Concentricity of body with flange	Gage
102. Perpendicularity of body with face of flange	Gage
103. Concentricity of datum diameter with flange	Gage
104. Diameter of body, min.	Gage
105. Diameter of flange, min.	Gage
106. Diameter at datum location, min.	Gage
107. Depth and angle of metering slot	Measured
108. Width of metering slot	Gage
109. Thickness of flange, min.	Gage
110. Datum angle incorrect	Measured
111. Diameter of cavity	Measured
112. Depth of cavity	Measured

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

4.3.2.2 (Cont'd)

Defect	Method of Inspection
113. Total length	Measured
114. Location of metering slot to centerline of body	Measured
115. Radius and chamfer missing or incorrect	Visual
116. Surface of 125 improper	Visual
117. Surface finish improper except as otherwise noted	Visual
118. Protective finish inadequate or defective	Visual
119. Metal defective	Visual
120. Burr	Visual
121. Foreign matter	Visual
122. Marking missing, incorrect or illegible	Visual
MINOR	
None defined	1/

4.3.2.3 Cap, Drawing D10522668 covering a detail of Drawing F10534133.

CRITICAL	
1. Thread damaged or not full	Visual
2. Foreign matter in gas port	Visual
MAJOR	
101. Concentricity of bore (unthreaded) with pitch diameter of internal thread	Gage
102. Concentricity of thread pilot on gas port outlet with pitch diameter of external gas port threads	Gage
103. Perpendicularity of base of bore (unthreaded) with internal threads	Gage
104. Pitch diameter of internal thread	Gage
105. Major diameter of internal thread, min.	Gage
106. Pitch diameter of external thread, min.	Gage
107. Major diameter of external thread, min.	Gage
108. Diameter of bore (unthreaded)	Gage
109. Diameter of bore (threaded)	Gage
110. Diameter of body (small end)	Measured
111. Diameter of body (large end), min.	Gage
112. Diameter of gas port outlet (before external thread), min.	Gage
113. Diameter of gas port outlet (after external thread), min.	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

4.3.2.3 (Cont'd)

	Defect	Method of Inspection
114.	Diameter of gas port hole	Gage
115.	Pitch diameter of set screw hole (2 holes)	Gage
116.	Major diameter of set screw hole (2 holes), min.	Gage
117.	Angle of chamfer on face of bore (threaded)	Measured
118.	Width of chamfer on face of bore (threaded)	Gage
119.	Angle at the ends of external thread	Measured
120.	Basic angle of nose of gas port outlet	Measured
121.	Width of counterbore between threaded bore and unthreaded bore	Gage
122.	Angle of countersink of set screw hole (2 holes)	Measured
123.	Depth of countersink of set screw hole (2 holes	Gage
124.	Internal angle incorrect	Measured
125.	Location of base of bore (unthreaded) face of body (large end)	Gage
126.	Location of internal angle to face of body (large end)	Measured
127.	Location of set screw hole (2 holes) to face of body (large end)	Measured
128.	Location of datum diameter	Gage
129.	Location of front of external thread to nose of gas port outlet	Gage
130.	Location of rear of external thread to face of body (small end)	Gage
131.	Angular location of set screw hole (2 holes) on body (large end)	Measured
132.	Total length, min.	Measured
133.	Length of body (large end)	Measured
134.	Length of gas port outlet	Gage
135.	Width and angle of beveled edge of body (small end)	Measured
136.	Surface finish 125 improper, except as otherwise noted	Visual
137.	Protective finish inadequate or defective	Visual
138.	Burr or sharp corners	Visual
139.	Radius and chamfer missing or incorrect	Visual
140.	Surface finish improper	Visual
141.	Metal defective	Visual
142.	Marking missing, incorrect or illegible	Visual
143.	Foreign matter	Visual

MINOR

None defined	1/

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

4.3.2.4 Cap, Initiator, Drawing 10534135 covering a detail of Drawing F10534133 .

Defect	Method of Inspection
CRITICAL	
1. Surface finish 63 improper	Visual
MAJOR	
101. Concentricity of body (large) with pitch diameter of thread (large bore)	Gage
102. Concentricity of pitch diameter of thread (large end) with firing pin housing cavity	Gage
103. Concentricity of firing pin cavity with the firing pin housing cavity	Gage
104. Concentricity of small bore with firing pin housing cavity	Gage
105. Parallelism of stand groove with safety pin hole	Gage
106. Perpendicularity of thread (bore) undercut with firing pin housing cavity	Gage
107. Diameter of body (large), min.	Gage
108. Diameter of body (small)	Measured
109. Diameter of firing pin cavity	Gage
110. Diameter of firing pin housing cavity	Gage
111. Diameter of thread (bore) undercut	Gage
112. Diameter of small bore	Gage
113. Diameter of base of safety pin groove, min.	Gage
114. Diameter of safety pin hole	Gage
115. Diameter of stand groove, min.	Gage
116. Pitch diameter of thread (large bore)	Gage
117. Major diameter of thread (large bore, min.	Gage
118. Pitch diameter of thread of forward set screw hole (2 holes)	Gage
119. Major diameter of thread of forward set screw hole (2 holes), min.	Gage
120. Pitch diameter of thread of rear set screw	Gage
121. Major diameter of thread of rear set screw hole, min.	Gage
122. Width of body (large)	Measured
123. Widht of large bore	Gage
124. Diameter of safety pin groove	Gage
125. Width of stand groove	Gage
126. Location of face of small body to stand groove, min.	Gage

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

4.3.2.4 (Cont'd)

Defect	Method of Inspection
127. Location of face of small body to base of safety pin groove, min.	Gage
128. Location of base of firing pin cavity to face of large body	Gage
129. Location of base of firing pin housing cavity to face of large body	Measured
130. Location of forward set screw hole (2 holes) to face of large body	Measure
131. Location of rear set screw hole to face of large body	Measure
132. Width of thread undercut (bore)	Measure
133. Location of safety pin hole to center of small body, min.	Gage
134. Depth of stand groove	Gage
135. Depth of set screw hole chamfer	Gage
136. Width of chamfer at face of small body and large body	Measure
137. Depth of chamfer at large bore	Gage
138. Depth of chamfer at small bore	Measure
139. Depth of chamfer at firing pin housing cavity	Measure
140. Width of stand groove	Gage
141. Angle cut of large body	Measure
142. Angled surfaces missing or incorrect	Visual/Measure
143. Location of forward set screw hole (2 holes) on large body	Measure
144. Total length, min.	Gage
145. Surface finish 125 improper, except as otherwise noted	Visual
146. Protective finish inadequate or defective	Visual
147. Burr	Visual
148. Radius and chamfer missing or incorrect	Visual
150. Metal defective	Visual
151. Marking missing, incorrect or illegible	Visual
152. Foreign matter	Visual
MINOR	
None defined	1/

4.3.2.5 Initiator, Pin, Drawing C10534138 covering a detail of Dwg. F10534133.

CRITICAL	
1. Metal defective	Visual
2. Surface finish 63 improper	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the currentversion before use.

4.3.2.5 (Cont'd)

Defect	Method of Inspection
3. Surface finish 32 improper	Visual
MAJOR	
101. Concentricity of body with head	Gage
102. Diameter of body, min.	Gage
103. Large diameter of head, min.	Gage
104. Small diameter of head	Measure
105. Daimater of base of safety pin groove, min.	Gage
106. Diameter of pull hole tab shoulder	Measure
107. Diameter of pull hole tab body	Measure
108. Spherical profile of pull hole tab	Measure
109. Diameter of pull hole	Gage
110. Thickness of pull hole tab, min.	Gage
111. Width of minor chamfer of head	Gage
112. Width of flat and minor chamfer of head combined, min.	Gage
113. Thickness of pull hole tab body	Measure
114. Location of face to center of pull hole, min.	Gage
115. Location of pull hole tab body to face of head	Gage
116. Location of body to pull hole tab body, min.	Gage
117. Location of safety pin groove to body, min.	Gage
118. Total length, min.	Gage
119. Angle of ball seat, min.	Gage
120. Angled surfaces missing or improper	Visual/Measure
121. Surface finish 125 improper, except as otherwise noted	Visual
122. Protective finish inadequate or defective	Visual
123. Burr	Visual
124. Radius and chamfer missing or incorrect	Visual
125. Surface finish improper	Visual
126. Marking missing, incorrect or illegible	Visual
127. Foreign matter	Visual
MINOR	
None defined	1/

4.3.2.6 Housing, Firing Pin, Dwg. C10534136 covering a detail of Dwg. F10534133.

CRITICAL	
1. Surface finish 16 improper	Visual
2. Diameter of striker hole	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

4.3.2.6 (Cont'd)

Defect	Method of Inspection
MAJOR	
101. Concentricity of striker hole with body	Gage
102. Concentricity of pitch diameter of thread (boss) with body	Gage
103. Concentricity of bore with body	Gage
104. Perpendicularity of face of head with body diameter	Gage
105. Pitch diameter of boss thread, min.	Gage
106. Major diameter of boss thread, min.	Gage
107. Diameter of face of head, min.	Gage
108. Diameter of body, min.	Gage
109. Diameter of bore	Gage
110. Diameter of firing pin seat	Measure
111. Diameter of mounting hole (2 holes)	Measure
112. Depth of mounting hole (2 holes)	Measure
113. Width of firing pin seat	Gage
114. Width of body chamfer, min.	Gage
115. Width of head	Gage
116. Location of base of bore to face of head, min.	Gage
117. Location of thread boss to face of head	Gage
118. Centerline distance between strikes hole and mounting hole (2 holes), min.	Gage
119. Centerline distance between mounting hole (2 holes), min.	Gage
120. Total length, min.	Gage
121. Angled surfaces missing or improper	Visual/Measure
122. Surface finish 125 improper, except as otherwise noted	Visual
123. Surface finish improper	Visual
124. Protective finish inadequate or defective	Visual
125. Metal defective	Visual
126. Burr	Visual
127. Sharp corners	Visual
128. Radius and chamfer missing or incorrect	Visual
129. Marking missing, incorrect or illegible	Visual
130. Foreign matter	Visual
MINOR	
None defined	1/

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

4.3.2.7 Pin, Firing, Drawing C10534137 covering a detail of Dwg. F10534133.

Defect	Method of Inspection
CRITICAL	
1. Surface finish 32 improper	Visual
2. Surface finish 16 improper	Visual
3. Major diameter of ball hole (3 holes)	Gage
4. Minor diameter of ball hole (3 holes)	Gage
5. Diameter of striker	Gage
MAJOR	
101. Concentricity of small internal diameter with external datum diameter	Gage
102. Concentricity of striker with external datum diameter	Gage
103. Concentricity of large diameter of ball hole (3 holes) with small diameter of ball hole (3 holes)	Gage
104. Concentricity of large internal diameter with external datum diameter	Gage
105. Concentricity of body with external datum diameter	Gage
106. True position of air hole (2 holes) with small internal diameter	Gage
107. Perpendicularity of face of body (striker end) with axis of external datum diameter	Gage
108. Diameter of body, min.	Gage
109. Diameter of large internal diameter	Gage
110. Diameter of small internal diameter	Gage
111. External datum diameter, min.	Gage
112. Major diameter of ball hole (3 holes)	Gage
113. Minor diameter of ball hole (3 holes)	Gage
114. Diameter of air holes (2 holes)	Gage
115. Radial profile of striker	Gage
116. Length of striker head	Gage
117. Length of striker body	Gage
118. Angle surface of striker shoulder	Measure
119. Width of forward body chamfer	Measure
120. Width of bearing surface lands (3 lands), min.	Measure
121. Width of chamfer on bearing surface land (3 lands)	Gage
122. Width of rear body chamfer	Gage
123. Depth of large bore	Gage
124. Location of ball (3 holes) to face of body (large internal diameter end), min.	Gage
125. Location of small internal diameter to face of body (large internal diameter end)	Gage

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the currentversion before use.

4.3.2.7 (Cont'd)

Defect	Method of Inspection
126. Total length	Gage
127. Angular location of ball hole (3 holes) on body, min.	Measure
128. Ball (3 balls) flush (within specified tolerance) with bearing surface lands	Gage
129. Diameter of ball (3 balls), min.	Gage
130. Radius and chamfer missing or incorrect	Visual
131. Surface finish 125 improper, except as otherwise noted	Visual
132. Surface finish improper	Visual
133. Protective finish inadequate or defective	Visual
134. Metal defective	Visual
135. Any parts missing	Visual
136. Burr	Visual
137. Marking missing, incorrect, or illegible	Visual
138. Foreign matter	Visual
MINOR	
None defined	1/

4.3.2.8 Spring, Firing, Drawing C10534139 covering a detail of Dwg. F10534133.

CRITICAL	
None defined	
MAJOR	
101. Diameter of wire	Gage
102. Active coils	Visual
103. Total coils	Visual
104. Load of compressed length (specified)	Measure
105. Ends incorrect	Visual
106. Free length	Gage
107. Outside diameter of spring, min.	Gage
108. Burr or sharp edges	Visual
109. Surface finish improper	Visual
110. Protective finish inadequate or defective	Visual
111. Metal defective	Visual
112. Foreign matter	Visual
MINOR	
None defined	1/

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

4.3.2.9 Stand, Drawing C10534141 covering a detail of Drawing F10534133.

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Total length	Measure
102. Thickness of stand	Measure
103. Width of stand, min.	Gage
104. Diameter of hole (2 holes)	Gage
105. Centerline distance between hole (2 holes)	Measure
106. Location of hole (2 holes) to ends	Measure
107. Location of hole (2 holes) to sides	Measure
108. Surface finish improper	Visual
109. Protective finish inadequate or defective	Visual
110. Metal defective	Visual
111. Foreign matter	Visual
112. Marking missing, incorrect or illegible	Visual
MINOR	
None defined	1/

4.3.2.10 Strap, Drawing C10534142 covering a detail of Drawing F10534133.

CRITICAL	
None defined	
MAJOR	
101. Total length	Measure
102. Thickness	Measure
103. Width, min.	Gage
104. Diameter of hole (2 holes)	Gage
105. Radius of bend	Gage
106. Location of top of bend to end	Measure
107. Centerline distance between holes (2 holes)	Measure
108. Location of top of bend to hole (2 holes)	Measure
109. Height of striaght portion of bend	Measure
110. Location of hole (2 holes) to sides	Measure
111. Radius missing or incorrect	Visual
112. Surface finish improper	Visual

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the current version before use.

4.3.2.10 (Cont'd)

	Defect	Method of Inspection
113.	Protective finish inadequate or defective	Visual
114.	Metal defective	Visual
115.	Marking missing, incorrect or illegible	Visual

MINOR

	None defined	1/

4.3.2.11 Pin, Safety, Drawing C10534140, covering a detail of Dwg. F10534133.

CRITICAL

None defined

MAJOR

101.	Diameter of wire	Measure
102.	Radius of major bend (for safety pin groove of initiator cap)	Gage
103.	Total length	Measure
104.	Inside diameter of head	Measure
105.	Profile incorrect	Visual
106.	Metal defective	Visual
107.	Protective finish inadequate or defective	Measure
108.	Burr or sharp edges	Visual
109.	Foreign matter	Visual

MINOR

	None defined	1/

4.3.2.12 Metal Parts Assembly, Drawing F10534133.

CRITICAL

1.	Improper assembly	Visual
2.	Any part missing	Visual/X-ray
3.	Foreign matter in gas port	Visual

MAJOR

101.	Thread damaged	Visual
102.	Strap and stand insecure	Visual
103.	Initiator pin not free to rotate	Manual
104.	Safety pin loose or deformed	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the currentversion before use.

4.3.2.12 (Cont'd)

Defect	Method of Inspection
105. Marking missing, incorrect or illegible	Visual
106. Burr	Visual
107. Foreign matter	Visual

MINOR

None defined	1/

1/ All other drawing dimensions and requirements not listed as "Critical or Major Defects", shall be inspected for as Minor Defects by the supplier, using the sampling plans in Tables I and II.

4.3.2.13 Container, Fiber Drawing C8796726.

CRITICAL

None defined

MAJOR

None defined

MINOR

201. Gap between body and cover, max.	Manual
202. Contents loose	Manual
203. Metal ends loose or distorted	Manual
204. Cut or damaged through all impregnated layers	Visual
205. Initiator improperly packed	Visual
206. Marking missing, incorrect or illegible	Visual
207. Adhesives improperly applied	Visual
208. Tape incomplete or badly wrinkled	Visual
209. Length of tear tab, min.	Visual
210. Color of tape incorrect	Visual

4.3.2.14 Box, Packing, Drawing C8796707.

CRITICAL

None defined

MAJOR

None defined

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the currentversion before use.

4.3.2.14 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Contents loose	Manual
202. Hardware missing, loose, broken or improperly engaged	Visual/Manual
203. Contents improperly packed	Visual
204. Box damaged	Visual
205. Contents of box exposed	Visual
206. Strapping missing, loose, broken or improperly assembled	Visual/Manual
207. Marking missing, incorrect or illegible	Visual
208. Number of units incorrect	Visual
209. Car seal missing, unsealed or improperly positioned	Visual

4.3.2.15 Carton, Alternative Packing, Drawing C9241015.

CRITICAL

None defined

MAJOR

None defined

MINOR

201. Contents loose	Manual
202. Carton broken or damaged	Visual
203. Number of units contained incorrect	Visual
204. Marking missing, incorrect or illegible	Visual
205. Tape incorrect	Visual

4.4 Test Methods and Procedures.

4.4.1 Hardness.-Prior to the application of protective finish, ten (10) units from each heat-treated lot of components shall be tested by a hardness tester for compliance with the requirements specified on the applicable drawing. Failure of any unit to comply with the drawing requirements shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

4.4.2 Hydrostatic pressure.-Prior to application of protective finish, the cap and chamber shall be mounted in the device, using the fixture for properly sealing all openings and shall be subjected to the internal hydrostatic pressure test to determine compliance with the requirements of 3.3. Failure of any subassembly to comply shall be cause for rejection of the subassembly.

4.4.3 Firing pin release.-The initiator pin of each subassembly shall be subjected to the firing pin release test. The subassembly shall be secured in the fixture and a pull shall be applied to the initiator pin in the longitudinal direction in conjunction with the device to register the amount of pull. Failure of any subassembly to comply with the requirements of 3.4 shall be cause for rejection of the subassembly.

4.4.4 Initiator pin security.-The initiator pin of each subassembly shall be subjected to the initiator pin security test. The subassembly shall be secured in the fixture with safety pin in place and a pull shall be applied to the initiator pin in the longitudinal direction in conjunction with the fixture to register the amount of pull. The test shall be performed with the safety pin in each position. Failure of any subassembly to comply with the requirements of 3.5 shall be cause for rejection of the subassembly.

4.4.5 Protective finish.-Test procedures, number of specimens and acceptance criteria for protective finish shall be in accordance with the applicable Military Standard referenced on the component drawing.

4.4.6 Residual magnetism.-Each assembly shall be subjected to the test for excessive residual magnetism. The test shall be conducted in an area free of local magnetic effects by placing the assembly 6 inches from and at the same height as the compass in a north-south horizontal position (cap end at south) with the compass set in an east-west heading. The assembly shall be moved slowly past the compass in a longitudinal direction for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the assembly. Failure of any assembly to comply with the requirements of 3.8 shall be cause for rejection of the assembly.

4.4.7 Inspection equipment.-The examination and test shall be made using equipment listed on IEL 10534133.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.-Packing and marking shall be as specified by the procuring activity: Level A - Drawings C8796707 and C8796726, Level B - Drawings C8796726 and C9261015.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:02Z
Check the source to verify that this is the currentversion before use.

6. NOTES

6.1 Ordering data.-Procurement documents should specify the title, number, and date of this specification.

6.2 Mechanical failure is defined as any deformation or breakage of a part, the occurence of which is other than a design function.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A563

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Frankford Arsenal
ATTN: SARFA-MDM
Philadelphia, Penna. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-I-50362(MU) Initiator, Cartridge Actuated, M8, Metal Parts Assembly

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:02Z
Check the source to verify that this is the current version before use.