NOT MEASUREMENT SENSITIVE


MIL-M-3946/66
26 February 1992

MILITARY SPECIFICATION SHEET

MEDAL, KUWAIT LIBERATION, KINGDOM OF SAUDI ARABIA

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-M-3946



DEVICE — BASE - OBVERSE WITH DEVICE ATTACHED — BASE - REVERSE

MATERIAL: Red brass

DASH NO:
-1: Regular size
-2: Miniature size

DIMENSIONS:
BASE:
DIAMETER:
-1: 1 25/32 inches (4.52 cm)
-2: 7/8 inch (2.22 cm) (REF)
THICKNESS:
-1: .095 ± .005 inch (0.241 ± 0.012 cm)
-2: .060 ± .005 inch (0.152 ± 0.012 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:42Z
Check the source to verify that this is the current version before use.

DEVICE:

HEIGHT (at highest point):
-1: 1 27/32 inches (4.68 cm)
-2: 29/32 inch (2.30 cm) (REF)

WIDTH (At widest point):
-1: 1 1/4 inch (3.18 cm)
-2: 5/8 inch (1.59 cm)(REF)

THICKNESS:
-1: .050 ± .005 inch (0.127 ± 0.012 cm)
-2: .025 ± .005 inch (0.063 ± 0.012 cm)

DAPPING: The base and device shall be dapped as indicated on the horizontal plane.
-1: 1/8 inch ± 1/32 inch (0.32 ± 0.08 cm)
-2: 1/16 inch ± 1/32 inch (0.16 ± 0.08 cm)

FINISH:

BASE:

OBVERSE: Nickel plated, mirror-like polished (the center of the base with the outline of Kuwait is gold plated, mirror-like polished).

REVERSE: Stippled, nickel plated, matte finish (Stipple is not required in the center forced area).

DEVICE: Gold plated, matte finish.

NOTES:

1. A forcer shall be used to bring up the design of the globe.

2. The device shall be pierced as indicated.

3. The device shall be riveted or soft soldered to the base in the location shown.

4. The lug shall be riveted or hard soldered to the base in the area indicated.

5. The ribbon for the pendant drape and service ribbon shall conform to MIL-R-11589/365.

6. The ribbon attachment for the service ribbon shall conform to MIL-R-41819/39.

7. Government furnished hubs for the regular size medal are not available; however, ribbon for the pendant drape shall conform to MIL-R-11859/365. Pendant ribbon length of the regular size medal shall be adjusted so the overall length (including pendant) is 3-11/16 inches ± 1/32 inch (9.37 cm ± .08 cm).

Custodian:
Army - IH
Air Force - 11
Navy - NU

Review activities:
Air Force - 82,99
Navy - MC, CG
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0647)

Source: https://assist.dla.mil -- Downloaded: 202610-17T02:42Z
Check the source to verify that this is the current version before use.