MIL-C-11009B(MU)
10 June 1968
SUPERSEDING
MIL-C-11009A(ORD)
29 June 1953

MILITARY SPECIFICATION
CLIP, CARTRIDGE, CARBINE, CALIBER .30

1. SCOPE

1.1 This specification covers one type and one class of assembled 10-round Carbine Cartridge Clip suitable for loading cartridges into 30-round magazines of Caliber .30 Carbines, M1, M1A1, M2 and M3.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal
PPP-B-636 - Boxes, Fiberboard

STANDARDS

Federal
Federal Test Method Standard No. 151 - Metals; Test Methods

Military
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-171 - Finishing of Metal and Wood Surfaces

DRAWINGS

Munitions Command
C7553187 - Clip, Cartridge, Carbine Cal. .30 Assembly
IEL-7553187 - Inspection Equipment List for Clip, Cartridge, Carbine, Cal. .30 Assembly

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:52Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- The cartridge clips and parts shall conform to the materials, configuration and design requirements specified on Drawing C7553187, the referenced specifications and as specified herein.

3.2 Details.

3.2.1 Spring.- The spring shall be capable of being readily assembled to and disassembled from the body. When assembled, the spring shall be retained in the body by engagement of its detents in the spring retaining holes of the body.

3.2.2 Body and shoe.- The body shall be capable of readily fitting the shoe and the force required to slide the body within the shoe to the full limit of its travel shall be not less than 1/8 pound nor greater than 8 pounds.

3.2.3 Spring tab bend strength.- The cartridge retaining tab of the spring shall be capable of a minimum of 2 complete 90° bends over a radius of .010, plus .005 minus .000 without evidence of cracks. The bend should be made at the root of tab and toward the channel opening.

3.2.4 Cartridge stipping force.- The force required to remove all the cartridges from the clip with a bent tab shall be not less than 1 pound nor greater than 10 pounds.

3.3 Protective finish.- The steel parts of the clip shall have the protective finish and final supplementary coating of rust inhibitor specified on the drawing and referenced specifications. The coated clips shall withstand 16 hours exposure to a 5% salt spray.

3.4 Marking.- Each clip shall be clearly marked in accordance with applicable drawing.

3.5 Workmanship.- The requirements for workmanship are as specified in the applicable drawings, referenced specifications and the following:

3.5.1 Metal defects.- The clips shall be free of folds, wrinkles, scaly metal and burrs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:52Z
Check the source to verify that this is the current version before use.

3.5.2 Foreign matter.- The clips shall be free of corrosion, stains, discolorations, dirt or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 for definition of quality assurance terms.

4.2 First article sample.

4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 300 assembled cartridge clips. The sample shall be manufactured using the same materials, equipment, processes and procedures as will be used in regular production. All parts and materials shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and test.- After inspection and provisional acceptance at source, the initial production sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Initial production sample failure.- Failure of sample to comply with requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Lot.

4.3.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:52Z
Check the source to verify that this is the current version before use.

4.3.2 Examination.- Examination for Major and Minor defects for visual inspection, gaging and slide test shall be performed on a class basis in accordance with the classification of defects, Table I, using applicable sampling plans and acceptance criteria of MIL-STD-105. The acceptable quality level (AQL) for the major class shall be 1.50 percent and the AQL for the minor class shall be 2.50 percent.

4.3.2.1 Classification of defects.- The classification of defects shall be as specified in Table I.

TABLE I

No.	Defect	Major	Minor
	Visual		
1.	Missing spring tab	X	
2.	Improper assembly (incorrect number of components, spring improperly seated, body tabs not bent sufficiently to hold body in shoe)	X	
3.	Excessive oil film 1/	X	
4.	Splits, tears, dents, scratches 2/		X
	Gaging		
5.	Inside width of body slot (.300 + .015")	X	
6.	Overall height of shoe (.318 - .012")	X	
7.	Inside width of shoe max. (708")	X	
8.	Inside width of shoe min. (.676")		X
	Slide Test		
9.	Excessively tight (requiring more than 8 pounds pull)	X	
10.	Excessively loose (requiring less than 1/8 pound pull)		X

1/ No oil permitted on inside of body or exposed surface of spring (assembled clip).

2/ Dents or scratches showing exposed steel.

NOTE: Clips not damaged in the sampling and inspection operations and which are in accordance with the detailed requirements may be included in the lot from which selected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:52Z
Check the source to verify that this is the current version before use.

4.3.3 Tests.- The tests listed in Table II shall be conducted in accordance with the methods and procedures specified in 4.4.

4.3.3.1 Test samples.- The quantities for the various tests shall be as specified in Table II. Only cartridge clips having met the visual and dimensional requirements shall be used in the tests and shall have been selected in such manner that the sample is representative of the entire lot. The cartridge clips selected shall be thoroughly mixed before being divided into samples for the various tests.

TABLE II

Tests	Number of Cartridge Clips	Requirement Paragraph
Spring Tab Bend Test 1/	50	3.2.3
Cartridge Stripping Test 2/	50	3.2.4
Salt Spray Test 2/	20	3.3

1/ Failure of 4 or more clips to comply with the applicable requirements shall be cause for rejection of the lot. If more than one, but less than four clips fail the first test, a second sample consisting of double the number of clips in the first sample shall be tested. The lot shall be rejected if in the combined first and second sample, four or more clips fail to comply with the applicable requirement.

2/ Failure of two or more clips to comply with the applicable requirement shall be cause for rejection of the lot. If one clip fails in the first test, a second sample consisting of double the number of clips in the first sample shall be tested. If any failing clips are found in the second sample, the lot shall be rejected.

4.4 Test methods and procedures.

4.4.1 Protective finish test.- Clips shall be tested in accordance with Federal Test Method Standard No. 151 - Metals; Test Methods. After the clips or clip components have been given the final supplementary finish, the coated clips shall withstand 16 hours exposure to a 5% salt spray.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:52Z
Check the source to verify that this is the current version before use.

4.4.2 Spring tab bend test.- The tab of the assembled clip shall be bent, straightened and bent again. The bend should be made at the root of the tab and toward the channel of opening. The test shall be by or in a device approved by the procuring agency.

4.4.3 Cartridge stripping test.- The pull force shall be applied at the lowest exposed point of the cartridge. This test shall be made in a device approved by the procuring agency.

4.4.4 Slide test.- The slide test shall be made in a device approved by the procuring agency. The clip shall be opened and closed once manually prior to subjection to this test.

5. PREPARATION FOR DELIVERY

5.1 Packing.- Packing shall be "Level C". The clips shall be packed in bulk, 2000 units (approximately 70 pounds) in a corrugated fiberboard box, 350 pound test, conforming to style RSC of Specification PPP-B-636. The contents shall be immobilized to prevent damage from shifting and the pack shall be acceptable for shipment by common carrier.

5.2 Marking.- Each box shall be marked with the clip manufacturer's name, lot number and date of manufacture. Shipments shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Ordering data.- Invitations for bids and contracts or orders will specify the following:

6.1.1 Title, number and date of this specification.

6.1.2 Requirements for contractor to provide and maintain an inspection system in accordance with MIL-I-45208, Inspection System Requirements.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1305-A446

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:52Z
Check the source to verify that this is the current version before use.