INCH-POUND
MIL-C-11015/2E
25 October 2021
SUPERSEDING
MIL-C-11015/2D
14 May 2001


MILITARY SPECIFICATION SHEET

CAPACITOR, FIXED, CERAMIC DIELECTRIC (GENERAL PURPOSE), STYLE CK22

INACTIVE FOR NEW DESIGN.
FOR REPLACEMENT PURPOSES ONLY

This specification sheet is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-C-11015.



Inches	mm
.001	0.03
.004	0.10
.025	0.64
.030	0.76
.060	1.52
.225	5.72
.250	6.35
.430	10.92
1.250	31.75

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are in millimeters and are given for general information only.
3. Insulating coating shall not extend more than .125 inch (3.18 mm) along lead wires measured from body of capacitor.
4. The beginning of the part or identifying number (PIN) shall be adjacent to the end having the inner-electrode terminal.

FIGURE 1. Dimensions and configuration.

AMSC N/A
FSC 5910

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:53Z
Check the source to verify that this is the current version before use.

TABLE I. Style CK22 characteristics.

PIN 1/	Rated voltage (V_{dc})	Rated temperature and voltage-temperature limits	Capacitance (pF)	Capacitance tolerance
CK22AX120K	500	AX	12	K
CK22AX150K	500	AX	15	K
CK22AX180K	500	AX	18	K
CK22AX220K	500	AX	22	K
CK22AX270K	500	AX	27	K
CK22AX330K	500	AX	33	K
CK22AX390K	500	AX	39	K
CK22AX470K	500	AX	47	K
CK22AX560K	500	AX	56	K
CK22AX680-	500	AX	68	K, M
CK22AX820K	500	AX	82	K
CK22AX101-	500	AX	100	K, M
CK22AX121K	500	AX	120	K
CK22AX151-	500	AX	150	K, M
CK22AX181K	500	AX	180	K
CK22AX221-	500	AX	220	K, M
CK22AX271K	500	AX	270	K
CK22AX331-	500	AX	330	K, M
CK22AX391K	500	AX	390	K
CK22AX471-	500	AX	470	K, M
CK22AX561K	500	AX	560	K
CK22AX681-	500	AX	680	K, M

1/ Where applicable, the complete PIN will include an additional symbol to indicate capacitance tolerance.

REQUIREMENTS

Dimensions and configuration: See figure 1.

Case type: Tubular with radial leads.

Capacitance value: See table I.

Capacitance tolerance: ± 10 percent (K) or ± 20 percent (M) as shown in table I.

Rated temperature: -55°C to +85°C.

Dielectric withstanding voltage: In accordance with MIL-C-11015.

Dielectric:

Test voltage: 250 percent of rated voltage.

Body insulation: Shall be able to withstand 1,300 volts for 5 ± 1 seconds between leads and a V-block which shall extend beyond the ends of the capacitor body.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:53Z
Check the source to verify that this is the current version before use.

Barometric pressure (reduced): In accordance with MIL-C-11015 and MIL-STD-202-105, 0.82 inch of mercury (80,000 ft).

Test potential: 150 percent of rated voltage.

Insulation resistance (IR): In accordance with MIL-C-11015 and MIL-STD-202-302, condition B. 20,000 megohms, minimum.

Dissipation factor (DF): 1.5 percent, maximum.

Shock, specified pulse: Not applicable.

Vibration, high frequency: In accordance with MIL-C-11015 and MIL-STD-202-204, condition B (15 g's).

Thermal shock and immersion: In accordance with MIL-C-11015.

IR: 3,000 megohms, minimum.

Salt atmosphere (corrosion): Not applicable.

Terminal strength: In accordance with MIL-C-11015.

Moisture resistance: In accordance with MIL-C-11015.

IR: 3,000 megohms, minimum.

Solderability: In accordance with MIL-C-11015; 2 terminals.

Resistance to soldering heat: Not applicable.

Voltage-temperature limits: In accordance with MIL-C-11015.

Life (at elevated ambient temperature): In accordance with MIL-C-11015.

Test potential: 200 percent of rated voltage.

IR: 500 megohms, minimum (at +85°C); 10,000 megohms, minimum (at +25°C).

DF: 3 percent, maximum (at +25°C).

Marking: In accordance with MIL-C-11015.

Referenced documents: In addition to MIL-C-11015, this document references the following:

MIL-STD-202-105
MIL-STD-202-204
MIL-STD-202-302

Changes from previous issue: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:53Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5910-2021-025)

Review activities:
Army - MI
Navy - MC
Air Force – 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:53Z
Check the source to verify that this is the current version before use.