INCH-POUND

MIL-DTL-10986G
SUPPLEMENT 1
19 November 2007

DETAIL SPECIFICATION

INDICATORS AND TRANSMITTERS: LIQUID, TEMPERATURE AND PRESSURE

Inactive for new design after 22 January 1992.

This supplement forms a part of MIL-DTL-10986G, dated 19 November 2007.

SPECIFICATION SHEETS

MS24537 - Transmitter, Temperature Electrical Resistance - 24 Volt DC.
MS24538 - Transmitter, Pressure - 24 Volt DC 60 PSI.
MS24539 - Transmitter, Pressure - 24 Volt DC 120 PSI.
MS24540 - Indicator, Pressure 24 Volt, DC, Range 0-120 PSI.
MS24541 - Indicator, Pressure: 24 Volt, DC, Range 0-60 PSI.
MS24542 - Indicator, Temperature, Electrical Resistance: 24 Volt DC, Range 160 - 320 °F.
MS24543 - Indicator, Temperature, Electrical Resistance: 24 Volt DC, Range 120° - 240 °F.
MS24544 - Indicator, Liquid Quantity: 24 Volt DC, Engine Fuel.
MS500040 - Transmitter, Liquid Quantity, Float Type, Engine Fuel.

Custodians:
Army - AT
Navy - YD

Preparing Activity:
DLA - GS1

Review Activities:
Army - CR, CR4
Navy - MC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:51Z
Check the source to verify that this is the current version before use.