NOT MEASUREMENT SENSITIVE

MIL-I-11132/42
20 February 1992

MILITARY SPECIFICATION SHEET

INSIGNIA, RANK; CADET, OFFICERS, SROTC, FATIQUE, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-I-11132

-1
COLONEL

-2
LIEUTENANT COLONEL

-3
MAJOR

-4
CAPTAIN

-5
1st LIEUTENANT



-6
2d LIEUTENANT

Dash Number
-1: Colonel
-2: Lieutenant Colonel
-3: Major
-4: Captain
-5: First Lieutenant
-6: Second Lieutenant

MATERIAL: Gilding metal

DIMENSIONS:
HEIGHT: 1 inch ± 1/64 inch (2.54 cm ± 0.04 cm)(REF)
WIDTH: 1 inch ± 1/64 inch (2.54 cm ± 0.04 cm)(REF)
THICKNESS (At thickest point): .070 inch ± .005 inch (0.177 cm ± 0.014 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:23Z
Check the source to verify that this is the current version before use.

FINISH: Hard Enamel, Nickel Plated, Mirror-like Polished

NOTES:

1. Enameled areas shall be as indicated. The enamel colors shall match the TIOH color chip listed below:

COLOR	CHIP NUMBER
Black	26

2. Attaching device shall be prong and clutch type. Two prongs shall be attached on the horizontal center line of the reverse side, 3/16 inch ± 1/64 inch (0.12 cm ± 0.04) from each side.

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of manufacturer. Epoxy resin shall be a stoning epoxy, have a shore D hardness of 85, and incorporate an ultraviolet inhibitor.

Custodians:
Army - IH
Air Force - 11

Review activities:
Air Force - 82, 99
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0641)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:23Z
Check the source to verify that this is the current version before use.