NOT MEASUREMENT SENSITIVE

MIL-DTL-11132/46
6 June 1997
SUPERSEDING
MIL-B-14632/5C
12 January 1995

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, AVIATION, FLIGHT TRAINING GRADUATE, ROTC, ARMY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11132 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL: Red Brass or Nickel Silver

FINISH: Nickel Plated (Red Brass Only), Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

DIMENSIONS:
HEIGHT (Overall): 23/32 inch (1.83 cm) (REF)
WIDTH (Overall): 2-1/2 inches (6.35 cm) (REF)
THICKNESS (At Thickest Point): 0.105 inch ± 0.005 inch (0.266 ± 0.012 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Attaching device shall be prong and clutch type. Prongs shall be located on the horizontal line passing through the center of the circle,

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:24Z
Check the source to verify that this is the current version before use.

equidistant from each end and 2 inches ± 1/32 inch (5.08 cm ± 0.08 cm) apart.

3. A mock forcer may be made used to bring up the design on the circle portion only.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0895)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:24Z
Check the source to verify that this is the current version before use.