NOT MEASUREMENT SENSITIVE

MIL-DTL-11132/49A
22 July 1997
SUPERSEDING
MIL-DTL-11132/49
6 June 1997

DETAIL SPECIFICATION SHEET

BADGE, QUALIFICATION, MISSILEMAN, ROTC, AIR FORCE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-11132 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

MATERIAL: Red Brass or Nickel Silver

FINISH: Nickel Plated (Red Brass Only), Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

DIMENSIONS:
HEIGHT: 2 inches (5.08 cm) (REF)
WIDTH: 21/32 inch (1.67 cm) (REF)
THICKNESS (On Missile): 0.085 inch ± 0.005 inch (0.215 cm ± 0.012 cm)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:25Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The attaching device shall be prong and clutch type. Two prongs shall be located on the vertical center line, equidistant from each end and 1-5/8 inch ± 1/32 inch (4.13 cm ± 0.08 cm) apart.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH
Air Force - 45

Preparing activity:
Army - IH

Review activities:
Air Force - 32, 82, 99
DLA - CT

(Project No. 8455-0900)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:25Z
Check the source to verify that this is the current version before use.