INCH-POUND

MIL-DTL-3943/200A
21 April 2006
SUPERSEDING
MIL-DTL-3943/200
30 June 1997

DETAIL SPECIFICATION SHEET

MEDAL, ARMY RESERVE COMPONENTS ACHIEVEMENT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943.

OBVERSE

-2, -4

-1, -3

REVERSE

DASH NO.
-1: Army Reserve, Regular Size
-2: Army National Guard, Regular Size
-3: Army Reserve, Miniature Size
-4: Army National Guard, Miniature Size

MATERIAL: Red Brass
FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH metal finish chip Number 4.

DIMENSIONS:
DIAMETER:
-1, -2: 1-1/4 inches (3.18 cm) (REF)
-3, -4: 5/8 inch (1.59 cm) (REF)

THICKNESS (At Outer Wreath Between Star Points):
-1, -2: 0.115 inch $\pm$ 0.010 inch (0.292 cm $\pm$ 0.025 cm)
-3, -4: 0.075 inch $\pm$ 0.010 inch (0.191 cm $\pm$ 0.025 cm)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:26Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The ribbon for the pendant drape shall conform to MIL-DTL-11589/196.

3. The lapel button shall conform to MIL-DTL-11484/101.

4. The obverse design is identical for all medals. Only the design on the reverses vary.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No.8455-2006-029)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:26Z
Check the source to verify that this is the current version before use.