NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/205D(NU)
20 May 2026
SUPERSEDING
MIL-DTL-3943/205C(NU)
14 May 2021

DETAIL SPECIFICATION SHEET

MEDAL, GOOD CONDUCT, U.S. NAVY

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

DASH NO.
-1: Regular Size
- 2: Miniature Size

MATERIAL (-1 and -2): Red Brass 85/15 (UNS Alloy No. C-230)

FINISH (-1 and -2): Brass, Oxidized, Buffed Relieved and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 4.

DIMENSIONS:
DIAMETER:
-1: 1-1/4 inches (REF)
-2: 5/8 inches (REF)
THICKNESS (At rim):

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:27Z
Check the source to verify that this is the current version before use.

-1: 0.105 inch ± 0.010 inch
-2: 0.080 inch ± 0.005 inch

DECORATION SET: Decoration set presentation case shall be as specified by the procuring agency.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon for the pendant drape is MIL-DTL-11589/70.

3. For commercial sale only may be manufactured using 24K Gold Plate Mirror-like Polished and shall match TIOH Metal Finish Chip Number 6.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Navy - NU

Preparing activity:
Navy - NU

Review activity:
DLA - CT

(Project No. 8455-2026-282)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:27Z
Check the source to verify that this is the current version before use.