MIL-A-18889(NOrd)

30 June 1955

SUPERSEDING
NAVORD OS 1215
9 January 1941
NAVORD OS 1403
5 April 1943

MILITARY SPECIFICATION

ARBOR, DEPTH CHARGE, MK 7 MOD 3

1. SCOPE

1.1 This specification governs the manufacture, assembly, and preparation for delivery of the Depth Charge Arbor Mk 7 Mod 3 and the methods of inspection and tests upon which acceptance will be based.

2. APPLICABLE DOCUMENTS

2.1 The following drawings and publications, of the issue in effect on date of invitation for bids, form a part of this specification:

STANDARDS

MIL-STD-105 -- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 -- Marking for Shipments and Storage.

DRAWINGS

BUREAU OF ORDNANCE

LD SK 109607 -- Depth Charge Arbor Mk 7 Mod 3, and all specifications, standards, drawings, and publications listed thereon.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:04Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

BUREAU OF ORDNANCE

OP 400 -- General Instructions for the Design, Manufacture, and Inspection of Naval Ordnance Equipment.

(Copies of specifications, drawings and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity, or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.

3.1.1 The depth charge arbor covered by this specification shall be manufactured in accordance with LD SK 109607 and all documents listed thereon.

3.1.2 The requirements and procedures established in OP 400 shall be adhered to wherever applicable.

3.2 Stem, drawing 375996, piece 4. -- After final assembly the machine finished portion of the stem shall be straight within .010 inch throughout its finished length.

4. QUALITY ASSURANCE PROVISIONS AND TEST REQUIREMENTS.

4.1 Sampling. -- Unless otherwise specified, and when applicable, the sampling plans and procedures used by the Government Inspector in the determination of the acceptability of products submitted by a supplier for government inspection will be in accordance with the provisions of MIL-STD-105.

4.1.1 Lot. -- As applied to the government inspection of units of product, the term "lot" shall mean "inspection lot", i.e. a collection of units of the product used as a basis for government inspection. Unless otherwise specified, the number of units of product in "inspection lots" shall be as determined by the government inspector, and may differ from the quantity designated in the contract or order as a lot for production, shipment, or other purpose.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:04Z
Check the source to verify that this is the current version before use.

4.1.2 Sampling for tests. -- Five samples from each lot of fifty arbors shall be subjected to the tests as specified in 4.4 with lot disposition determined in accordance with MIL-STD-105, code letter "C", AQL 4.0%.

4.2 Preproduction sample. -- Before entering into quantity production, a preproduction sample of five (5) complete depth charge arbors shall be delivered by the contractor for test to an agency designated by the procuring agency. This depth charge arbor shall be manufactured by the same procedures and processes and at the same location proposed by the contractor for the execution of the contract. When a preproduction sample is received which proves to be satisfactory for the purpose intended, the contractor will be notified and will be authorized by the procuring agency to proceed with the submission of the product for acceptance. Accepted samples will become the property of the procuring agency and will be included in the number called for in the contract schedule.

4.2.1 Preproduction sample for a subsequent contract. -- The necessity for a preproduction sample will be determined by the procuring agency when production under a new contract by the same contractor at the same location follows the manufacture of satisfactory material as covered by this specification.

4.3 Inspection. -- The general inspection procedures shall be in accordance with General Instructions for the Design, Manufacture, and Inspection of Naval Ordnance Equipment, OP 400; government inspection shall be in accordance with the provisions of General Procedure for Government Inspection and contractor's inspection shall be in accordance with Inspection by Contractor, as contained in OP 400.

4.4 Tests. -- Each arbor to be tested shall be subjected to the following tests.

4.4.1 Support the arbor in a bearing having a diameter of 6.0 and a length of at least 25 inches, so that the arbor stem and the long axis of the tray will each be horizontal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:04Z
Check the source to verify that this is the current version before use.

4.4.2 Attach a dummy weighted depth charge (having a total weight of approximately 420 pounds) to the arbor tray by means of the securing mechanism. Tighten the rope by turning up the securing nut as far as possible without using a wrench.

4.4.3 Apply to the dummy depth charge an additional weight or force of 500 pounds acting vertically downward through the center of the charge.

4.4.4 Under either of the loadings specified above, no part or welded joint of the arbor assembly shall show indication of excessive or destructive deformation.

4.4.5 After relief of the 500 pound additional weight record the force required to operate the release mechanism by giving a pull, parallel to the arbor stem, on the release chain. The release shall operate by a pull of not less than 200 pounds or not more than 800 pounds.

4.4.6 Remove the release rope from the arbor and apply a force equivalent to a 3200 pound weight hanging from the rope eyelet with the other end secured by the threaded terminal. Neither the rope nor the swaged fittings shall show indication of excessive or destructive deformation.

5. PREPARATION FOR DELIVERY

5.1 Packaging and packing. -- Each Depth Charge Arbor Mk 7 Mod 3 is to be packaged and packed for shipment as specified on Drawing 440289.

5.2 Marking. -- In addition to any special marking required by the contract or order, each container shall be marked in accordance with MIL-STD-129, "Marking for Shipments and Storage."

6. NOTES

6.1 The Depth Charge Arbor Mk 7 Mod 3 is used with Depth Charges Mk 6, Mk 8, Mk 9 Mods 0, 1, 2 and 3 and The British Depth Charge Mk 7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:04Z
Check the source to verify that this is the current version before use.

Patent Notice. -- When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any otherperson or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:04Z
Check the source to verify that this is the current version before use.