MIL-R-18967C(YD)
20 December 1982
SUPERSEDING
MIL-R-18967B(YD)
4 November 1976

MILITARY SPECIFICATION

RANGES, OIL BURNING (SUITABLE FOR USE WITH KEROSENE, DIESEL FUEL, AND NO. 2 FUEL OIL)

This specification is approved for use by the Naval Facilities Engineering Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers kerosene and oil fired, single or double oven, heavy-duty ranges equipped with a cooking top suitable for grilling, frying, and normal range top cooking.

1.2 Classification. Ranges shall be of the following types as specified (see 6.2).

Type I - Single oven.
Type II - Double oven.

2. APPLICABLE DOCUMENTS

2.1 Government documents

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

VV-F-800 - Fuel Oil, Diesel.
VV-F-815 - Fuel Oil, Burner.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commanding Officer (Code 156), Naval Construction Battalion Center, Port Hueneme, CA 93043, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 7310

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:09Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-V-173 - Varnish, Moisture-and-Fungus Resistant (For Treatment of Communications, Electronic, and Associated Equipment).
MIL-T-5624 - Turbine Fuel, Aviation, Grades JP-4 and JP-5.
MIL-R-11337 - Ranges, Packaging and Packing of.
MIL-T-13867 - Treatment, Moisture-and-Fungus Resistant for Fire Control, Electrical, and Electronic Instruments and Equipment.
MIL-I-24092 - Insulating Varnish, Electrical, Impregnating Solvent Containing.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-461 - Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference.
MIL-STD-462 - Electromagnetic Interference Characteristics, Measurements of.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents that are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA):

ICS - 1 - General Standards for Industrial Controls and Systems.
ICS - 2 - Industrial Control Devices, Controllers and Assemblies.
ICS - 6 - Enclosures for Industrial Controls and Systems.
MG - 1 - Motors and Generators.

(Application for copies should be addressed to the National Electrical Manufacturers Association, 2101 L Street, NW, Washington, DC 20037.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

No. 70 - National Electrical Code.

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.)

Source: https://assist.dla.mil -- Downloaded: 202610-18T12:09Z
Check the source to verify that this is the currenversion before use.

SOCIETY OF AUTOMOTIVE ENGINEERS, INC. (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 400 Commonwealth Drive, Warrendale, PA 15096.)

UNDERWRITER'S LABORATORIES, INC., (UL)

Gas and Oil Equipment List.
UL296 - Oil Burners.
UL372 - Primary Safety Controls.
UL873 - Temperature - Indicating and Regulating Equipment.

(Application for copies should be addressed to Underwriter's Laboratories, Inc., 333 Pfingsten Road, Northbrook, IL 60062.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. Ranges shall be of the type specified in 1.2 and shall be equipped with burners that meet the requirements of the safety standard specified in 3.6. The range shall include necessary controls, cooking top, insulation, and piping connections to be readily assembled for operation with the specified fuels and electrical supply. The burner ignition shall be automatic. Fuel shall be gravity-fed to the burner. The range burner shall be equipped to operate with the following fuels:

Kerosene - ASTM D 3699
Diesel - VV-F-800, grade DF-2
Distillate - VV-F-815, grade No. 2; ASTM D396, grade No. 2; and MIL-T-5624, JP-5

3.2 First article. When specified (see 6.2), the contractor shall furnish an oil burning range for first article inspection and approval (see 4.2.1 and 6.4).

3.3 Standard commercial product. The oil burning range shall, as a minimum, be in accordance with the requirements of this specification and shall be the manufacturer's standard commercial product. Additional or better features that are not specifically prohibited by this specification but that are a part of the manufacturer's standard commercial product, shall be included in the equipment being furnished. A standard commercial product is a product that has been sold or is being currently offered for sale on the commercial market through advertisements or manufacturer's catalogs, or brochures, and represents the latest production model.

Source: https://assist.dla.mil -- Downloaded: 202640-18T12:09Z
Check the source to verify that this is the currentversion before use.

3.4 used shall be free from defects that would adverse ce or maintainability of individual components or ove s not specified herein shall be of the same qualit purpose in commercial practice. Unless otherwi l equipment, material, and articles incorporated in the ecification are to be new and fabricated using materi red materials to the maximum extent possible withou ded use. The term "recovered materials" means materi cted or recovered from solid waste and repro- cessed aw materials, as opposed to virgin raw materials. None o erpreted to mean that the use of used or rebuilt produc s specification unless otherwise specified.

3.5 11 units of the same classification furnished with specific contract shall be identical to the extent erchangeability of component parts, assemblies, access

3.6 oil burning ranges under this specification shall the following codes and standards to the extent specif hall conform to the applicable requirements of UL296. automatic ignition, automatic air-flow switch, solenoi flow upon failure of electric service with manual burners shall not be permitted.

3.7 L296. Prior to approval of the first article sample r prior to approval of the first shipment by the contra is not specified, the contractor shall submit to the his authorized representative, satisfactory eviden roposes to furnish under this specification meet the re ceptable evidence of meeting the requirements of UL296 's Laboratory certification symbol or label, a listing Equipment list or a certified test report from a recogn laboratory indicating that the burner has been tested Such evidence shall be acceptable to the contra

3.8 all be such as to prevent conditions hazardous to per equipment as indicated herein. The range shall be des y and shall be easily cleaned. The range shall be des trains and temperature variations encountered in normal de burner flame blowout. The unit shall be access nt of wearing parts.

3.9 cooking top unloaded and the range oven empty, the rang requirements within the fuel consumption rate of tab rature not exceeding 85° Fahrenheit (F). The burner n that 1 gallon of water at lower than ambient or ambi heated to boiling temperature in accordance with td on the cooking top over the burner section of an init oven deck temperature distribution shall not vary mo are operated at the high-fire setting.

reatment
Equip-

Fire
s and

Solvent

by

equire-
ference.

cations
ions

this
nts
ent

al

tection

Source: https://assist.dla.mil -- Downloaded: 202610-18T12:09Z
Check the source to verify that this is the current version before use.

TABLE I. Range characteristics.

	Type I	Type II
Height to range top from floor to cooking surface (inches min)	32	32
*Cooking surface depth (inches min)	25	30
*Cooking surface width (inches min)	48	72
Range width overall (inches max.)	62	100
Range depth (inches max.)	38	40
Oven width inside (inches min)	22	22
Oven height (inches min)	15	15
Oven depth inside (inches min)	23	23
**Range weight lb net	1200	2100
Flue connection diameter (inches min)	8	8 to 10
Oil consumption range (gph) (see 6.1.2)	1/2 to 1-1/2	1/2 to 1-1/2
Shelf loading (psf)	125	125
Oven temperature range °F	200 to 550	200 to 550
Time to boil 1 gallon of water on top (minutes max.)	30	30
Time to heat oven to 550° from cold start (minutes max.)	70	70

* Total accumulated when in more than one section.
** Includes canopy weight.

3.10 Construction. When applied with the specified fuel and electrical input as applicable, the range shall perform in accordance with 3.9. Range physical dimensions and weight limitations shall conform to the requirements of table I. The burner shall be on the front or left side of the unit and so arranged as not to interfere with the operator. The range shall be constructed to provide ready access for repair and cleaning. Controls shall be mounted convenient to the operator.

3.10.1 Body and doors. The range body shall be constructed of steel not less than 0.0747-inch (U.S. revised standard gage No. 14) nominal thickness, reinforced to prevent buckling or permanent set. The bottom shall be steel, not less than 0.1046-inch (U.S. revised standard gage No. 12) nominal thickness, reinforced with structural shapes. The oven door(s) shall be malleable iron, of the drop-front, shelf type and shall be capable of supporting not less than 125 pounds per square foot without permanent deformation. The door shall be hinged, equipped with a heat-resistant handle and securely latched by means of dropbar latches that require positive means to unlatch. Each door shall be equipped with a dial thermometer graduated in degrees from 200°F to 550°F. Heat loss through the door shall be minimum.

3.10.2 Cooking top. The cooking top shall be constructed of gray iron-alloy casting and shall be made in one or two sections. The exposed surfaces shall be ground and polished. The cooking top edges shall be arranged to butt against the ends of adjacent units. A corrosion-resistant metal grease trough shall be supplied for removal of grease from the cooking top. The trough shall include a drainhole at the low end for drainage of grease into a removable receptacle mounted on the range body. A chromium-plated pro bar shall be supplied at the level of the cooking top to guard against accidental burning.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:09Z
Check the source to verify that this is the current version before use.

3.10.3 Burners. The burners shall be horizontal-rotary-cup type driven by a direct-connected, totally enclosed electric motor, complete with all controls. Oil shall be supplied to the rotary cup by gravity through a fuel tube running through the center of the burner. The oil atomized by the rotary cup shall light off easily by automatic means without undue smoking, flarebacks, puffing, repeated relighting, or deposit of wet soot in firebox, flues, or stacks. The burners shall be hinge-mounted to enable the unit to be rotated away from the firing position without disturbance of the electrical or piping connections. Fuel flow shall be manually controlled so that the burner turndown conforms to the fuel consumption as specified in table I when fired by fuel as described in 3.1.

3.10.4 Burner controls. Each burner assembly shall be equipped with a manual resetting solenoid oil valve installed on the burner unit between the burner hinge pin and the tubing, used to introduce fuel into the rotating cup. The solenoid valve shall be installed and wired so that the flow of oil to the burner will be automatically interrupted upon failure of electric service to the burner and the oil flow shall not reestablish itself until the valve is manually reopened. The oil and air controls shall be interlocked to ensure proper proportioning of air and fuel from full capacity as required by the range to 1/3 rate. The burner shall be equipped with an automatic air-flow safety switch that, upon the loss of primary air pressure, shall shut down the burner. The burner motor shall be provided with an enclosed safety switch incorporating thermal overload protection. All switches shall open the ungrounded side of the electrical service to the motor and solenoid valve.

3.10.5 Primary control. The primary safety control shall respond directly to flame properties, sensing the presence or absence of flame. In the event that flame failure occurs on initial start or during the firing cycle, the primary control shall be designed to shut down the burner or may recycle once after a 60-second attempt to indicate a normal starting program is made and shall then lock out and require a manual reset. The direct spark ignition shall have a nominal voltage of at least 10,000 volts and shall be of the interrupted type as defined in UL296. The primary safey control programming, as designated in UL372 for the main burner establishing period, shall not exceed 30 seconds and the flame failure response time shall not exceed 4 seconds.

3.10.6 Combustion chamber. The combustion chamber shall be of a size to permit proper combustion and shall be fully enclosed and leak-tight to preclude mixing of the products of combustion with the air of the oven interior. The products of combustion shall pass through the heat-radiating chamber and enter the flue pipe mounted on the rear of the range. The chamber shall be lined with high-grade refractory and shall be of the replaceable type.

3.10.7 Range oven(s). The interior of the oven shall be constructed of steel, not less than 0.0747-inch (U.S. revised standard gage No. 14) nominal thickness, and shall be securely attached to the range. The oven bottom shall be of sheet metal, not less than 0.1046-inch (U.S. revised standard gage No. 14) nominal thickness, reinforced with structural shapes. Space between the oven and range shall be provided for the circulation of hot air and gases. Baffles shall be placed around the oven to provide for temperature distribution as required in table I. Unless otherwise specified (see 6.2), a

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:09Z
Check the source to verify that this is the current version before use.

corrosion-resistant metal rack with a smooth surface and means for mounting on the oven guides shall be supplied to permit adjustable shelf capability. Each oven shall have a bypass damper actuated by a lever exterior to the oven.

3.10.8 Oven thermostat control. The ovens shall be equipped with thermostat control. The control may be an integral part of the dial thermostat (as described in 3.10.1) or may be a separate control. The control shall have the same range scale graduation as the thermostat described in 3.10.1. The control shall regulate the ON and OFF periods of the burner to maintain the oven temperature set point within 20°F at midrange of its scale. The control shall conform to UL873.

3.10.9 Canopy. A steel canopy of 0.0239-inch (U.S. revised standard gage No. 24) nominal thickness shall be provided to fit the range specified. The canopy shall be mounted on the range top to preclude interference with grease removal and shall include provisions for accommodating the flue pipe.

3.10.10 Draft regulation. A barometric type damper shall be provided for draft regulation. The damper shall be preset, tamper-proof, and designed to automatically maintain the optimum draft for firing the range for each setting of the fuel control. The draft for high fire shall be maintained within 0.015-inch water pressure of the draft required. The damper shall be sized for mounting in the flue pipe of the range. Component parts of the draft regulator shall be corrosion-resistant metal. When specified (see 6.2), the flue pipe, of the size specified in table I and having a minimum thickness of 0.0179-inch (U.S. revised standard gage No. 26) including necessary elbows, shall be provided in the quantity, as specified (see 6.2). The pipe and fittings shall have interlocking seams and shall be leaktight. A vent shall be provided for each oven compartment.

3.10.11 Insulation. The range shall be insulated with glass fiber insulation and positioned to provide minimum heat leakage consistent with the specified oven performance for the maximum fuel consumption permitted in 3.9. Range components designed to be handled shall not reach temperatures in excess of 131°F for bare or painted metal, 149°F for glass, or 167°F for wood or plastic under any operating condition involved in normal baking applications.

3.10.12 Motor. Electric motors shall be rated and constructed for continuous duty in accordance with the applicable provisions of NEMA MG1. Unless otherwise specified (see 6.2), the electric supply shall be a nominal 120-volt, single-phase, 3-wire including ground wire, 60-Hertz alternating current. Wiring shall conform to NFPA No. 70.

3.10.12.1 Motor disconnect switch. A disconnect switch, conforming to NEMA ICS-1 and ICS-2, shall be furnished as a separate item for remote mounting. The switch shall be rated in accordance with NFPA No. 70. The switch shall be enclosed in a NEMA ICS-6, type No. 1 enclosure.

3.11 Fire extinguisher. When specified (see 6.2), a fire extinguisher of the dry chemical type shall be furnished as a separate item. The extinguisher shall be suitable for electrical or flammable liquid fires and shall have a capacity of not less than 2-1/2 pounds (content).

3.12 Lubrication. Unless otherwise specified (see 6.2), means for lubrication shall be in accordance with the manufacturer's standard practice. The lubricating points shall be easily visible and accessible. All parts

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:09Z
Check the source to verify that this is the current version before use.

requiring lubrication shall be properly lubricated as specified in section 5. Hydraulic lubrication fittings shall be in accordance with SAE J534. Where use of high pressure lubricating equipment, 1,000 pounds per square inch or higher, will damage grease seals or other parts, a suitable warning shall be affixed to the equipment in a conspicuous location.

3.13 Fungus resistance. When specified (see 6.2), electric components and circuit elements including terminal and circuit connections shall be treated for moisture and fungus resistance in accordance with MIL-T-13867 as specified herein. Electrical components with temperature rise of 40° centigrade (C) or less shall be coated in accordance with type II of MIL-T-13867 with fungus-resistant varnish conforming to MIL-V-173. Components with a temperature rise exceeding 40°C shall be coated in accordance with type III or IV of MIL-T-13867 with varnish conforming to MIL-I-24092 with grade and class of varnish dependent on the component, class of insulation above 40°C, and the recommendations of the manufacturer of the equipment.

3.14 Treatment and painting. Unless otherwise specified (see 6.2), the range shall be treated and painted in accordance with the manufacturer's standard practice. All surfaces of the range, other than corrosion-resisting steel, shall be protected against corrosion and present a neat appearance.

3.15 Electromagnetic interference suppression. When specified (see 6.2), the equipment shall conform to the electromagnetic interference suppression requirements and test limits for class C3, Group III equipment as specified in MIL-STD-461.

3.16 Instruction plates. The range shall be equipped with instruction plates suitably located, describing any special or important procedure to be followed in operating and servicing the equipment. Plates shall be of a material that will last and remain legible for the life of the equipment and shall be securely affixed thereto with nonferrous screws or bolts of at least 1/8-inch diameter. The letters and numerals comprising the descriptive data shall be at least 1/8 inch in height.

3.17 Identification plate. The contracting officer will furnish the required identification plates to the Government inspector. The contractor will be required to stamp the necessary data in the blank spaces thereon and securely affix said plates in a conspicuous place on each unit, assembly and/or subassembly, and parts as directed by the Government inspector. Nonferrous screws, rivets, or bolts of not less than 1/8 inch in diameter shall be used to affix the plates. Nomenclature shall be RANGE, OIL BURNING.

3.18 Workmanship. The quality of workmanship shall be such as to produce ranges that are in accordance with the requirements of this specification and ensure proper functioning of all parts of the unit.

3.18.1 Castings. All castings shall be sound and free from patching, misplaced coring, warping, or any other defect that reduces the castings ability to perform its intended function.

3.18.2 Steel fabrication. The steel used in fabrication shall be free from kinks, sharp bends, and other conditions that would be deleterious to the finished product. Manufacturing processes shall not reduce the strength of

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:09Z
Check the source to verify that this is the current version before use.

the steel to a value less than intended by the design. Manufacturing processes shall be done neatly and accurately. All bends shall be made by controlled means to ensure uniformity of size and shape.

3.18.3 Bolted connections. All bolt holes shall be accurately punched or drilled and shall have the burrs removed. Washers and lockwashers shall be provided. All nuts, bolts, and screws shall be tight.

3.18.4 Riveted connections. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall be driven with pressure tools and shall completely fill the holes. Rivet heads, when not countersunk or flattened, shall be of approved shape and of uniform size for the same diameter of rivet. Rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.18.5 Welding. Welding procedures shall be in accordance with a nationally recognized welding code. The surface of parts to be welded shall be free from rust, scale, paint, grease, or other foreign matter. Welds shall be of sufficient size and shape to develop the full strength of the parts connected by the welds. Welds shall transmit stress without permanent deformation or failure when the parts connected by the weld are subjected to proof and service loadings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure that supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. Components and materials shall be inspected in accordance with all the requirements specified herein and in applicable referenced documents.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2.1).
b. Quality conformance inspection (see 4.2.2).

4.2.1 First article inspection. The first article inspection shall be performed on one range when a first article is required (see 3.2 and 6.4). This inspection shall include the examination of 4.5 and the tests of 4.6. The first article may be a first production item or a standard production item from the supplier's current inventory provided the item meets the requirements of the specification and is representative of the design, construction, and manufacturing technique applicable to the remaining items to be furnished under the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:09Z
Check the source to verify that this is the current version before use.

4.2.2 Quality conformance inspection. The quality conformance inspection shall include the examination of 4.5, the tests of 4.6.1, and the packaging inspection of 4.8. This inspection shall be performed on the samples selected in accordance with 4.4.

4.3 Inspection lot. All units of the same type, offered to the Government at one time, shall be considered a lot for purposes of inspection. The sample unit shall be one complete range.

4.4 Sampling

4.4.1 Sampling for examination. A random sample of the range shall be selected from each lot offered to the Government in accordance with MIL-STD-105 at inspection level II. In terms of defects per 100 units, the Acceptable Quality Level (AQL) shall be 2.5 percent.

4.4.2 Sampling for tests. A random sample of the range shall be selected from each lot offered to the Government in accordance with MIL-STD-105 at inspection level S-4. In terms of defects per 100 units, the AQL shall be 2.5 percent.

4.5 Examination. Each sample range shall be examined for compliance with the requirements specified in section 3 of this specification. Any redesign or modification of the contractor's standard product to comply with specific requirements or any necessary redesign or modification following failure to meet specified requirements shall receive particular attention for adequacy and suitability. This element of inspection shall encompass all visual examinations and dimensional measurements. Noncompliance with any specified requirements or presence of one or more defects preventing or lessening maximum efficiency shall constitute cause for rejection.

4.5.1 Standards compliance. The manufacturer shall make available to the contracting officer or his authorized representative evidence of compliance with the applicable standard(s) cited in 3.7.

4.6 Tests

4.6.1 Operational test. The range shall be operated with the burners to test the burner performance when the specified type of fuel is used. Draft control and fuel intake shall be inspected for proper assembly and high-fire capability. Inspection of the electrical circuit and sequence of operation shall be made to verify compliance with 3.10.4 and 3.10.10. Oven shelf and door loading shall be checked for the loading requirements of 3.10.1 and table I.

4.6.2 Heat-up time. The cold-range oven shall be treated to determine oven heat-up time and check fuel consumption of the burner as indicated in table I. Number 2 fuel oil shall be used and ambient temperature shall not exceed 85°F. The range top shall be checked to verify compliance with 3.9.

4.6.3 Heat distribution. The cold emply range oven(s) shall be heated to an equilibrium temperature of approximately 400°F. Temperature measurements by at least five thermocouples equally spaced over the entire oven deck shall be taken every 1/2 hour for a 2-hour period. Temperature variations indicated

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:09Z
Check the source to verify that this is the current version before use.

by the thermocouple readings shall not be greater than 35°F. For each set of temperature readings, average compartment temperatures, as measured by the thermocouples, shall not vary more than 20°F during the 2-hour test.

4.6.4 Insulation. Exterior range temperatures of components designed to be handled shall be checked to determine compliance with 3.10.9.

4.7 Test for electromagnetic interference suppression. When conformance to electromagnetic interference suppression limits is required, the equipment shall be tested in accordance with MIL-STD-462 to determine conformance to the electromagnetic suppression characteristics of 3.15. When suppressed to conform to the electromagnetic interference requirements of 3.15, the manufacturer may, upon approval of the contracting officer, furnish certification that the ranges meet the requirements in lieu of the test as part of the first article (see 6.3). The manufacturer shall also furnish a list of suppression devices installed that shall be sufficiently detailed to allow visual determination that the devices are installed.

4.8 Packaging inspection. The inspection of the preservation, packing, and marking shall be in accordance with the requirements of section 4 of MIL-R-11337.

5. PACKAGING

5.1 Preservation, packing, and marking. Preservation, packing, and marking shall be in accordance with the requirements of MIL-R-11337 with the level of preservation and the level of packing as specified (see 6.2).

6. NOTES

6.1 Intended use. The ranges specified herein are to be used in field installations where steam, electrical, or gas heating source is not readily available for cooking equipment. The ranges are suitable for range-top frying and cooking and oven baking and roasting.

6.1.2 Fuel consumption. The fuel consumption of the burner is based on No. 2 fuel oil at 70°F. Since the flow of kerosene and other fuels through a given orifice moves faster than No. 2 fuel oil, because of the lower viscosity, the fuel consumption of the burner at the high-fire setting will be somewhat greater than that specified. When kerosene and other fuels are used, the fuel control should be cut back to reduce the fuel flow and thereby preclude the possibility of a smokey combustion flame that results in reduced burner efficiency.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. If specification and standards are different (see 2.1.1).
c. Type range required (see 1.2).
d. When first article is required for inspection and approval (see 3.2, 4.2.1, and 6.4).
e. When an oven rack is not required (see 3.10.7).
f. Quantity of flue pipe and fittings required (see 3.10.10).
g. Electrical supply voltage, if different (see 3.10.12).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T12:09Z
Check the source to verify that this is the current version before use.

h. When a fire extinguisher is required (see 3.11).
i. If lubrication is different (see 3.12).
j. Fungus resistance, if required (see 3.13).
k. When cleaning, treatment, and painting is different (see 3.14).
l. When electromagnetic interference suppression is required (see 3.15).
m. Level of preservation-packaging and level of packing required (see 5.1).

6.3 Contract data requirements. When this specification is used in an acquisition that incorporates a DD Form 1423 and invokes the provisions of paragraph 7-104.9(n) of the Defense Acquisition Regulations (DAR), the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of DAR 7-104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

6.4 First article. When a first article inspection is required, the item will be tested and should be a first production item or it may be a standard production item from the contractor's current inventory as specified in 4.2.1. The first article should consist of one complete range unit. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Preparing activity

Navy - YD

Project No. 7310-N610

Source: https://assist.dla.mil -- Downloaded: 202610-18T12:09Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. 7310-N610

DOCUMENT IDENTIFIER *(Number)* AND TITLE RANGES, OIL BURNING (SUITABLE FOR USE WITH MIL-R-18967C(YD) - KEROSENE, DIESEL FUEL, AND NO. 2 FUEL OIL)

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 1 OCT 76

Replaces edition of 1 Jan 72 which may be used.

S/N 0102-LF-001-4260

★ U.S. Government Printing Office: 1976—703-175/5001 2-1

Source: https://assist.dla.mil -- Downloaded: 202610-18T12:09Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL

FIRST CLASS PERMIT NO. 12503 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE NAVY

COMMANDING OFFICER (156)
NAVAL CONSTRUCTION BATTALION CENTER
PORT HUENEME, CA 93043

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-18T12:09Z
Check the source to verify that this is the current version before use.