INCH-POUND

MIL-DTL-32480
SUPPLEMENT 1
17 December 2014

DETAIL SPECIFICATION

ADAPTER, HYDRAULIC AND PNEUMATIC, FLARELESS TUBE FITTING TO ORFS CONNECTORS, 1500 TO 3000 PSI AND -65°F TO 250°F, GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-DTL-32480, dated 29 August 2014.

SPECIFICATION SHEETS

MIL-DTL-32480/1 - Fitting, Adapter, Straight, Hydraulic and Pneumatic, Flareless Male to ORFS Male
MIL-DTL-32480/2 - Fitting, Adapter, 45° Elbow, Hydraulic and Pneumatic, Flareless Male to ORFS Male
MIL-DTL-32480/3 - Fitting, Adapter, 90° Elbow, Hydraulic and Pneumatic, Flareless Male to ORFS Male
MIL-DTL-32480/4 - Fitting, Adapter, Straight, Hydraulic and Pneumatic, Flareless Male to ORFS Bulkhead
MIL-DTL-32480/5 - Fitting, Adapter, 45° Elbow, Hydraulic and Pneumatic, Flareless Male to ORFS Bulkhead
MIL-DTL-32480/6 - Fitting, Adapter, 90° Elbow, Hydraulic and Pneumatic, Flareless, Male to ORFS Bulkhead
MIL-DTL-32480/7 - Fitting, Adapter, Straight, Hydraulic and Pneumatic, Flareless, Male to ORFS, Female Swivel
MIL-DTL-32480/8 - Fitting, Adapter, 45° Elbow, Hydraulic and Pneumatic, Flareless, Male to ORFS, Female Swivel
MIL-DTL-32480/9 - Fitting, Adapter, 90° Elbow, Hydraulic and Pneumatic, Flareless, Male to ORFS, Female Swivel

CONCLUDING MATERIAL

Custodians:
Army – AT
Navy – AS
Air Force – 99
DLA – CC

Preparing activity:
DLA – CC

(Project 4730-2015-001)

Review activities:
Army – AR
Navy – CG, MC, SA, SH
Air Force – 71

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A

FSC 4730

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T06:33Z
Check the source to verify that this is the current version before use.