MIL-B-48761(AR)
AMENDMENT 4
30 October 1985
SUPERSEDING
AMENDMENT 3
24 November 1981

MILITARY SPECIFICATION

BATTERY,SINGLE CELL,PRIMARY RESERVE

This Amendment forms a part of Military Specification MIL-B-48761(AR), dated 17 March 1978, and is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Inspection Equipment Drawings-Delete "8841278 - Firing Pin" and substitute "9275628 - Firing Pin".

PAGE 9

4.4.2.2, Terminal Plate Assy, Machined 9275568:
Delete: Minor Defect 203 in its entirety.

Add:

"Minor	Exam or Test	AQL	Reqm't Para	Insp Method
203.	Height of terminal pin above inside shoulder,improper	0.65%	3.2	Gage
205.	Height of terminal pin above outside shoulder,improper	0.65%	3.2	Gage

PAGE 10

4.4.2.3, Pin, Terminal 9275569:

Delete: Minor Defect 201 in its entirety.

FSC 1345

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.

PAGE 11

4.4.2.4, Plate, Terminal, 9275570: Change Next Higher Assembly from "9275603" to "9275568".

Add:

"Minor	Exam or Test	AQL	Reqm't Para	Insp Method
204	Taper not present	1.0%	3.2	Visual"

PAGE 12

4.4.2.5 Cell Assembly, 9275571, Major Defect 101 is revised as follows:

Change Major Defect 101 from "Anode lead not positioned....." to "Screen lead not positioned ....."

PAGE 14

4.4.2.7, Screen Assembly, Anode 9275574. Change next higher assembly; from "9275576" to "9275572".

Add:

"Major	Exam or Test	AQL	Reqm't Para	Insp Method
104	Length of lead from screen, improper	0.40%	3.2	Gage
105	Length of lead overlap on screen,improper	0.40%	3.2	Gage"

Delete Minor Defects 201, 203, 204, and 205 in their entirety. Delete Notes 1, 2. and 3.

PAGE 15

4.4.2.8, Lead, 9275575. Under Minor Defects, delete "None defined", add:

"Minor	Exam or Test	AQL	Reqm't Para	Insp Method
201	Lead thickness improper	0.65%	3.2	Gage
202	Lead width improper	0.65%	3.2	Gage"

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:39Z
Check the source to verify that this is the current version before use.

4.4.2.19, Plate Assembly, Terminal, 9275603: Delete paragraph in its entirety.

PAGE 34

4.4.6.2.1 - Delete "(Dwg. 8841278)" and substitute"(Dwg.9275628)".

PAGE 35

* 4.4.6.5.1 Gross Leak.

Add to paragraph , " or alternatively, each cell shall be subjected to the gross leak test using the fine leak test equipment of paragraph 4.4.6.5.2, provided the equipment has the caability of gross leak detection. Any cell failing to meet the leak rate of MIL-STD-202E, Method 112B, Condition B, shall be rejected.

PAGE 38

Add "-A204" after project number.

NOTE: The margins of this amendment are marked with an asterisk vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a covenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1345-A347)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:39Z
Check the source to verify that this is the current version before use.