MILITARY SPECIFICATION SHEET

CIRCUIT CARD ASSEMBLY, 9290623
(OPERATOR CONTROL PANEL INTERFACE)

This Amendment forms a part of Military Specification Sheet MIL-C-63371/4B(AR) dated 31 July 1984, and is approved for use within the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Electrical Requirements; delete second sentence of paragraph 1 in its entirety and substitute:

"All other input and output levels shall be consistent with IC operating levels and power supply regulation and shall not exceed plus or minus 1.0% of the indicated values, unless otherwise noted. Output voltages shall read as indicated in the table below".

Electrical Requirements; delete paragraph 2 in its entirety and substitute:

"2. All frequencies and pulse widths shall be within plus or minus 10% of the values indicated herein:

Test Number	Specified Output Voltage	Allowable Voltage Range
1-6	0	0 to 1.2V
	14V	12.8V to 14.2V
	24V	22V to 24.2V
5-6	Output waveform levels	± 10%"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

PAGE 2

MCS Self-Test, Time Long, Delete the NOTE in its entirety and substitute:

"NOTE: Connect a 130 ohm, 6 watt resistor between pin no. 69 and 28 volts.
Connect a 180 ohm, 2 watt resistor between pin no. 41 and 24 volts".

PAGE 9

Add the following NOTE after Test 4J:

"NOTE: Connect a 180 ohm, 2 watt resistor between pin no. 68 and 24 volts."

PAGE 10

Test 5B (50° Left); Add the following NOTE after Test 5B:

"NOTE: Connect a 12 ohm, 60 watt resistor between pin no. 63 and 24 volts and pin no. 39 and 24 volts.

Maintain the following throughout TEST 5:

Pin No.	Voltage
62	14
65	0"

PAGE 13

Test 5I; Delete Input Table in its entirety and substitute:

INPUT	
Pin No.	Voltage
60	14
58	14
59	14
46	0
47	0
48	0
50	0

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.

Test 5I; Delete Output Table in its entirety and substitute:

OUTPUT	
Pin No.	Voltage
63	24
39	24

Test 6A (90° Full); Add the following NOTE after Test 6A:

"NOTE: Connect a 12 ohm, 60 watt resistor between pin no. 39 and 24 volts. Maintain the following throughout Test 6:

Pin No.	Voltage
62	14
65	0"

NOTE: the margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1095-A256-4)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:43Z
Check the source to verify that this is the current version before use.