MIL-C-55302/38A
1 February 1973
SUPERSEDING
MIL-C-55302/38
29 November 1971

MILITARY SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: PLUG, ELECTRICAL, POLARIZED SHELL, MALE, 0.100 INCH CONTACT SPACING, PIN TERMINAL

The complete requirements for procuring the connector described herein shall consist of this document and the latest issue of Specification MIL-C-55302

This specification is approved for use by all Department and Agencies of the Department of Defense.




FIGURE 1. Connector, plug, male...100 contact spacing, pin terminal.

FSC 5935

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:46Z
Check the source to verify that this is the current version before use.

INCHES	MM
.001	.03
.002	.05
.0025	.06
.005	.13
.010	.25
.020	.51
.025	.61
.031	.79
.040	1.02
.047	1.19
.050	1.27
.062	1.57
.078	1.98
.084	2.13
.100	2.54
.112	2.84
.140	3.56
.156	3.96
.200	5.08
.297	7.54
.350	8.89
.375	9.53
.504	12.80
.604	15.34
.800	20.32

NOTES:
1. Dimensions are in inches.
2. Metric equivalents (to the nearest .01 mm) are given for general information only and are based upon 1 inch = 25.4 mm.
3. Unless otherwise specified, tolerance is ± .015 (.38 mm).
4. Break all sharp edges .005 (.13 mm) minimum.
5. C dimension is measured at the top of the draft angle at the base of the chamfer, at center line of shell.
6. Nominal spacing between any two adjacent contacts shall be .100 ± .002 (2.54 ± .05 mm); overall tolerance between any span of 23 to 28 contacts shall be ±.004 (.10 mm), overall tolerance between any span of 29 through 35 contacts shall be ±.005 (.13 mm).
7. For dimensions A through G, see table I.
8. Detail contour of insert beyond shell optional, provided maximum dimensions are not exceeded.
9. No. 6 fillister head machine screw (MS35265, MS35273, MS35275 or equivalent) recommended for mounting.

FIGURE 1. Connector, plug, male, .100 contact spacing, pin terminal - continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:46Z
Check the source to verify that this is the current version before use.




FIGURE 2. Insert arrangement for contact spacing connectors.
(Female engaging face)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:46Z
Check the source to verify that this is the current version before use.

TABLE I. Part number, dimensions and characteristics.

Part number	Dimensions 1/ 2/							Characteristics		
	A	B ± .010	C ± .005	D	E(min)	F	G +.015 -.000	Number of contact	Board thickness	Contact termination
M55302/38-01	2.097 (53.26)	1.800 (45.97-45.47)	1.260 (32.13-31.88)	1.000 (25.40)	1.250 (30.61)	.149 (3.78)	.125 (3.56-3.18)	11	1/16	Pin, right angle
M55302/38-02	2.097 (53.26)	1.800 (45.97-45.47)	1.260 (32.13-31.88)	1.000 (25.40)	1.205 (30.61)	.149 (3.78)	.188 (5.16-4.78)	11	2/16	Pin, right angle
M55302/38-03	2.097 (53.26)	1.800 (45.97-45.47)	1.260 (32.13-31.88)	1.000 (25.40)	1.205 (30.61)	.149 (3.78)	.312 (8.31-7.92)	11	4/16	Pin, right angle
M55302/38-04	2.721 (69.11)	2.400 (61.21-60.71)	1.884 (47.98-47.73)	1.600 (40.64)	1.805 (45.84)	.161 (4.09)	.125 (3.56-3.18)	17	1/16	Pin, right angle
M55302/38-05	2.721 (69.11)	2.400 (61.21-60.71)	1.884 (47.98-47.73)	1.600 (40.64)	1.805 (45.85)	.161 (4.09)	.188 (5.16-4.78)	17	2/16	Pin, right angle
MS55302/38-06	2.721 (69.11)	2.400 (61.21-60.71)	1.884 (47.98-47.73)	1.600 (40.64)	1.805 (45.85)	.161 (4.09)	.312 (8.31-7.92)	17	4/16	Pin, right angle
MS55302/38-07	3.346 (84.99)	3.000 (76.45-75.95)	2.509 (63.86-63.60)	2.200 (55.88)	2.405 (61.09)	.173 (4.39)	.125 (3.56-3.18)	23	1/16	Pin, right angle
MS55302/38-08	3.346 (84.99)	3.000 (76.45-75.95)	2.509 (63.86-63.60)	2.200 (55.88)	2.405 (61.09)	.173 (4.39)	.188 (5.16-4.78)	23	2/16	Pin, right angle
MS55302/38-09	3.346 (84.99)	3.000 (76.45-75.95)	2.509 (63.86-63.60)	2.200 (55.88)	2.405 (61.09)	.173 (4.39)	.312 (8.31-7.92)	23	4/16	Pin, right angle
MS55302/38-10	3.971 (100.86)	3.600 (91.69-91.19)	3.134 (79.73-79.48)	2.800 (71.12)	3.005 (76.33)	.186 (4.72)	.125 (3.56-3.18)	29	1/16	Pin, right angle
MS55302/38-11	3.971 (100.86)	3.600 (91.69-91.19)	3.134 (79.73-79.48)	2.800 (71.12)	3.005 (76.33)	.186 (4.72)	.188 (5.16-4.78)	29	2/16	Pin, right angle
MS55302/38-12	3.971 (100.86)	3.600 (91.69-91.19)	3.134 (79.73-79.48)	2.800 (71.12)	3.005 (76.33)	.186 (4.72)	.312 (8.31-7.92)	29	4/16	Pin, right angle
MS55302/38-13	4.596 (116.74)	4.200 (106.93-106.43)	3.759 (95.61-95.35)	3.400 (86.36)	3.605 (91.57)	.198 (5.03)	.125 (3.56-3.18)	35	1/16	Pin, right angle
MS55302/38-14	4.596 (116.74)	4.200 (106.93-106.43)	3.759 (95.61-95.35)	3.400 (86.36)	3.605 (91.57)	.198 (5.03)	.188 (5.16-4.78)	35	2/16	Pin, right angle
MS55302/38-15	4.596 (116.74)	4.200 (106.93-106.43)	3.759 (95.61-95.35)	3.400 (86.36)	3.605 (91.57)	.198 (5.03)	.188 (8.31-7.92)	35	2/16	Pin, right angle

1/ Dimensions are in inches.
2/ Metric equivalents (to the nearest .01 mm) are given for general information only, and are based upon 1 inch - 25.4 mm.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:46Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration	See figure 1 and table I.
Materials:	
Trapezoidal shells	Die cast aluminum, per QQ-A-591, compositions 13, A13, 380, or A380, cadmium plated, iridescent gold color, type II, class 1 or 2, or QQ-P-416.
Contact identification	Shall be numberical and sequential, in the pattern indicated. See figure 2.
Contact plating	To conform to type II, class 2, of MIL-G-45204. Silver underplate shall not be used.
Contact resistance	The average resistance of all contact pairs measured shall not exceed 0.010 ohm, and no individual contact pair shall have a resistance exceeding 0.020 ohm.
Dielectric withstanding voltage:	
Sea level	1,700 volts rms, 60 Hz. ac.
70,000 feet altitude	565 volts rms, 60Hz. ac.
Working voltage	500 volts rms, maximum.
Contact size	20.
Current rating, maximum	7.5 amperes.
Contact current rating	5 amperes.
Insert arrangement	See figure 2.
Mating connectors	See MIL-C-55302/36, MIL-C-55302/37, and MIL-C-55302/42.
Part number	See table I.

TABLE II. Cross reference between MIL-C-23353 type number and MIL-C-55302 part number.

MIL-C-23353 type no.	MIL-C-55302 part no.
P11C16	M55302/38-01
P11C26	M55302/38-02
P11C46	M55302/38-03
P17C16	M55302/38-04
P17C26	M55302/38-05
P17C46	M55302/38-06
P23C16	M55302/38-07
P23C26	M55302/38-08
P23C46	M55302/38-09
P29C16	M55302/38-10
P29C26	M55302/38-11
P29C46	M55302/38-12
P35C16	M55302/38-13
P35C26	M55302/38-14
P35C46	M55302/38-15

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:46Z
Check the source to verify that this is the current version before use.

Custodian:
Army - EL
Navy - EC
Air Force - 17

Review activities:
Army - EL, MU, MI
Navy - OS
Air Force - 11, 17, 80
DSA - ES

User activities:
Army - ME, AT, AV, SL, WC
Navy - MC, SH, AS
Air Force - 19, 80

Preparing activity:
Army - EL

Agent:
DSA - ES

(Project 5935-1875-6)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:46Z
Check the source to verify that this is the current version before use.