INCH-POUND

MIL-E-63241B(AR)
AMENDMENT 5
14 November 1988
SUPERSEDING
AMENDMENT 4
3 September 1987

MILITARY SPECIFICATION

ELECTRONIC ASSEMBLY, FOR MINES, M718/M741, SYSTEM

This Amendment forms a part of Military Specification MIL-E-63241B(AR), dated 14 July 1983, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 7

* Add new paragraph:

"3.5.7 Shorting bar open circuit. The resistance in the shorting bar loop when measured between the output terminal to ground shall be greater than 100K ohms. (see 4.5.16.1)"

PAGE 8

4.3.1: Delete Quantity "50" and substitute "90" for Dwg. 9287150-1 and Dwg. 9287151-1.

PAGE 10

Table I. First Article Inspection, under paragraph reference/ inspection method, delete "4.4.2.27" and substitute "4.4.2.25".

Delete "4.4.2.28" and substitute "4.4.2.26".

Delete "4.4.2.25" and substitute "4.4.2.23".

Delete "4.4.2.26" and substitute "4.4.2.24".

Table I. First Article Inspection, under No. of Sample, delete quantity "50" and substitute "90" for Dwg. 927150-1 and Dwg. 9287151-1.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.

PAGE 11

Table I. First Article Inspection, under paragraph reference/ inspection method, delete "4.4.2.22" and substitute "4.4.2.21".

PAGE 23

4.4.2.11: Under title, delete "JAN 2N1907A" and substitute "JAN 2N2907A".

PAGE 28

4.4.2.16 Delete the page in its entirety and substitute included page 28.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.16	A. D. Switch Assembly				9298512
					NEXT HIGHER ASSEMBLY 9287138
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Switch function seven (7) contact closures minimum each direction		100%	3.2	4.5.17.1
102	Contact closure duration 0.60 seconds max.		100%	3.2	4.5.17.1
103	Insulation resistance		100%	3.2	4.5.17.2
104	Assembly damaged, distorted or incomplete		0.40%	3.2	Visual
105	Ribbon improperly welded to can		0.40%	3.2	Visual
106	Epoxy seal missing or incomplete		0.40%	3.2	Visual
107	Solderability, 2 leads			5.5.5.1	Visual (Note 1)
Minor					
201	Evidence of poor workmanship		1.0%	3.12	Visual

NOTES:
1. Verify double dip operation each shift.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.

PAGE 37

4.4.2.25: Delete critical defect 2 and substitute the following critical defect:

"Category Critical	Exam/Test	No. of Sample Units	AQL	Req Para	Para Ref/ Insp Method
2	SD Time out high-real time test				
	Hot Temp. (Note 4)		8-0-1	3.5.2.4.1	4.5.26
	Cold Temp. (Note 5)		8-0-1	3.5.2.4.1	4.5.26
	Ambient Temperature		16-0-1	3.5.2.4.1	4.5.26"

Under Note 3, delete "16-0-1 Critical".

PAGE 39

Add the following Major Defect:

"Category Major	Exam/Test	No. of Sample Units	AQL	Req Para	Para Ref/ Insp Method
126	Output terminal(s) with excess potting material or exposed base metal	4.4.3.3		3.10	Visual, 4X Magnifying Lamp"
* 127	Shorting bar open circuit (note 9)		32-0-1	3.5.7	4.5.16.1"

* Add new note:

"(9) Use the units from the Real Time SD Timeout Test."

Delete Major 124 in its entirety.

Delete Note 8 in its entirety.

PAGE 40

4.4.2.26: Critical Defect 1, delete "4.5.7" under paragraph reference/inspection method and substitute "4.5.8".

Delete Critical Defect 2 in its entirety and substitute the following Critical Defect:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.

"Category Critical	Exam/Test	No. of Sample Units	AQL	Req Para	Para Ref/ Insp Method
2	SD Time out high-real time test				
	Hot Temp. (Note 4)		8-0-1	3.5.2.4.2	4.5.26
	Cold Temp. (Note 5)		8-0-1	3.5.2.4.2	4.5.26
	Ambient Temperature		16-0-1	3.5.2.4.2	4.5.26"

Under Note 3, delete "16-0-1 Critical".

PAGE 41

4.4.2.26, Major 104: Delete "4.5.7" under paragraph reference and substitute "4.5.8".

Major 105: Delete "9287150-2" under Examination or Test and substitute "9287151-2".

PAGE 42

4.4.2.26: Add the following Major Defect:

"Category Major	Exam/Test	No. of Sample Units	AQL	Req Para	Para Ref/ Insp Method
126	Output terminal(s) with excess potting material or exposed base metal	4.4.3.3		3.10	Visual, 4X Magnifying Lamp"
* 127	Shorting bar open circuit (note 9)	32-0-1		3.5.7	4.5.16.1"

* Add new note:

"(9) Use the units from the Real Time SD Timeout test."

Delete Major 124 in its entirety.

Delete Note 8 in its entirety.

PAGE 43

4.4.3.1, Second paragraph: Delete "4.4.2.27, 4.4.2.28" and substitute "4.4.2.25, 4.4.2.26".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.

PAGE 44

4.4.5 Eleventh line down: Delete "4.4.2.24" and substitute "4.4.2.22".

Twenty-ninth line down: Delete sentence "ARRADCOM, Dover, New Jersey 07801, ATTN: DRDAR-QAT-M" and substitute "ARDEC, Picatinny Arsenal, New Jersey 07806-5000, ATTN: AMSMC-QAT-M (D)".

PAGE 47

4.5.1.3, Fifth line down: Delete the word "Ambient".

PAGE 48

* Add new paragraph:

"4.5.16.1 Shorting bar open circuit. The resistance of each shorting bar circuit shall be measured, using an approved ohmmeter, between the test points E3 and TP9. Observation shall be made for compliance with requirement of 3.5.7. This is a destructive test to be performed after the Real Time SD Timeout Test."

PAGE 49

Sixth line down: Delete "DI-R-5372" and substitute "DI-T-5372".

PAGE 50

* 4.5.26 Sub paragraph d: Delete in its entirety and substitute:

"d. If an electronic assembly fails to function in the self-destruct mode after it maximum SD time period, the assembly shall be subjected to functioning by physical disturbance to promote anti-disturbance functioning, by applying a valid target signature using a simulated prime target sensor input after SD time (Hazardous) shall be considered defective. The battery voltage shall then be measured and recorded and the electronic assembly shall be set aside for dismantling and failure analysis."

4.5.26, Fourth line down: Delete "appropriate test fixture" and substitute "electric battery primer, Dwg. No. 9292624".

5.2, Second line: Delete the word "Level C" and substitute with "Level B".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.

3.6.1 of Appendix: Delete paragraph in its entirety.

3.5.1 of Appendix: Delete paragraph number "3.5.1" and substitute "3.6.1".

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A493)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:27Z
Check the source to verify that this is the current version before use.