MIL-S-48735A(AR)
AMENDMENT 2
7 June 1984
SUPERSEDING
AMENDMENT 1
12 August 1983

MILITARY SPECIFICATION

SAFE AND ARMING DEVICE FOR MINES,
M718/M741 SYSTEMS, METAL PARTS FOR

This Amendment forms a part of Military Specification MIL-S-48735A(AR) dated 31 March 1982, and is approved for use by the U.S. Army ARmament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

* 2.1.1: Add the following under Specifications-Military:

"MIL-P-50884 - Printed Wiring, Flexible, General Specification For."

PAGE 3

* 3.6.5: Add new paragraph as follows:

"3.6.5 Flexcable solder pads. The pad area shall be continuous, shall not indicate dullness, oxidation or contain glaring structures. It shall be free of glue and kapton coverings over plated surfaces.

3.7 Solderability. All pad areas contained on the flexcable shall comply with the specified solderability requirements of MIL-P-50884.

PAGE 5

* Replace page 5 with new page 5.

PAGE 8

* Replace page 8 with new page 8.

FSC 1345

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

PAGE 43

Replace page 43 with new page 43.

The margines of this amendment are marked with an asterisk or verticial lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A311)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:38Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	S & A Metal Parts				See Below
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cable, Flexible (Dwg. 9277774)				
	Examination for defects	10		3.2	4.4.2.1
	Continuity resistance	10		3.4	4.5.4
	Solderability	25		3.6.5	4.4.2.1
	Lock, Centrifugal (Dwg. 9277786)				
	Examination for defects	10		3.2	4.4.2.2
	"G" Weight (Dwg. 9177790)				
	Examination for defects	10		3.2	4.4.2.3
	Hardness	Note 1		3.2	4.5.1
	Lock, "G" Weight (Dwg. 9277871)				
	Examination for defects	10		3.2	4.4.2.19
	Hardness	Note 1		3.2	4.5.1
	Clip, Grounding (Dwg. 9278001)				
	Examination for defects	10		3.2	4.4.2.23
	Housing (Dwg. 9278008)				
	Examination for defects	10		3.2	4.4.2.25

NOTES:
1. Ten (10) parts shall be selected from each heat treat batch.

Source: https://assist.dla.mil - Downloaded: 2026-10-22 19:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Cable, Flexible		9277774
			NEXT HIGHER ASSEMBLY 9277868

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of terminal holes		0.40%	3.2	Gage
102	Diameter of terminal holes		0.40%	3.2	Gage
103	Continuity resistance	Note 1	0.40%	3.4	4.5.4
104	Any bridging of copper between conductive path		100%	3.2	Visual
105	Any separation of plastic lamination		0.40%	3.2	Visual
106	Workmanship		0.40%	3.6.5	Visual
107	Solderability		25/0/1	3.7	MIL-P-50884
Minor					
201	Profile of cable		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES: 1. Any cable which fails to comply with the specified resistance shall be classed defective and removed from the lot. (Non-destructive test.)
2. Sampling shall be on a plating batch basis. Failure of any pad on the cable to comply with all of the solderability requirements shall cause the plating batch to be classed defective.

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2023-10-22 19:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.31	Retainer, Spring				9278041
					NEXT HIGHER ASSEMBLY 9278015
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Flatness		0.40%	3.2	Gage
102	Diameter improper (min.)		0.40%	3.2	Gage
103	Thickness improper (min.)		0.40%	3.2	Gage
104	O.D. of pilot		0.40%	3.2	Gage
105	True position of pilot		0.40%	3.2	Gage
106	Height of pilot		0.40%	3.2	Gage
Minor					
201	Protective finish missing or improper		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2020-10-22 19:58Z
Check the source to verify that this is the current version before use.