
MILITARY SPECIFICATION SHEET

CABLES, RADIO FREQUENCY, COAXIAL, SEMIRIGID, CORRUGATED OUTER CONDUCTOR, LOW LOSS FOAM DIELECTRIC, 1/4 INCH NOMINAL, 50 OHMS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-28830.




Inches	mm
.001	0.03
.005	0.13
.010	0.25
.040	1.02
.075	1.90
.105	2.67
.186	4.72
.250	6.35
.355	9.02

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.

FIGURE 1. Cable configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:21Z
Check the source to verify that this is the current version before use.



Standard conditions for average power and attenuation;

For average power:
VSWR: 1.0.
Ambient temperature: 40°C (104°F).
Inner conductor temperature: 100°C (212°F).

For attenuation:
VSWR: 1.0.
Ambient temperature: 24°C (75°F).

FIGURE 2. Power rating and attenuation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:21Z
Check the source to verify that this is the current version before use.

ENGINEERING INFORMATION:

Weight:

Type II jacketing: .05 lb/ft nominal.
Type IV jacketing: .07 lb/ft nominal.

Minimum in-service bending diameter: 2 inches (51 millimeters).

Average power rating: See figure 2.

REQUIREMENTS:

Design and Construction: See figure 1.

Flexibility and cold bend mandrel diameter: 2 inches (51 millimeters) maximum.

Test cable length: 6 feet (1.8 meters).

Impedance: 50 ±3 ohms.

Attenuation (maximum):

At 400 MHz: 4.1 dB/100 feet (30.5 meters).
At 4,000 MHz: 14.1 dB/100 feet (30.5 meters).
At 14,000 MHz: 29.4 dB/100 feet (30.5 meters).

Velocity of propagation: 84 percent nominal.

Capacitance: 24.2 pF/ft nominal.

Voltage standing wave ratio (VSWR): 2.0 maximum.

VSWR frequency range: 100 MHz to 14,000 MHz.

Dielectric withstanding voltage: 1,600 V dc.

Jacket spark:

Type II jacketing: 5,000 V rms.
Type IV jacketing: 4,000 V rms.

Acid gas generation (type IV only): 2.0 maximum.

Halogen content (type IV only): 0.2 maximum.

Smoke index (type IV only): 35 maximum.

Toxicity index (type IV only): 5 maximum.

Tensile strength and elongation:

Type II jacketing: 2,100 psi and 700 percent minimum elongation.
Type IV jacketing: 1,200 psi and 115 percent minimum elongation.

Part or Identifying Number (PIN):

M28830/6-II
M28830/6-IV

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:21Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85

Review activities:
Navy - AS, MC, SH
Air Force - 17, 19, 99
DLA - IS

Preparing activity:
DLA - ES

(Project 6145-2030-04)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:21Z
Check the source to verify that this is the current version before use.