INCH-POUND

MIL-DTL-28837/7A
October 30, 2001
SUPERSEDING
MIL-M-28837/7
1 June 1979

DETAIL SPECIFICATION SHEET

MIXER STAGES, RADIO FREQUENCY, DOUBLE BALANCED, TO-5 CONFIGURATION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-28837.



Ltr	Dimension			
	Inches		mm	
	Min	Max	Min	Max
A	.315	.345	8.00	8.76
B	---	.407	---	10.34
C	.140	---	3.56	---
D	.015 DIA	.019 DIA	0.38 DIA	0.48 DIA
E	.335	.370	8.51	9.40
F	.190	.210	4.83	5.33
G	---	.050	---	1.27
H	.026	.036	0.66	0.91

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.

FIGURE 1. Outline drawing for mixers PIN M28837/7-01N, M28837/7-02N, and M28837/7-02S.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:24Z
Check the source to verify that this is the current version before use.



Ltr	Dimension			
	Inches		mm	
	Min	Max	Min	Max
A	.305	.335	7.75	8.51
B	---	.275	---	6.99
C	.140	---	3.56	---
D	.015 DIA	.019 DIA	0.38 DIA	0.48 DIA
E	.335	.370	8.51	9.40
F	.190	.210	4.83	5.33
G	---	.050	---	1.27

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1 inch = 25.4 mm.

FIGURE 2. Outline drawing for mixers PIN M28837/7-03N.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:24Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figures 1 and 2.

Electrical characteristics:

Operating frequency range: See table I.

LO drive power: See table I.

Conversion loss (max): See table I.

Noise figure (SSB): See table I.

Isolation (minimum): See table I.

Maximum input power: See table I.

Conversion compression: See table I.

Desensitization: See table I.

Physical and environmental characteristics:

Weight: 2 grams maximum.

Temperature:

-01N, 03N = Operating: -54°C to +100°C.
Nonoperating: -65°C to +100°C

-02N, 02S = Operating: -65°C to +100°C.
Nonoperating: -65°C to +100°C

Shock: Test condition C.

Life: -01 = 100,000 hours minimum.

Seal: Hermetic.

Part or Identifying Number (PIN): M28837/7 (dash number from table I).

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:24Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics.

Dash no.	Operating frequency range (MHz)	LO input drive power in dBm 1/	Maximum conversion loss (SSB) dB MHz	Noise figure (SSB) dB MHz	Isolation Minimum LO-RF dB	Isolation Minimum LO-IF dB	Isolation Minimum RF-IF dB	Isolation Frequency MHz
01N 01S	RF 10-500 LO 10-5000 IF DC-500	nominal +7 TV +7	7.0 at: f_L and f_R 10-200 f_I DC-200	7.0 at: f_L and f_R 10-200 f_I 0.4-200	40 35 30 25	35 30 25 15	25 20 15 10	10-50 50-100 100-200 200-500
			8.0 at: f_L and f_R 200-350 f_I DC-350	8.0 at: f_L and f_R 200-350 f_I 0.4-350				
			9.0 at: f_L and f_R 350-500 f_I DC-500	9.0 at: f_L and f_R 350-500 f_I 0.4-500				
02N 2/ 02S	RF 350-500 LO 350-500 IF DC-500	nominal +7 TV +7	9.0 at: f_L and f_R 350-500 f_I DC-500	9.0 at: f_L and f_R 350-500 f_I 0.4-500	25	15	10	350-500
03N 03S	RF 0.4-500 LO 0.4-500 IF DC-500	minimum +4 TV +7 maximum +13	6.5 at: f_L and f_R 1-200 f_I DC-200	6.5 at: f_L and f_R 2-200 f_I 2-200	45	30	N/A	0.4-60
			7.5 at: f_L and f_R 0.4-500 f_I DC-500	7.5 at: f_L and f_R 2-500 f_I 2-500	30	20	N/A	60-500

1/ Unless otherwise specified, TV is the test value of the LO power for electrical characteristics.
2/ Use for reacquisition purposes only.
3/ With two in-phase signals applied to the LO and RF ports.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:24Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR, MI
Navy - AS, CG, MC, OS
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5985-1230-03)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:24Z
Check the source to verify that this is the current version before use.