INCH-POUND


MIL-DTL-28837/7B
w/AMENDMENT 1
24 March 2022
SUPERSEDING
MIL-DTL-28837/7B
5 July 2012

DETAIL SPECIFICATION SHEET

MIXER STAGES, RADIO FREQUENCY, DOUBLE BALANCED, TO-5 CONFIGURATION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-DTL-28837.



Dimension				
Ltr	Inches		mm	
	Min	Max	Min	Max
A	.315	.345	8.00	8.76
B	---	.407	---	10.34
C	.140	---	3.56	---
D	.015 DIA	.019 DIA	0.38 DIA	0.48 DIA
E	.335	.370	8.51	9.40
F	.190	.210	4.83	5.33
G	---	.050	---	1.27
H	.026	.036	0.66	0.91


NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.

FIGURE 1. Outline drawing for mixers PIN M28837/7-01N, M28837/7-02N, and M28837/7-02S.

AMSC N/A
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

FSC 5895

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:24Z
Check the source to verify that this is the current version before use.



Ltr	Dimension			
	Inches		mm	
	Min	Max	Min	Max
A	.305	.335	7.75	8.51
B	---	.275	---	6.99
C	.140	---	3.56	---
D	.015 DIA	.019 DIA	0.38 DIA	0.48 DIA
E	.335	.370	8.51	9.40
F	.190	.210	4.83	5.33
G	---	.050	---	1.27

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1 inch = 25.4 mm.

FIGURE 2. Outline drawing for mixers PIN M28837/7-03N.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:24Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figures 1 and 2.

Electrical characteristics:

Operating frequency range: See table I.

LO drive power: See table I.

Conversion loss (max): See table I.

Noise figure (SSB): See table I.

Isolation (minimum): See table I.

Maximum input power: See table I.

Conversion compression: See table I.

Desensitization: See table I.

Physical and environmental characteristics:

Weight: 2 grams maximum.

Temperature:

-01N, 03N = Operating: -54°C to +100°C.
Nonoperating: -65°C to +100°C

-02N, 02S = Operating: -65°C to +100°C.
Nonoperating: -65°C to +100°C

Shock: Test condition C.

Life: -01 = 100,000 hours minimum.

Seal: Hermetic.

Part or Identifying Number (PIN)
Example of Nonscreened PIN M28837/7- 01N
Example of Screened PIN M28837/7- 01S
Space flight mixers shall be marked with “T”, example M28837/7- 01 T

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:24Z
Check the source to verify that this is the current version before use.

TABLE I. Electrical characteristics.

Dash no.	Operating frequency range (MHz)	LO input drive power in dBm 1/	Maximum conversion loss (SSB) dB MHz	Noise figure (SSB) dB MHz	Isolation			
						Minimum		Frequency
					LO-RF	LO-IF	RF-IF	
					dB	dB	dB	MHz
01N 01S	RF 10-500 LO 10-500 IF DC-500	nominal +7 TV +7	7.0 at: f_L and f_R 10-200 f_I DC-200	7.0 at: f_L and f_R 10-200 f_I 0.4-200	40 35 30 25	35 30 25 15	25 20 15 10	10-50 50-100 100-200 200-500
			8.0 at: f_L and f_R 200-350 f_I DC-350	8.0 at: f_L and f_R 200-350 f_I 0.4-350				
			9.0 at: f_L and f_R 350-500 f_I DC-500	9.0 at: f_L and f_R 350-500 f_I 0.4-500				
02N 2/ 02S	RF 350-500 LO 350-500 IF DC-500	nominal +7 TV +7	9.0 at: f_L and f_R 350-500 f_I DC-500	9.0 at: f_L and f_R 350-500 f_I 0.4-500	25	15	10	350-500
03N 03S	RF 0.4-500 LO 0.4-500 IF DC-500	minimum +4 TV +7 maximum +13	6.5 at: f_L and f_R 1-200 f_I DC-200	6.5 at: f_L and f_R 2-200 f_I 2-200	45	30	N/A	0.4-60
			7.5 at: f_L and f_R 0.4-500 f_I DC-500	7.5 at: f_L and f_R 2-500 f_I 2-500	30	20	N/A	60-500

1/ Unless otherwise specified, TV is the test value of the LO power for electrical characteristics.
2/ Use for reacquisition purposes only.
3/ With two in-phase signals applied to the LO and RF ports.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:24Z
Check the source to verify that this is the current version before use.

Referenced documents. This specification sheet only references MIL-DTL-28837.

Amendment notations. The margins of this specification sheet are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5895-2022-003)

Review activities:
Army - AR, MI
Navy - AS, CG, MC, OS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:24Z
Check the source to verify that this is the current version before use.