INCH-POUND

MIL-DTL-3943/345
6 September 2011

DETAIL SPECIFICATION SHEET

MEDAL, NATIONAL RESPONSE DEPLOYMENT, NOAA CORPS

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

DASH NUMBERS:
-1 Regular Size
-2 Miniature Size

MATERIAL (-1 and -2): Red Brass 85/15 (UNS Alloy C-23000)

FINISH (-1 and -2): Brass, Oxidized, Buffed Relieved, and shall match The Institute of Heraldry (TIOH) Metal Finish Chip #4.

AMSC N/A

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:11Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

HEIGHT (including lug):

-1: 1-3/8 inches (REF)

-2: 11/16 inch (REF)

DIAMETER (excluding lug):

-1: 1-1/4 inches (REF)

-2: 5/8 inch (REF)

THICKNESS (at apex of triangle):

-1: 0.145 ± 0.010 inch

-2: 0.100 ± 0.010 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.
2. The decoration set consists of a regular-size medal, a miniature-size medal, and a service ribbon bar, and shall be packaged in a presentation case conforming to MIL-C-14633, Type XVI, with a Class 2 pad.
3. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/644.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

Civil agency:
DOC - CNA

(Project No. 8455-2011-064)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:11Z
Check the source to verify that this is the current version before use.