MILITARY SPECIFICATION

PIN, SPRING, TUBULAR (COILED AND SLOTTED)

This amendment forms a part of Military Specification MIL-P-10971E, dated 23 May 1969, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1 Under Federal Specifications: Add "PPP-H-1581 - Hardware, (Fasteners and Related Items), Packaging Of".

Under Military Specifications: Delete "MIL-H-3982 - Hardware (Fasteners and Related Items), Packaging and Packing for Shipment and Storage Of".

Under Military Standards: Add "MIL-STD-1312 - Fasteners, Test Methods".

Under Military Standards: Delete "MS33547 - Pins, Spring, Functional Limitations of a Design Standard".

PAGE 3

2.2 Line 13: Delete and substitute "400 Commonwealth Drive, Warrendale, PA 15096".

*Add "American Society of Mechanical Engineers
ANSI/ASME B18.8.2-78 Taper Pins, Dowel Pins, Straight Pins, Grooved Pins, and Spring Pins (Inch Series).

(Applications for copies should be addressed to the American Society of Mechanical Engineers, Inc. 345 East 47th Street, NY, NY 10017.)

ASTM
ASTM B565 - Rivets and Cold Heading Wire and Rods, Testing of Aluminum and Aluminum Alloy.

(Application for copies should be addressed to ASTM, 1916 Race Street, Philadelphia, PA 19103.)"

PAGE 7

4.2.4 Delete in its entirety.

FSC 5315
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:50Z
Check the source to verify that this is the current version before use.

PAGE 9

4.3.4 Delete and substitute: "4.3.4 Packaging inspection - The sampling and inspection of the preservation - packaging, packing, and container marking shall be in accordance with the requirements of PPP-H-1581."

4.4.3.1 Delete and substitute: "4.4.3.1 Type I, slotted pins. Slotted pins shall be tested for hardness in accordance with MIL-STD-1312, Test 6, Hardness. The hardness shall be within the hardness limits of 3.5."

PAGE 10

4.4.3.2 Delete and substitute: "4.4.3.2 Type II, coiled pins. Coiled pins shall be tested for hardness on the inside surface of the outside half coil of the pin in accordance with MIL-STD-1312, Test 6, Hardness. The hardness shall be within the hardness limits of 3.5."

*4.4.4 f. Add new sentence as follows: "Test fixtures conforming to ASTM B565 or ANSI B18.8.2 shall be used to determine shear values specified in tables I and II herein.

PAGE 11

5. Delete in its entirety and substitute:

"5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with PPP-H-1581 (see 6.2)."

6.1 Delete "See MS33547 for functional limitations" and substitute "(For functional limitations, see 6.4)".

6.2 e. and f. Delete and substitute: "e. Applicable levels of packaging (see 5.1)".

6.4 Delete in its entirety and substitute new paragraph as follows: "6.4 Functional limitations. Functional limitations of spring pins conforming to MIL-P-10971 are specified in MS33547. It is essential that proper performance of spring pins be taken into consideration when used in the design and construction of military equipment."

Add new paragraph as follows: "6.5 Standard hardness conversion tables. Standard hardness conversion data is specified in ANSI/ASTM E 140, Standard Harndess Conversion Tables for Metals. ANSI/ASTM E 140 states, "Conversion of hardness values should be used only when it is impossible to test the material under the conditions specified, and when conversion is made it should be done with discretion and under controlled conditions. Each type of hardness test is subject to certain errors, but if precautions are carefully observed,

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:50Z
Check the source to verify that this is the current version before use.

the reliability of hardness readings made on instruments of the indentation type will be found comparable. Differences in sensitivity within the range of a given hardness scale (for example, Rockwell B) may be greater than between two different scales or types of instruments. The conversion values now in use are only approximate and may be inaccurate for specific application.
Note 1.5 The values stated in inch-pound units are to be regarded as the standard."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - AR
Navy - OS
Air Force - 99

Preparing activity:
Army - AR

(Project 5315-0417)

Review activities:
Army - AT, ER, MI
DLA - IS
NSA - NS

User activities:
Army - AV, ME
Navy - MC, SA, SH

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T14:50Z
Check the source to verify that this is the current version before use.