MILITARY SPECIFICATION

COMBUSTIBLE CARTRIDGE CASE ASSEMBLY PARTS FOR CHARGE, PROPELLING, 155MM, M203A1

This Amendment forms a part of Military Specification MIL-C-70461C (AR), dated 4 April 1986, and is approved for use within the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of Department of Defense.

PAGE 2

2.1.2 Delete drawing "9435091" and substitute drawing "9345091".

PAGE 3

* Add the following new paragraphs:

"3.5.1 Assembly test. The mating surfaces between rear cap and igniter container shall be tight. The igniter container shall not be separated from the assembly when tested in accordance with 4.5.1.1.

3.5.2 Destructive pull test. The force of the adhesive bond between rear cap and igniter container shall be 200 lbs minimum when tested in accordance with 4.5.1.2."

PAGE 4

Add new paragraph:

"3.7.1 First article test (see 6.6.3). Test samples shall be withdrawn from the first lot produced by the contractor and tested in accordance with all the requirements of this specification and with Table IV. Until the first article test has been performed and found to be acceptable, the contractor is in no way authorized by the Government to initiate second lot production unless otherwise directed by the contracting officer."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

PAGE 8

4.4.2.2.1 Body, Molded:

Minor Category: Delete "Minor 202" and substitute new Minor Defect 202 as follows:

"202 Improper chamfer 0.65% 3.2 Visual"

PAGE 10

4.4.2.2.2 Igniter Container:

Minor Category: Delete "Minor 201" and substitute new Minor Defect 201 as follows:

"201 Improper chamfer o.65% 3.2 Visual"

PAGE 11

4.4.2.2.3 Rear Cap:

Minor Category: Delete "Minor 203" and susbstitute new Minor Defect 203 as follows:

"203 Improper chamfer of lip 0.65% 3.2 Visual"

PAGE 12

* Add the following new paragraphs:

"4.4.3.1.2 Assembly test. Each rear cap and igniter container shall be tested in accordance with 4.5.1.1. If the assesmbly fails the test, the rear cap and igniter container shall be rejected and removed from the lot (see 6.10)."

"4.4.3.1.3 Destructive pull test. Five (5) rear caps and five (5) igniter containers shall be randomly selected from the lot and tested in accordance with 4.5.1.2. Any failure shall be cause for lot rejection.

PAGE 13

* Add the following new paragraphs:

"4.5.1.1 Assembly test. The rear cap shall be assembled to igniter container. The assembly shall be lifted above the

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

surface by using fingers through the hole of the rear cap without touching the igniter container. Separation of the igniter container from the rear cap shall be cause for rejection of the assembly. The rejected assembly shall be removed from the lot for proper disposition (see 6.10).

"4.5.1.2 Destructive pull test. This test shall be performed after the adhesive bond between the igniter container and rear cap has had sufficiet time to set. The assembly shall be held in a suitable test fixture clamping on the igniter container. The test apparatus shall apply a longitudinal load distributed over 360° around the lip of the rear cap. Observation shall be for the force required for separation of the rear cap from the igniter container. If any sample fails to meet the specified requirement, the lot shall be rejected."

PAGE 14

4.5.3.2.2: Delete "70%" wherever it appears in this paragraph and substitute "90%".

PAGE 22

Add a new paragraph:

"6.6.3 First article test. The first article test is a one time qualification test for a new contractor to produce acceptable combustible cartridge case. Once a contractor has demonstrated the ability to produce acceptable combustible cartridge case the first article test may be waived by the contracting officer. The following test program shall be used for the first article test:

Table IV. First article test.

Test Phase	Temp. (°F)	No. of Control rds	No of Test rds	TECOM TOP
Uniformity	70		10	TOP-4-2-504
	145		10	TOP-4-2-504
	-60		10	TOP-4-2-504
Sequential	145	15	60	TOP-4-2-504
Environmental	160	15	60	TOP-4-2-504

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.

* Add the following new paragraph:

"6.10 Assembly test. The rear cap and igniter container which fail the assembly test may be used again and can be assembled to different rear cap or igniter container with the same interfix number. The failed rear cap and igniter container will not be considered acceptable until they pass the assembly test.

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320-A965)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:29Z
Check the source to verify that this is the current version before use.