INCH-POUND

MIL-DTL-55041/11A
2 October 2006
SUPERSEDING
MIL-S-55041/11
10 January 1984

DETAIL SPECIFICATION SHEET

SWITCHES, WAVEGUIDE, 1P2T, LATCHING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

Requirements for acquiring the switches described herein shall consist of this specification sheet and MIL-DTL-55041.





FIGURE 1. Switch configuration and schematic, part numbers M55041/11-001 through -005.

AMSC N/A FSC 5985

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:18Z
Check the source to verify that this is the current version before use.

SCHEMATIC




SHOWN IN LATCHING POSITION (POSITION 1)

NOTES:

1. Dimensions are in inches.
2. Metric equivalents (in millimeters) are given for general information only.
3. Round corners of case may be squared.
4. Unless otherwise specified, tolerances are ± .010 inch (0.25 mm) for three place decimals and ± .03 inch (0.8 mm) for two place decimals.
5. DC polarity must be observed.

FIGURE 1. Switch configuration and schematic, part numbers M55041/11-001 through -005 - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:18Z
Check the source to verify that this is the current version before use.




Inches	mm
.138	3.50
.19	4.8
.22	5.6
.62	15.7
.625	15.8
.75	19.05
.875	22.2
1.250	31.7
1.75	44.5
1.85	46.9
1.87	47.5
4.00	101.6

FIGURE 2. Switch configuration and schematic, part number M55041/11-006.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:18Z
Check the source to verify that this is the current version before use.

SCHEMATIC



SHOWN IN LATCHING POSITION (POSITION 1)

NOTES:

1. Dimensions are in inches.
2. Metric equivalents (in millimeters) are given for general information only.
3. Round corners of case may be squared.
4. Unless otherwise specified, tolerances are ± .010 inch (0.25 mm) for three place decimals and ± .03 inch (0.8 mm) for two place decimals.
5. DC polarity must be observed.

FIGURE 2. Switch configuration and schematic, part numbers M55041/11-006 - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:18Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and dimensions.

Dash number	A max	B ±.03	C ±.03	D ±.010	E ±.010	F ±.010	G ±.010	H max	J max	K	L	M	N
001	3.25	9.00	5.88	2.940	4.750	2.375	2.750	2.57	0.65	.250-20 x .40 deep	.250-20 x .50 deep	M3922/ 56-002	M85/1-041
002	3.25	7.50	4.25	2.125	3.500	1.750	2.000	2.57	0.65	.190-32 x .31 deep	.250-20 x .40 deep	M3922/ 57-001	M85/1-053
003	3.25	7.00	4.25	2.125	3.500	1.750	1.750	2.57	0.65	.250-20 x .40 deep	.190-32 x .30 deep	M3922/ 55-002	M85/1-065
004	2.25	5.10	2.38	1.190	2.000	1.000	1.245	2.07	0.65	.164-32 x .31 deep	.164-32 x .28 deep	M3922/ 53-003	M85/1-078
005	1.85	4.00	1.88	0.94	1.437	0.719	0.877	1.87	0.65	.138-32 x .22 deep	.164-32 x .25 deep	M3922/ 53-006	M85/1-091

TABLE II. Electrical performance characteristics.

Dash number	Figure number	Housing	Operating frequency range	Position indicator circuit	Interlock circuit	Nominal operating range	Pull-in voltage (less than)	Operating current (max) 3/
			GHz	amperes 3/		V dc	V dc	amperes
001	1	1/ 2/	2.60 - 3.95	0.1	N/A	28	20	1.5
002	1	1/ 2/	3.95 - 5.85	0.1	N/A	28	20	1.0
003	1	1/ 2/	5.85 - 8.20	0.1	N/A	28	20	1.0
004	1	1/ 2/	7.05 - 10.0	0.1	N/A	28	20	1.0
005	1	1/ 2/	12.4 - 18.00	0.1	N/A	28	20	1.0
006	2	1/ 2/	12.4 - 18.00	0.1	N/A	28	20	2.0

TABLE II. Electrical performance characteristics - Continued.

Dash number	Transient interference provisions	Isolation (min)	VSWR (max)	Insertion loss (max)	Switching time	Waveguide pressuri-zation	RF power handling capability (peak)	Life cycles (X1,000)	Weight (max)
		dB		dB	ms	$1b_f/in^2$	duty kW cycle		
001	yes	60	1.10:1	0.08	500	20	2200 33×10^{-3}	200	17 lbs
002	yes	60	1.10:1	0.08	500	20	1400 31×10^{-3}	200	9 lbs
003	yes	60	1.10:1	0.1	150	20	560 26×10^{-3}	200	8.3 lbs
004	yes	60	1.10:1	0.15	100	20	275 27×10^{-3}	200	2.3 lbs
005	yes	60	1.10:1	0.15	100	20	120 24×10^{-3}	200	1.3 lbs
006	yes	60	1.10:1	0.1	125	45	43 1×10^{-3}	500	1.5 oz

1/ Enclosed, sand- and dust-proof when waveguide flanges are capped.
2/ Rotor and housing of aluminum alloy.
3/ At 28 V dc and 20°C to 25°C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:18Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1, figure 2, and table I.

Power connectors: See figure 1 and figure 2.

Operation: Break before make.

Operating temperature range: -54°C to +95°C.

Electrical performance characteristics: See table II.

Part or identifying number (PIN): M55041/11- (and dash number from tables I and II).

Substitutability data: The switches covered by this specification sheet are substitutable for the user's or manufacturer's PIN specified in table III. This information in no way implies that the manufacturer's PIN or NSN is suitable as a substitute for the military PIN.

TABLE III. Substitutability data.

Dash number	Manufacturer's code	Commercial type	NSN 5985-
001	00471	33D08400	01-073-1529
002	00471	33D06400	01-235-7794
003	00471	33D04400	01-233-2561
004	81755	654VE4826-3	01-099-6113
004	00471	33D03400	01-099-6113
005	81755	C4715-1	00-009-3159
005	00471	33D00400	00-009-3159

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5985-2006-021)

Review activities:
Army - SM, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:18Z
Check the source to verify that this is the current version before use.