INCH-POUND

MIL-C-70508 (AR)
AMENDMENT 7
18 MARCH 1993
SUPERSEDING
AMENDMENT 6
30 March 1990

MILITARY SPECIFICATION

CARTRIDGE, 9MM, BALL, NATO, XM882

This Amendment forms a part of MIL-C-70508(AR), dated 7 February 1985, and is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title: Add, "(M882)" after "XM882".

1.1, Last line: Add "(M882)" after "XM882".

PAGE 2

2.1.2, under DRAWING 9345111: Add "(M882)" after "(XM882)".

2.2.1, Delete: "9354344 - Packaging and Marking, Cartridges, 9mm, Ball, NATO, XM882, Cartons, Box Ammunition, M2A1, Box Wirebound" and substitute, "9396206 - Packing and Marking for Box, Wirebound, for Cartridges, Small Caliber".

PAGE 3

3.6, second line: Delete "385" and substitute "375".

Add paragraph "3.8.1":

"3.8.1 Alternate accuracy requirement. The average mean radius of all ten round targets fired at a range of 50 yards from the muzzle shall not exceed 3.47 centimeters."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:35Z
Check the source to verify that this is the current version before use.

PAGE 4

Delete paragraph "3.12" in its entirety and substitute:

"3.12 Compressive force resistance. When subjected to a compressive force of 75 pounds, the average overall length of the sample cartridges shall not be less than 1.140 inches, and no individual cartridge shall be less than 1.125 inches."

PAGE 8

4.4.2.1:

* Delete:

"3.	No primer	100%	3.3	Visual
4.	Cocked primer	100%	3.3	Visual
5.	Inverted primer	100%	3.3	Visual"

Add under "CRITICAL":

"3.	Minimum propellant level (Dwg. 9345211, Note 4)	100%	3.3	Gage"

* Add after critical defects:

"SPECIAL:

a.	No primer	100%	3.3	Visual
b.	Cocked primer	100%	3.3	Visual
c.	Inverted primer	100%	3.3	Visual"

PAGE 11

TABLE II, Delete Note "3" in its entirety and substitute:

"3/ Function and casualty defects shall not exceed the acceptance percentages specified in Table III. When testing submachine guns, the number of cartridges specified at ambient temperatures shall be equally divided between horizontal and 80° depressed weapon firings. Failure of the cartridges to comply with the function and casualty requirements shall be cause for rejection of the lot, subject to the testing of a second sample consisting of double the quantity of cartridges used in the first sample. For those defects for which the allowable acceptance percentage in Table III is 0.00, the occurrence of a defect of this type in the second sample shall be cause for rejection of the lot. For those defects for which the allowable acceptance percentage is greater than 0.00, failure of the cartridges in the combined first and second sample to comply with the requirements of Table III shall be cause for rejection of the lot."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:35Z
Check the source to verify that this is the current version before use.

PAGE 13

4.5.6, End of paragraph: Add "Record the sample standard deviation of the mean radii for the ten targets".

PAGE 14

4.5.7.e, Delete "Model 4" and substitute: "Model 12/5".

Delete paragraph "4.5.7.1" in its entirety and substitute:

"4.5.7.1 Test weapons. Unless otherwise specified in the contract, the contractor shall furnish unaltered commercially equivalent pistols (weapons b. and c. listed in 4.5.7). Function and casualty testing with other weapon types shall be limited to those weapon types identified as government furnished in the contract. (See 6.1.c)"

Add paragraph "4.5.7.2":

"4.5.7.2 Reduced function and casualty testing. When five (5) successive production lots have successively met the function and casualty requirements in all required weapons, testing for function and casualty shall be reduced. Reduced tests shall consist of function and casualty testing one out of every ten (10) production lots in all specified weapon types. The lot to be tested shall be selected randomly by the government. The remaining nine (9) lots shall be function and casualty tested only in the M9, 9mm pistol. Failure of any lot to meet the function and casualty requirements shall result in reinstatement of lot-by-lot testing in all specified weapon types and the above procedure shall be repeated in returning to reduced inspection."

4.5.12, First line: Delete "proving ground" and substitute: "test facility or Government representative".

5.1, Last line: Delete "9354344" and substitute "9396206".

PAGE 15

Add under paragraph 6.1: "c. Provisions for supply, maintenance and disposition of function and casualty test weapons."

Add paragraph "6.4":

"6.4 International agreement. Certain provisions of this specification are the subject of international standardization agreement NATO STANAG 4090. When amendment, revision, or cancellation of this specification is proposed which will modify the international agreement concerned, the preparing

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:35Z
Check the source to verify that this is the current version before use.

activity will take appropriate action through international standardization channels including departmental standardization offices to change the agreement or make other appropriate accommodations."

The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-AE57)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:35Z
Check the source to verify that this is the current version before use.