MILITARY SPECIFICATION

GUARD, ROADWAY CROSSING, 6-INCH HOSELINE

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a roadway crossing guard.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-601	- Boxes, Wood, Cleated-Plywood.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4610

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

2.1.2 Other Government drawings. The following other Government drawings form a part of this specification to the extent specified herein.

DRAWINGS

ME

A2 13226E1576	- Roadway Crossing Guard, 6-Inch Hoseline.

(Copies of specifications, standards, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The roadway crossing guard (hereinafter called "guard") shall be in accordance with Drawing A2 13226E1576 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the guard. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or his designated representative.

3.2 First article first produced guard. The contractor shall furnish one or more guards as specified (see 6.2) for examination within the time frame specified (see 6.2) to provide that his production methods will produce guards that comply with the requirements of this specification. Examination shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

3.3 Materials. Materials shall be as specified herein and on the drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.4).

3.3.1 Material deteriorations prevention and control (MADPAC). The roadway crossing guard shall be fabricated from compatible materials, suitably finished, to provide protection from corrosion and other forms of material deterioration. Assurance shall be given in the form of a finish plan which clearly identifies the specific finish or treatment to be used on the various components and assemblies, to provide protection against the various forms of material deterioration in the applicable operating and storage environments to which they may be exposed.

3.3.2 Galvanic corrosion. Dissimilar metals as defined in MIL-STD-889 shall not be used in intimate contact without suitable protection to circumvent galvanic corrosion.

3.4 Identification marking. The guard shall be identified in accordance with MIL-STD-130.

3.5 Workmanship. The guards shall be free from burrs, sharp edges or corners, except when sharp edges or corners are required and are not deterimental to safety or cause damage to the hoseline.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First produced kit inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.5).

4.3 First produced guard inspection.

4.3.1 Examination. The first produced guard shall be examined as specified in 4.4.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

4.4.1 Examination. Each guard shall be examined as specified herein for the following defects. Presence of one or more defects shall be cause for rejection.

101. Dimensions not as specified.
102. Finish plan not adequate.
103. Material not as specified.
104. Identification marking missing, incomplete or illegible.
105. Workmanship not as specified.
106. Dissimilar metals not in compliance with MIL-STD-889.

4.5 Inspection of packaging.

4.5.1 Quality conformance inspection of pack.

4.5.1.1 Sampling. Sampling for inspection shall be in accordance with MIL-STD-105.

4.5.1.2 Examination. Samples selected in accordance with 4.5.1.1 shall be examined for the following defects. AQL shall be 2.5 percent defective.

107. Packing not as specified for level A.
108. Guards not bundled in quantities specified in the contract or order.
109. Bundle not tightly and compactly formed.
110. Bundle not secured through the center holes on each side.
111. Marking illegible, incomplete, incorrect, or missing.

5. PACKAGING

5.1 Packing. Packing shall be level A or commercial, as specified (see 6.2).

5.1.1 Level A. The guards shall be packed in a close-fitting box conforming to PPP-B-601, Overseas Type, Grade A, in quantities not to exceed the weight and dimensional limitations of the box specification. The guards shall be tightly nested together to form a compact bundle. Quantity bundled together shall be as specified (see 6.2). The bundle shall be secured through the center holes on each side with tying material of sufficient strength to prevent movement between the guards.

5.1.2 Commercial. Commercial packing shall be in accordance with MIL-STD-1188.

5.2 Marking (see 6.4). In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129, for military protection, and in accordance with MIL-STD-1188 for commercial protection.

6. NOTES

6.1 Intended use. The guard is intended for use with a 6-inch, lightweight, collapsible hoseline system.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Degree of packing required (see 5.1).
c. Number of guards to be bundled together (see 5.1.1).

6.3 First produced guard. Any changes or deviations of production guard from the approved first produced guard during production will be subject to the approval of the contracting officer. Approval of the first produced guard will not relieve the contractor of his obligation to furnish guards to this specification.

6.4 Marking for degree of protection. Since no preservation is required, the degree of protection marking for items packed level A shall be A/A.

6.5 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification (see 3.3).

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 4610-A082

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-G-53017(ME) Guard, Roadway Crossing, 6-Inch Hoseline

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1426 *1 OCT 76*

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
USA Mobility Equipment R & D Command
Attn: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:49Z
Check the source to verify that this is the current version before use.